Issue Date: 18th July 2016

Revision: 0.2

SAFETY DATA SHEET

Section 1 - PRODUCT IDENTIFIER/CHEMICAL IDENTITY

1.1 PRODUCT IDENTIFIER: 8 YR RED COOLANT PREMIX

1.2 PRODUCT CODE: COOLREDPMX

1.3 RELEVANT IDENTIFIED USES OF THE MIXTURE AND USES ADVISED AGAINST:

RELEVANT IDENTIFIED USES: Ready to use engine coolant

RESTRICTIONS ON USE: None known

1.4 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:

SUPPLIER NAME: PENRITE OIL Company Pty Ltd (ABN: 25005 001 525)

ADDRESS (Australia): 110-116 Greens Rd, Dandenong South, VIC, Australia, 3175

TELEPHONE (Australia): 1300 736 748; +61 3 9801 0877; Fax 1800 736 748

ADDRESS (New Zealand): 75 Lady Ruby Dr, East Tamaki, Auckland, New Zealand, 2013

TELEPHONE (New Zealand): 0800 533 698; Fax 0800 533 698

EMAIL: <u>tech@penriteoil.com</u> (Aust and NZ)

1.5 EMERGENCY TELEPHONE: Australia: 1300 736 748 New Zealand: 0800 533 698

Poisons information Centre: Australia: 131 126 New Zealand: 0800 764 766

1.6 HSNO APPROVAL NUMBER: HSR002606

HSNO GROUP TITLE: Lubricants, Lubricant Additives, Coolants and Anti-Freeze

Agents (Subsidiary Hazard) Group Standard, 2006

Section 2 - HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE HAZARDOUS CHEMICAL:

GHS CLASSIFICATION HAZARD CLASS AND CATEGORY: Under the model work Health and Safety Regulations, the product would be rated as hazardous: Acute Toxicity – Oral Cat. 4

2.2 LABEL ELEMENTS INCLUDING PRECAUTIONARY STATEMENTS:

SIGNAL WORD: Warning

PICTOGRAMS: Exclamation mark

HAZARD STATEMENTS: H302 - Harmful if swallowed.

PRECAUTIONARY STATEMENTS:

PREVENTION: P102 - Keep out of reach of children.

P103 - Read label before use.

P264 - Wash hands with soap and water thoroughly after handling.

P270 - Do not eat drink or smoke when using this product.

Issue Date: 18th July 2016

Revision: 0.2

RESPONSE: P101 - If medical advice is needed, have product container or label

at hand.

P301+P312 - IF SWALLOWED: Call a POISON CENTRE or doctor if

you feel unwell. P330 - Rinse mouth.

STORAGE: There are no storage statements

DISPOSAL: P501 - Dispose of contents/container in accordance with local

regulations.

2.3 OTHER HAZARDS: The product is rated as Harmful if swallowed. Ethylene glycol poisoning can be fatal after ingestion. Ingestion of large quantities can cause kidney damage. The product may be mildly irritating to the respiratory system and eyes. The Ethylene glycol constituent has the Skin Annotation assigned to it. This means absorption through the skin may be a significant source of exposure. As for all chemical products, persons should not expose open wounds, cuts, abrasions or irritated skin to this material.

Section 3 - COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS	CAS	CONC (%W/W)	GHS	Code
Ethanediol [Ethylene glycol]	107-21-1	30<60	Acute Tox. Cat. 4	H302
Denatonium Benzoate	3734-33-6	10mg/kg	Not Applicable	
Fluro Orange Scarlet	N/A	50 ppm	Not Applicable	
Other non hazardous ingredients		To 100	Not Applicable	

Section 4 - FIRST AID MEASURES

4.1 DESCRIPTION OF NECESSARY FIRST AID MEASURES:

INGESTION: Rinse mouth out and give a glass of water. Never give fluid to a person exhibiting decreased awareness. Do NOT induce vomiting. Seek medical advice immediately. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. For advice, contact a Poisons Information Centre (Phone Australia 131 126; New Zealand 0800 764 766) or a doctor at once.

EYE: If in eyes, hold eyelids apart and flush the eye immediately with large amounts of running water. Continue flushing for at least 15 minutes or until advised to stop by a Doctor. Check for contact lenses. If there are contact lenses, these should be removed after several minutes of rinsing by the exposed person or medical personnel if it can be done easily. After flushing, if irritation develops or persists, seek medical assistance.

SKIN CONTACT: If skin or hair contact has occurred remove an contaminated clothing and footwear, wash skin or hair thoroughly with soap and water. If irritation develops or persists, consult a Doctor.

INHALATION: If affected, remove the patient from further exposure into fresh air, if safe to do so. If providing assistance, avoid exposure to yourself — only enter contaminated environments with adequate respiratory equipment. Once removed, lay patient down in a well-ventilated area and reassure them whilst waiting for medical assistance. If not breathing, provide artificial respiration and seek immediate medical assistance. If unconscious, place in

Issue Date: 18th July 2016

Revision: 0.2

a recovery position and seek immediate medical assistance. If irritation develops or persists, consult a Doctor.

PROTECTION FOR FIRST AIDERS: No personnel shall place themselves in a situation that is potentially hazardous to themselves. Assess the scenario for PPE requirements before entering. Assess environment for vapours before entering. Do not enter contaminated area without a respirator. As the product contains Ethylene glycol, if the person has ingested the product, do not use direct mouth-to-mouth resuscitation techniques. Always ensure that you are wearing gloves when dealing with first aid procedures involving chemicals and/or blood. **FIRST AID FACILITIES:** Eye wash fountain and safety showers are recommended in the area where the product is used.

4.2 MOST IMPORTANT SYMPTOMS & EFECTS, BOTH ACUTE & DELAYED, CAUSED BY EXPOSURE:

ACUTE: The product is rated as harmful by ingestion. Ingestion of large amounts of the product could lead to acute Ethylene glycol poisoning. Ingestion or inhalation of vapours may lead to irritation of the mouth and respiratory tract. Symptoms may include a burning sensation in the nose and throat, coughing or difficulty breathing. Ingestion may lead to nausea and diarrhoea. Eye contact may lead to localised burning, redness and tearing. Skin contact may lead to redness or itching. If material is aspirated into the lungs it may exhibit as coughing, wheezing, congestion or fever.

CHRONIC: Skin contact may aggravate/exacerbate existing skin conditions, such as dermatitis. Ingestion of large quantities of Ethylene glycol may cause kidney damage.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NECESSARY: Treat symptomatically. Ingestion of large amounts of Ethylene glycol can cause central nervous system depression and metabolic acidosis. Consider removal by gastric lavage after endotracheal intubation. Do not use mechanical or pharmacological means of emesis. Any material aspirated during vomiting may produce lung injury. If vomiting has occurred after ingestion, the patient should be monitored for difficulty in breathing, as adverse effects of aspiration into the lungs may be delayed for up to 48 hours. Monitor kidney function as large quantities may cause kidney damage. According to the IUCLID Report, in human Ethylene glycol poisoning cases ethanol/alkali/diuretic infusion antidotal treatment has been successful.

Section 5 - FIRE FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA:

SUITABLE MEDIA: Use extinguishing media appropriate for surrounding fire. Use carbon dioxide, alcohol resistant foam, dry chemical or water fog. Spray down fumes resulting from fire.

UNSUITABLE MEDIA: Avoid using full water jet directed at residual material that may be burning.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

COMBUSTION HAZARDS: Combustion may produce oxides of carbon as well as smoke and irritating vapours.

5.3 ADVICE FOR FIRE FIGHTERS:

Issue Date: 18th July 2016

Revision: 0.2

FIRE: This product is a combustible liquid under conditions of use with a Typical Flash Point of > 120°C. Keep storage tanks, pipelines, fire exposed surfaces, etc. cool with water spray.

HAZCHEM CODE: Not Applicable.

EXPLOSION: No information to indicate that the product is an explosion hazard. Extinguish all sources of flame or spark. Closed containers may explode when exposed to extreme heat.

PROTECTIVE EQUIPMENT: In the event of a fire, wear full protective clothing and self-contained breathing equipment with full-face piece operated in the pressure demand or other positive pressure mode.

Section 6 - ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

PERSONAL PROTECTION: For small spills wear nitrile gloves, glasses/goggles, boots and full-length clothing. During routine operation a respirator is not required. However, if mists or vapours are generated, an approved organic vapour/particulate respirator is required. For large spills, or in confined spaces, a full chemically resistant body suit is recommended and the atmosphere must be evaluated for oxygen deficiency. If in doubt about potential oxygen deficiency wear self-contained breathing apparatus.

CONTROL MEASURES: Ventilate area and extinguish and/or remove all sources of ignition. Stop the leak if safe to do so. CAUTION: The spilled product will be slippery. Avoid contact with the spilled material.

EMERGENCY PROCEDURES: In the event of a spill or accidental release, notify the relevant authorities in accordance with all applicable regulations.

6.2 ENVIRONMENTAL PRECAUTIONS:

SPILL ADVICE: Do not allow product to enter drains, surface water, sewers or watercourses – inform local authorities if this occurs.

6.3 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

CONTAINMENT: Contain the spill and absorb with a proprietary absorbent material, sand or earth. For large spills prepare a bund/barrier/dyke ahead of the spill to confine the spill and allow later recovery. If there is the possibility of spills to enter drains, surface water, sewers or watercourses ensure bunding, or that drains are covered, to minimise the potential for this to occur.

CLEANING PROCEDURES: Having contained the spill, as mentioned above collect all material quickly and place use absorbent in suitable containers. Follow local regulations for the disposal of waste. For large spills that have been bunded, the material can be pumped into vessels and returned for reprocessing or destruction. Personnel must wear gloves, goggles or glasses, boots and full-length clothing during cleaning procedures. Wash contaminated area and objects with detergent and water after spill has been cleared. Rinse the cleaned area with water. Do not allow wash water or rinsings to enter drains, surface water, sewers or water courses.

Issue Date: 18th July 2016

Revision: 0.2

Section 7 - HANDLING AND STORAGE, INCLUDING HOW THE CHEMICAL MAY BE SAFELY USED

7.1 PRECAUTIONS FOR SAFE HANDLING:

SAFE HANDLING: Avoid contact with the product by using appropriate protective equipment such as gloves, glasses or goggles and full-length clothing. Prevent small spills and leakage to avoid slip hazards. Properly dispose of any contaminated rags or cleaning materials in order to prevent fire hazards. Eating, drinking, and smoking should be prohibited in the area where this material is handled, stored and processed. Worker should follow good personal hygiene practices, such as washing hands before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Keep containers tightly closed when not in use. Prevent product from entering waterways, drains or sewers.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATABILITIES:

SAFE STORAGE: Store in a dry, well ventilated area away from direct sunlight, ignition sources, oxidising agents, foodstuffs and clothing. Keep containers closed when not in use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

INCOMPATIBILITIES: Oxidizing substances including strong acids, strong caustics, aliphatic amines, isocyanates and chlorosulfonic acid.

Section 8 - EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1 EXPOSURE CONTROL MEASURES:

EXPOSURE LIMIT VALUES: Exposure standards for the product have not been established. However, in the operation of certain equipment or at elevated temperatures, if ethylene glycol vapours or mists are generated the following Exposure Standard should be observed:

Ethylene glycol as Vapour (Skin annotation)

TWA: 20 ppm, 52 mg/m³ STEL: 40 ppm, 104 mg/m³

Ethylene glycol as Particulate (Skin annotation)

TWA: 10mg/m³

- 8.2 BIOLOGICAL MONITORING: No data available
- **8.3 CONTROL BANDING:** No data available
- **8.4 ENGINEERING CONTROLS:** Special ventilation is not normally required. However, in the enclosed spaces or at elevated temperatures mists or vapour may be generated and exhaust ventilation may be required to maintain airborne concentration levels below the exposure standards or below a level considered irritating by individuals.

8.5 INDIVIDUAL PROTECTION MEASURES:

EYE & FACE PROTECTION: Wear safety glasses/goggles to avoid eye contact when handling. If there is a risk of splashing during use, a full face shield is recommended. Use eye protection in accordance with AS 1336 and AS 1337.

SKIN (HAND) PROTECTION: If there is the chance of contact with the material wear gloves to provide hand protection. Natural rubber, Neoprene, Nitrile or PVC gloves are recommended.

Issue Date: 18th July 2016

Revision: 0.2

SKIN (CLOTHING) PROTECTION: During normal operating procedures, long sleeved clothing is recommended to avoid skin contact. Soiled clothing should be washed with detergent prior to re-use.

RESPIRATORY PROTECTION: During routine operation a respirator is not required. However, if mists or vapours are generated, an approved half face organic vapour/particulate respirator is required. Use respirators in accordance with AS 1715 and AS 1716.

THERMAL PROTECTION: Not Applicable

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 PHYSICAL AND CHEMICAL PROPERTIES:

APPERANCE: Viscous amber liquid

ODOUR: Typical lubrication oil odour.

ODOUR THRESHOLD:

PH:

Not applicable

MELTING/FREEZING POINT:

Not applicable

Not applicable

No data available

BOILING RANGE (°C):

No data available

FLASH POINT (°C): Typically >120 °C for Ethylene glycol

EVAPORATION RATE: No data available

FLAMMABILITY LIMITS (%): Ethylene glycol LEL: 3.4%; UEL: 15.1

VAPOUR PRESSURE (mmHg): Negligible (Air = 1.0)
VAPOUR DENSITY: No data available

DENSITY (g/mL @ 15 °C): Typically 1.069 – 1.073
SOLUBILITY IN WATER (g/L): Completely miscible

PARTITION COEFFICIENT: No data available for n-octanol/water

AUTO-IGNITION TEMP (°C): 420 °C for Ethylene glycol

VISCOSITY (cSt @ 40 °C): No data available No data available VISCOSITY (cSt @ 100 °C): No data available

Section 10 - STABILITY AND REACTIVITY

- **10.1 REACTIVITY:** The product does not pose any further reactivity hazards other than those listed in the following sub-sections
- **10.2 CHEMICAL STABILITY:** Stable under recommended storage and handling conditions (see section 7)
- **10.3 POSSIBILITY OF HAZARDOUS REACTION:** Keep away from strong oxidising agents, such as strong acids, chlorates, nitrates and peroxides. Hazardous polymerisation does not occur.
- 10.4 CONDITIONS TO AVOID: Observe the usual pre-cautionary measures for handling chemicals. Do not heat the container or leave the container open when not in use. Avoid sources of ignition.
- **10.5 INCOMPATIBLE MATERIALS:** Strong oxidizing agents including concentrated acids as well as strong bases, acid chlorides, isocyanates and acid anhydrides. Do not store in aluminium or galvanised containers.

Issue Date: 18th July 2016

Revision: 0.2

10.6 HAZARDOUS DECOMPOSITION PRODUCTS: Hazardous decomposition products are not expected to form during normal storage requirements. See Section 5.2 for Hazardous Combustion products.

Section 11 - TOXICOLOGICAL INFORMATION

- **11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:** The product is a mixture and test data is not available for the product as a whole.
- 11.2 IF SWALLOWED: The product is a Schedule 5 Poison and rated as harmful if swallowed. Acute poisoning with Ethylene glycol includes central nervous system effects, cardiopulmonary effects, usually attributed to metabolic acidosis, and finally renal failure. Neurological effects incorporating the facial nerves with visual impairment have occurred after Ethylene glycol ingestion by humans according to the IUCLID Report. The clinical effect of ingesting high doses of Ethylene glycol appears in 3 stages (IUCLID Report). The first twelve hours involves the central nervous system and is characterised by the appearance of drunkenness, nausea, vomiting, coma and then convulsions. There are also changes in blood cellular composition and urine profile, mild drops in blood pressure, rapid heartbeat, slight fever, depressed reflexes, eye effects and possibly seizures. The second stage involves the heart and lungs. The commonly observed effects include rapid breathing and heart beat, mild drops in blood pressure, blue colouration of the skin, possibly fluid in the lungs, pneumonia, enlarged or congested heart. Death in this stage starts 24 to 72 hours after ingestion. The final stage is kidney failure, with oxalic acid being found in the urine. The Ethylene glycol Estimated Lethal Dose (Human) is 100 mL with the Calculated Mean Lethal Dose being 1.2 - 1.5 g/kg, oral, adults. The Oral (human) LDLo is 398mg/kg. The Oral (child) TDLo: 5500 mg/kg.
- 11.3 SKIN/CORROSION/IRRITATION: This product is not expected to exhibit Dermal Corrosivity/Irritation according to OECD Test 404, based on the available data and the known hazards of the components. May be mildly irritating to the skin. The Ethylene glycol constituent has the Skin Annotation assigned to it. This means absorption through the skin may be a significant source of exposure. Correct handling procedures incorporating appropriate protective clothing and gloves should minimise the risk of skin absorption and irritation. People with pre-existing skin conditions, such as dermatitis, should take extreme care so as not to exacerbate the condition. The following RTECS data was reported for Ethylene glycol: Skin (Rabbit): 555 mg (open) mild.
- 11.4 SERIOUS EYE DAMAGE/IRRITATION: This product is not expected to exhibit Eye Irritation or Serious Damage/ Corrosivity according to OECD Test 405, based on the available data and the known hazards of the components. May be mildly irritating to the eyes. Symptoms may include localised burning, redness and tearing. Correct handling procedures incorporating appropriate eye protection should minimise the risk of eye irritation. The following RTECS data was reported for Ethylene glycol:

Eye (Rabbit): 100 mg/1 hr - mild Eye (Rabbit): 500 mg/24 hr - mild

Eye (Rabbit): 1,440 mg/6 hr - moderate

11.5 RESPIRATORY OR SKIN SENSITISATION: This product is not expected to be a skin sensitiser according to OECD Test 406, based on the available data and the known hazards of the components. This product is not expected to be a respiratory tract sensitiser, based on the available data and the known hazards of the components.

Issue Date: 18th July 2016

Revision: 0.2

11.6 GERM CELL MUTAGENICITY: This product is not expected to be mutagenic according to tests such as OECD Tests 471, 475, 476, 478 and 479, based on the available data and the known hazards of the components. However, studies have shown Ethylene glycol to be mutagenic to rat cells.

- **11.7 CARCINOGENICITY:** This product is not expected to be a carcinogen according to OECD test 451, based on the available data and the known hazards of the components.
- 11.8 REPRODUCTIVE TOXICITY: This product is not expected to be a reproductive hazard according to tests such as OECD Tests 414 and 421, based on the available data and the known hazards of the components. However, Ethylene glycol has been shown to cause birth defects in rat studies.
- 11.9 SPECIFIC TARGET ORGAN TOXICITY (STOT) SINGLE EXPOSURE: There is no data available for the product as a whole. As mentioned, acute poisoning with Ethylene glycol includes central nervous system effects, cardiopulmonary effects, usually attributed to metabolic acidosis, and finally renal failure. Inhalation of vapours or mist (generated at elevated temperatures or by mechanical action) may cause irritation to the nose and throat. At mist concentrations of 80ppm Ethylene glycol, a 1991 ACGIH report nominates that coughing and tracheal burning became intolerable. Inhalation of vapours or mist may cause drowsiness or dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of coordination and vertigo. This is likely to occur at temperatures higher than normally expected when using the product.
- **11.10 SPECIFIC TARGET ORGAN TOXICITY (STOT) REPEATED EXPOSURE:** This product is not expected to cause organ damage from prolonged or repeated exposure according to tests such as OECD Tests 410 and 412, based on the available data and the known hazards of the components. Evidence from animal studies indicates that repeated or prolonged exposure to Ethylene glycol could lead to central nervous system, liver and kidney side effects.
- **11.11 ASPIRATION HAZARD:** This product is not expected to be an aspiration hazard, based on the available data and the known hazards of the components. However, the manufacturer recommends that if swallowed, do NOT induce vomiting. If vomiting has occurred after ingestion the person should be observed to ensure that aspiration into the lungs has not occurred.
- 11.12 OTHER INFORMATION: INFORMATION: Ethylene glycol has been shown to produce teratogenic effects in mice when high doses were ingested. Though there is animal data that suggests that Ethylene glycol has some toxicological effects in regards to reproductive effects, mutagenicity and teratogenicity, the results were not considered relevant to normal industrial use of the product to require it to be rated. Though this highlights the fact that care should be taken when handling the product.

Section 12 - ECOLOGICAL INFORMATION

- **12.1 ECOTOXICITY:** There is no data available for the product as a whole. The product should not be discharged to sewer or waterways. Data reported for Ethylene glycol has the Fish $LC_{50}(96 \text{ hr})$ as 4,100 18,500 mg/L and Algae $LC_{50}(72 \text{ hr})$ as 180,000 mg/L.
- **12.2 PERSISTENCE & DEGRADABILITY:** Based on the available data and the known hazards of the components and similar products the product is expected to be readily biodegradable. Major

Issue Date: 18th July 2016

Revision: 0.2

constituents are expected to be inherently biodegradable. Ethylene glycol is expected to be readily biodegradable (OECD 301A > 70% DOC Reduction).

- **12.3 BIOACCUMULATIVE POTENTIAL:** No information is available for the product as a whole.
- **MOBILITY IN SOIL:** There is no data available for the product as a whole. Ethylene glycol is not expected to evaporate from the soil surface. Ethylene glycol has little or no capacity to bind to soil and will be mobile. The log Pow of Ethylene glycol is nominated as between -1.93 and -1.36
- **12.5 OTHER ADVERSE EFFECTS:** There is no data available for the product as a whole. The product is miscible in water.

Section 13 - DISPOSAL CONSIDERATION

13.1 DISPOSAL METHODS:

PRODUCT: The product should not be released to the environment, so any unused material should be recycled wherever possible or be disposed of as hazardous waste at an appropriate collection depot. Spilled product that cannot be recovered should be absorbed and then shovelled into a suitable waste container, such as a plastic drum and then be treated as a solid waste. Follow Government regulations for disposal of such waste. All unused, waste or spilled product must be taken for recycling or disposal by suitably licensed contractors in accordance with Government regulations.

CONTAINERS: Empty containers may contain residual oil. They should be completely drained and then stored until reconditioned or disposed of. Empty drums should be taken for recycling or disposal through suitably licensed contractors in accordance with Government regulations. Where the containers are of metal construction they should not be pressurised, cut by a grinder, welded, brazed, soldered, drilled or exposed to heat, flames or other sources of ignition. Closed metal containers when exposed to such conditions/treatment may explode causing serious injury or death.

Section 14 - TRANSPORT INFORMATION

This product is not regulated for land, sea or air transportation (HS Code: 3820.00.00).

14.1 LAND (ADG Code): Not applicable **UN NUMBER:** Not applicable **UN PROPER SHIPPING NAME:** Not applicable TRANSPORT HAZARD CLASS(ES): Not applicable **PACKAGING GROUP:** Not applicable **ENVIRONMENTAL HAZARDS:** Not applicable **SPECIAL PRECAUTIONS FOR USER:** Not applicable **HAZCHEM CODE:** Not applicable 14.2 SEA (IMDG): Not applicable

UN NUMBER:

UN PROPER SHIPPING NAME:

TRANSPORT HAZARD CLASS(ES):

PACKAGING GROUP:

Not applicable

Not applicable

Issue Date: 18th July 2016

Revision: 0.2

ENVIRONMENTAL HAZARDS: Not applicable **SPECIAL PRECAUTIONS FOR USER:** Not applicable 14.3 AIR (IATA): Not applicable Not applicable **UN NUMBER: UN PROPER SHIPPING NAME:** Not applicable TRANSPORT HAZARD CLASS(ES): Not applicable **PACKAGING GROUP:** Not applicable **ENVIRONMENTAL HAZARDS:** Not applicable **SPECIAL PRECAUTIONS FOR USER:** Not applicable

Section 15 - REGULATORY INFORMATION

15.1 SAFETY. HEALTH AND ENVIRONMENTAL REGULATIONS:

APPLICABLE REGULATONS:

SUSMP: Schedule 5

AICS: All ingredients are listed in the AICS list

MONTREAL PROTOCOL:

STOCKHOLM CONVENTION:

ROTTERDAM CONVENTION:

Not applicable

Not applicable

Not applicable

INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS

(MARPOL): Not determined

OTHER REGULATORY INFORMATION:

GHS CLASSIFICATION HAZARD CLASS & CATEGORY AND HAZARD STATEMENT:

Acute Toxicity - Oral Cat. 4; H302 - Harmful if swallowed

HSNO APPROVAL NUMBER: HSR002606

HSNO GROUP TITLE: Lubricants, Lubricant Additives, Coolants and Anti-

Freeze Agents (Subsidiary Hazard) Group Standard,

2006.

Section 16 - ANY OTHER RELEVANT INFORMATION

16.1 SDS INFORMATION:

16.2 Date of SDS Preparation: 18th July 2016

16.3 REVISION CHANGES: Update Aust/NZ address details (Sect.1), Rev 0.2

16.4 ACRONYMS:

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

CAS Number Chemical Abstract Service Registry Number

EINECS European Inventory of Existing Commercial Chemical Substances

UN Number United Nations Number

OSHA Occupational Safety and Health Administration

ACGIH American Conference of Governmental Industrial Hygienists

IMDG International Maritime Dangerous Goods
IATA International Air Transport Association

IUCLID International Uniform Chemical Information Database

RTECS Registry of Toxic Effects of Chemical Substances

Issue Date: 18th July 2016

Revision: 0.2

% W/W Percent weight for weight

OECD Organisation for Economic Co-Operation and Development

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail

HAZCHEM CodeEmergency action code of numbers and letters which gives information to

emergency services

NOHSC National Occupational Health and Safety Commission

AICS Australian Inventory of Chemical Substances

TWA Time – Weighted Average STEL Short term Exposure Limit

HSNO Hazardous Substances and New Organisms Act 1996

GHS Globally Harmonised System of Classification and Labelling of Chemicals

WHS Work Health and Safety

PPE Personal Protective Equipment.