SECTION 1 – IDENTIFICATION: PRODUCT IDENTIFIER/CHEMICAL IDENTITY

1.1 PRODUCT IDENTIFIER: Brake and Parts Cleaner 20L

1.2 PRODUCT CODE: MABAPC020

1.3 RELEVANT IDENTIFIED USES OF RELEVANT IDENTIFIED USES:	THE MIXTURE AND USES ADVISED AGAINST: Brake and parts cleaner.
RESTRICTIONS ON USE:	None known.
1.4 DETAILS OF THE SUPPLIER OF 1	THE SAFETY DATA SHEET:
SUPPLIER NAME:	PENRITE OIL Company Pty Ltd (ABN: 25005 001 525),
ADDRESS (Australia):	110-116 Greens Road, Dandenong South VIC, Australia, 3175
TELEPHONE NUMBER (Australia):	1300 736 748; +61 3 9801 0877 (Int); Fax: 1800 736 748
ADDRESS (New Zealand): TELEPHONE NUMBER (New Zealand E-MAIL:	75 Lady Ruby Drive, East Tamaki, Auckland, New Zealand, 2013):0800 533 698; Fax: 0800 533 698 <u>tech@penriteoil.com</u> (Aust and NZ)
1.5 EMERGENCY TEL. NUMBER:	Australia: 1300 736 748; New Zealand: 0800 533 698 (Poisons Information Centre (Aust 131 126; NZ 0800 764 766)
1.6 HSNO DETAILS: HSNO APPROVAL NUMBER: HSNO GROUP TITLE:	HSR002528. Cleaning Products (Flammable) Group Standard 2006

SECTION 2 – HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE HAZARDOUS CHEMICAL: GHS CLASSIFICATION HAZARD

CLASS & CATEGORY: Under the Model Work Health and Safety Regulations the product would be rated as hazardous: Flammable Liquids - Category 2 Aspiration Hazard - Category 1 Skin Corrosion/Irritation - Category 2 Serious Eye Damage/Irritation - Category 2A Specific Target Organ Toxicity (Single Exposure) - Category 3 Chronic Aquatic Toxicity - Category 2.

2.2 LABEL ELEMENTS INCLUDING PRECAUTIONARY STATEMENTS:

SIGNAL WORD: PICTOGRAMS:



HAZARD STATEMENTS:

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

SECTION 2 – HAZARD(S) IDENTIFICATION Continued

PRECAUTIONARY STATEMENTS:

PRECAUTIONARY STATEME	
PREVENTION:	P102 - Keep out of reach of children.
	P103 - Read label before use.
	P210 - Keep away from heat, sparks, open flames and hot surfaces - No
	smoking.
	P233 - Keep container tightly closed.
	P240 - Ground/Bond container and receiving equipment.
	P241 - Use explosion-proof electrical, ventilating, lighting equipment.
	P242 - Use only non-sparking tools.
	P243 - Take precautionary measures against static discharge.
	P261 - Avoid breathing mist, vapours and spray.
	P264 - Wash hands thoroughly after handling.
	P271 - Use only outdoors or in a well-ventilated area.
	P273 - Avoid release to the environment.
	P280 - Wear protective gloves/eye protection/face protection.
RESPONSE:	P101 - If medical advice is needed, have product container or label at hand.
	P301+P310 - IF SWALLOWED: Immediately call a POISON CENTRE or
	doctor/physician.
	P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
	P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all
	contaminated clothing. Rinse skin with water/shower.
	P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a
	position comfortable for breathing.
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several
	minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P312 - Call a POISON CENTRE or doctor/physician if you feel unwell.
	P331 - Do NOT induce vomiting.
	P332+P313 - If skin irritation occurs: Get medical advice/attention.
	P337+P313 - If eye irritation persists: Get medical advice/attention.
	P362 - Take off contaminated clothing and wash before reuse.
	P370+P378 - In case of fire: Use carbon dioxide, alcohol resistant foam, dry
	chemical or water spray for extinction.
	P391 - Collect spillage.
STORAGE:	P233 - Keep container tightly closed.
	P403+P235 - Store in a well-ventilated place. Keep cool.
	P405 - Store locked up.
DISPOSAL:	P501 - Dispose of contents/container in accordance with local regulations.
2.3 OTHER HAZARDS:	Due to the presence of solvents there is a possibility of organ system damage.
	The product is a highly flammable liquid and will potentially form
	flammable/explosive mixtures in air. There may be static discharge issues with
	the product that could lead to a fire. As for all chemical products, persons
	should not expose open wounds, cuts, abrasions or irritated skin to this
	material.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS	CAS NUMBER	Concentration % W/W	GHS Classification*
Pentane, 2-methyl- (Isohexane)	107-83-5	> 60%	Flam Liq 2 - H225 Asp Haz 1 - H304 Skin Irrit 2 - H315 STOT SE 3 - H336
2-Propanol	67-63-0	10% - 20%	Chron Aq Tox 2 - H411 Flam Liq 2 - H225 Eye Irrit 2A - H319 STOT SE 3 - H336
Cyclopentane	287-92-3	< 10%	Flam Liq 2 - H225 Chron Aq Tox 3 - H412
Not Applic = Not Applicable * Plea	ase see Section 15 of this	SDS for full text descript	ion of the Label Elements.

SECTION 4 – FIRST AID MEASURES

4.1 DESCRIPTION OF NECESSARY FIRST AID MEASURES:

INGESTION:	Rinse mouth out with water. If swallowed, do NOT induce vomiting. For advice, contact the Poisons Information Centre (phone Australia 131 126; New Zealand 0800 764 766) or a doctor at once. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Within 6 hours of ingestion, if delayed symptoms, such as a fever greater than 38.3°C, shortness of breath, chest congestion or continued coughing/wheezing occurs transport immediately to a medical facility. As the product is hydrocarbon based and of low viscosity (~2.3cSt @ 40°C), if ingested seek urgent medical assistance.
EYE:	If in eyes, hold eyelids apart and flush the eye immediately with large amounts of running water. Continue flushing for at least 15 minutes or until advised to stop by a Doctor. Check for contact lenses. If there are contact lenses, these should be removed after several minutes of rinsing by the exposed person or medical personnel if it can be done easily. As the product is rated as an eye irritant, after flushing, it is recommended that you seek medical assistance taking this Safety Data Sheet or the container with you.
SKIN CONTACT:	If skin or hair contact has occurred remove any contaminated clothing and footwear, wash skin or hair thoroughly with soap and water. As the product is rated as a skin irritant, after washing if skin irritation occurs, it is recommended that you seek medical advice/attention taking this Safety Data Sheet with you.
	If affected, remove the patient from further exposure into fresh air, if safe to do so. If providing assistance, avoid exposure to yourself - only enter contaminated environments with adequate respiratory equipment, once environment has been assessed for flammable vapours. Once removed, lay patient down in a well-ventilated area and reassure them whilst waiting for medical assistance. If the person feels unwell and symptoms, such as dizziness or uncoordination occur, contact the Poisons Information Centre (phone Australia 131 126; New Zealand 0800 764 766) whilst waiting for medical assistance. If not breathing, provide artificial respiration and seek immediate medical assistance. If unconscious, place in a recovery position and seek immediate medical assistance. If irritation develops or persists, consult a Doctor.
PROTECTION FOR FIRST	
AIDERS:	No personnel shall place themselves in a situation that is potentially hazardous to themselves. Assess the scenario for PPE requirements before entering. Assess environment for flammable vapours before entering. Never enter an environment with a flammable atmosphere. Do not enter contaminated area without a respirator or Self Contained Breathing Apparatus once you have assessed the atmosphere. As the product is hydrocarbon based and of low viscosity, if the person has ingested the product, do not use direct mouth-to-mouth resuscitation techniques. Always ensure that you are wearing gloves when dealing with first aid procedures involving chemicals and/or blood.
FIRST AID FACILITIES:	Eye wash fountain and safety showers are recommended in the area where the product is used.
4.2 MOST IMPORTANT SYMF ACUTE:	PTOMS & EFFECTS, BOTH ACUTE & DELAYED, CAUSED BY EXPOSURE: The product is rated as a skin and eye irritant by calculation. Skin contact may lead to redness or itching. Eye contact may lead to localised burning, redness, pain, swelling and tearing. Vapours may cause drowsiness or dizziness. Ingestion or inhalation of vapours may lead to irritation of the mouth and respiratory tract. Symptoms may include a burning sensation in the nose and throat, coughing or difficulty breathing. Ingestion may lead to nausea and diarrhoea. The product is an aspiration hazard. If material is aspirated into the lungs it may exhibit as coughing, wheezing, congestion or fever.
CHRONIC:	Skin contact may aggravate/exacerbate existing skin conditions, such as

dermatitis.

SECTION 4 – FIRST AID MEASURES Continued

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NECESSARY:

ADVICE TO DOCTOR: Treat symptomatically. As the product is hydrocarbon based and of low viscosity, if vomiting has occurred after ingestion, the patient should be monitored for adverse effects to ensure that the product has not aspirated into the lungs. Small amounts of this product aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary oedema. Inhalation of high vapour concentrations may cause central nervous system depression.

SECTION 5 – FIRE FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA:

SUITABLE MEDIA:	Use extinguishing media appropriate for surrounding fire. Use carbon dioxide,
	alcohol resistant foam, dry chemicals or water spray. Spray down fumes
	resulting from fire.

UNSUITABLE MEDIA: Avoid using full water jet directed at residual material that may be burning. Water may cause splattering on hot residues.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

COMBUSTION HAZARDS: Combustion may produce oxides of carbon, as well as smoke and irritating vapours.

5.3 ADVICE FOR FIREFIGHTERS:

FIRE: This product is highly flammable with a flash point of -9°C. The vapour is heavier than air and will spread along the ground and may accumulate in low points or depressions. Therefore, ignition may occur well away from the point of release of the material. Keep storage tanks, pipelines, fire exposed surfaces, etc. cool with water spray.

HAZCHEM CODE: 3YE.

EXPLOSION: No information to indicate that the product is an explosion hazard; though the solvent component will form an explosive mixture with air. NOTE: Under the WHS legislation, this product is rated as Flammable Liquid - Category 2, with a typical Flash point of -9°C. Extinguish all sources of flame or spark. Closed containers may explode when exposed to extreme heat.

 PROTECTIVE

 EQUIPMENT:

 In the event of a fire, wear full protective clothing and self-contained breathing equipment with full-face piece operated in the pressure demand or other positive pressure mode.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

- **PERSONAL PROTECTION:** For small spills, wear Nitrile gloves, glasses/goggles, boots and full-length clothing. During routine operation for a small spill in the open a respirator is not required. However, if mists or vapours are generated, an approved organic vapour/particulate respirator is required. For large spills, or in confined spaces, a full chemically resistant body-suit is recommended and the atmosphere must be evaluated for oxygen deficiency and whether the atmosphere is flammable. If in doubt about potential oxygen deficiency, wear self-contained breathing apparatus. Never enter an environment with a flammable atmosphere.
- **CONTROL MEASURES:** Ventilate area and extinguish and/or remove all sources of ignition. CAUTION: Vapour may form an explosive mixture with air. Never enter a spill area unless you know the vapours have dissipated to make the area safe. Stop the leak if safe to do so. CAUTION: The spilled product will be slippery. Avoid contact with the spilled material.

SECTION 6 – ACCIDENTAL RELEASE MEASURES Continued

EMERGENCY PROCEDURES: In the event of a spill or accidental release, notify the relevant authorities in accordance with all applicable regulations.

6.2 ENVIRONMENTAL PRECAUTIONS:

SPILL ADVICE:

Do not allow product to enter drains, surface water, sewers or watercourses inform local authorities if this occurs. Take precautions against static discharge. Ensure all equipment is grounded and use non-sparking tools during clean up operations.

6.3 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

CONTAINMENT: Personnel must wear the appropriate clothing as required in Section 6.1 during containment procedures; after the environment has been evaluated. Contain the spill and absorb with a proprietary absorbent material, sand or earth. Be careful of static discharges and/or sparking during clean up. For large spills prepare a bund/barrier/dyke ahead of the spill to confine the spill and allow later recovery. If there is the possibility of spills to enter drains, surface water, sewers or watercourses ensure bunding, or that drains are covered, to minimise the potential for this to occur.

CLEANING PROCEDURES: Having contained the spill, as mentioned above, collect all material quickly and place used absorbent in suitable containers. Be careful of static discharges and/or sparking during clean up. Use only non-sparking tools during cleaning operations. CAUTION: The spilled product will be slippery. Follow local regulations for the disposal of waste. For large spills that have been bunded, the material can be pumped, using flammable liquid equipment, into vessels and returned for reprocessing or destruction. Personnel must wear the appropriate clothing as required in Section 6.1 during cleaning procedures; after the environment has been evaluated. Wash contaminated area and objects with detergent and water after spill has been cleared. Rinse the cleaned area with water. Do not allow wash water or rinsings to enter drains, surface water, sewers or water courses.

SECTION 7 – HANDLING AND STORAGE, INCLUDING HOW THE CHEMICAL MAY BE SAFELY USED

7.1 PRECAUTIONS FOR SAFE HANDLING: SAFE HANDLING: Avoid contact

Avoid contact with the product by using appropriate protective equipment such as gloves, glasses or goggles and full-length clothing. Extinguish any potential sources of ignition before using as flammable vapours will be generated during application. Avoid breathing mists or vapours. Do not smoke when handling the material. Prevent small spills and leakage to avoid slip hazards. Properly dispose of any contaminated rags or cleaning materials in order to prevent fire hazards. Eating, drinking, and smoking should be prohibited in the area where this material is handled, stored and processed. Workers should follow good personal hygiene practices, such as washing hands before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Keep containers tightly closed when not in use. Prevent product from entering waterways, drains or sewers. There is the potential for electrostatic accumulation in the product. As a precaution, containers should always be earthed before dispensing commences.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATABILITIES:

SAFE STORAGE: This product is classified as a Class 3 Flammable Liquid (Flash Point -9°C). Store in a dry, well ventilated area away from direct sunlight, ignition sources, oxidising agents, foodstuffs and clothing. Keep containers closed when not in use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store only in original containers. It is recommended that the product is stored below 25°C.

INCOMPATIBILITIES: Oxidizing substances including strong acids.

SECTION 8 – EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1 EXPOSURE CONTROL MEASURES:

EXPOSURE LIMIT VALUES: Exposure standards for the product have not been established. The following values are applicable for the major component:

Isohexane (2-Methyl pentane) ACGIH

TWA:	500 ppm	1760 mg/m ³	STEL:	1000 ppm	1 3500 mg/m ³
Cycloper TWA:		1720 mg/m ³			
2-Propan TWA:		983 mg/m ³	STEL:	500 ppm	1230 mg/m³

MONITORING: No data available.

8.3 CONTROL BANDING: No data available.

8.4 ENGINEERING CONTROLS:

8.2 BIOLOGICAL

ENGINEERING CONTROLS: Special ventilation is not normally required when using this product in normal use scenarios. However, in the operation of certain equipment, at elevated temperatures, or in confined spaces mists or vapour may be generated and local exhaust ventilation should be provided to maintain airborne concentration levels below the nominated exposure standard and at an acceptable level that does not cause irritation. PLEASE NOTE: Due to the highly flammable nature of the product, if there is a necessity to use ventilation equipment it should not be a potential source of ignition for any vapours generated.

8.5 INDIVIDUAL PROTECTION MEASURES:

EYE & FACE PROTECTION: Wear safety glasses/goggles to avoid eye contact when handling. If there is a risk of splashing during use, a full face shield is recommended. Use eye protection in accordance with AS 1336 and AS 1337.

SKIN (HAND) PROTECTION: If there is the chance of contact with the material wear gloves to provide hand protection. Nitrile rubber gloves are recommended.

 SKIN (CLOTHING)

 PROTECTION:
 During normal operating procedures, long sleeved clothing is recommended to avoid skin contact. Soiled clothing should be washed with detergent prior to reuse.

RESPIRATORY PROTECTION: During routine operation a respirator is not required. However, if mists or vapours are generated, an approved half face organic vapour/particulate respirator is required. Use respirators in accordance with AS 1715 and AS 1716.

THERMAL PROTECTION: Not applicable.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

9.1 PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE:	Clear liquid.
ODOUR:	Characteristic hydrocarbon solvent odour.
ODOUR THRESHOLD:	No data available.
pH:	Not applicable.
MELTING/FREEZING POINT:	No data available.
INITIAL BOILING POINT:	No data available.
BOILING RANGE (°C):	No data available.
FLASHPOINT (°C):	Typically -9°C
EVAPORATION RATE:	No data available.
FLAMMABILITY LIMITS (%):	No data available.
VAPOUR PRESSURE (kPa):	No data available.
VAPOUR DENSITY:	No data available.
DENSITY @ 25.0°C:	Typically 0.69.
SOLUBILITY IN WATER(g/L):	Immiscible with water.
PARTITION COEFFICIENT:	No data available for the product.
AUTO-IGNITION TEMP (°C):	No data available.
DECOMPOSITION TEMP (°C)	: No data available.
VISCOSITY (cSt @ 100°C):	No data available.
VISCOSITY (cSt @ 40°C):	Typically 2.3.

SECTION 10 – STABILITY AND REACTIVITY

10.1 REACTIVITY:	The product does not pose any further reactivity hazards other than those listed in the following sub-sections. With its low flash point the product may form explosive mixtures with air at room temperature.
10.2 CHEMICAL STABILITY: 10.3 POSSIBILITY OF	Stable under recommended storage and handling conditions (see section 7).
HAZARDOUS REACTIONS:	Keep away from strong oxidising agents, such as strong acids, chlorates, nitrates and peroxides. Hazardous polymerisation does not occur.
10.4 CONDITIONS TO AVOID	The product has a flash point of -9°C. Avoid ignition sources including heat and sparks. Observe the usual precautionary measures for handling chemicals. Do not heat the container or leave the container open when not in use.
10.5 INCOMPATIBLE	·
MATERIALS:	Strong oxidising agents including concentrated acids.
10.6 HAZARDOUS DECOMPO	DSITION
PRODUCTS:	Hazardous decomposition products are not expected to form during normal storage requirements. See Section 5.2 for Hazardous Combustion products.

SECTION 11 – TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

The product is a mixture and test data is not available for the product as a whole.

11.2 SWALLOWED: This product is expected to have a low order of toxicity associated with it when ingested. It may cause slight irritation to the mouth, throat and digestive tract. As the product is hydrocarbon based and the viscosity is low, ~2.3cSt, caution should be taken in respect to aspiration into the lungs. Small amounts of this product aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary oedema. Ingestion of large amounts may lead to nausea and vomiting. During normal usage ingestion should not be a means of exposure.

SECTION 11 – TOXICOLOGICAL INFORMATION Continued

11.3 SKIN CORROSION/ IRRITATION:	This product is rated as Causes skin irritation. Prolonged or repeated contact may cause defatting of the skin which may lead to dermatitis. Correct handling procedures incorporating appropriate protective clothing and gloves should minimise the risk of skin irritation. People with pre-existing skin conditions, such as dermatitis, should take extreme care so as not to exacerbate the condition.
11.4 SERIOUS EYE DAMAGE/ IRRITATION:	This product is rated as Causes serious eye irritation. Symptoms may include localised burning, redness and tearing. Correct handling procedures incorporating appropriate eye protection should minimise the risk of eye irritation.
11.5 RESPIRATORY OR SKIN SENSITISATION:	This product is not expected to be a skin sensitiser according to OECD Test 406, based on the available data and the known hazards of the components. This product is not expected to be a respiratory tract sensitiser, based on the available data and the known hazards of the components.
11.6 GERM CELL MUTAGENICITY:	This product is not expected to be mutagenic according to tests such as OECD Tests 471, 475, 476, 478 and 479, based on the available data and the known hazards of the components.
11.7 CARCINOGENICITY:	This product is not expected to be a carcinogen according to OECD Test 451, based on the available data and the known hazards of the components.
11.8 REPRODUCTIVE TOXICITY:	This product is not expected to be a reproductive hazard according to tests such as OECD Tests 414 and 421, based on the available data and the known hazards of the components.
11.9 SPECIFIC TARGET ORG SINGLE EXPOSURE:	AN TOXICITY (STOT) - This product is rated as May cause drowsiness and dizziness. It contains volatile hydrocarbon components, hence inhalation of vapours or mist may cause irritation to the nose and throat. Inhalation of high concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea. Exposure to high levels of hydrocarbon solvent vapours may impact on the liver and kidneys.
11.10 SPECIFIC TARGET ORC REPEATED EXPOSURE:	•
11.11 ASPIRATION HAZARD:	This product is rated as an aspiration hazard - May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary oedema. This can be fatal. As the product is hydrocarbon based, if the product has been ingested or vomiting has occurred after ingestion, the patient must seek urgent medical attention and should be monitored for adverse effects.

11.12 OTHER INFORMATION: There is no additional information available.

SAFETY DATA SHEET

SECTION 12 – ECOLOGICAL INFORMATION

12.1 ECOTOXICITY:	There is no data available for the product as a whole. However, some of the components have been rated as Toxic to aquatic life with long lasting effects and Harmful to aquatic life with long lasting effects. Based upon these nominated values the product is expected to be Toxic to aquatic life with long lasting effects.
12.2 PERSISTENCE & DEGRADABILITY:	There is no data available for the product as a whole.
12.3 BIOACCUMULATIVE POTENTIAL:	There is no data available for the product as a whole.
12.4 MOBILITY IN SOIL:	There is no data available for the product as a whole.
12.5 OTHER ADVERSE EFFECTS:	There is no data available for the product as a whole.

SECTION 13 – DISPOSAL CONSIDERATIONS

13.1 DISPOSAL METHODS: PRODUCT: The product should not be released to the environment, so any unused material should be recycled wherever possible or be disposed of as hazardous waste at an appropriate collection depot. The product is suitable for incineration at very high temperatures to prevent formation of undesirable combustion products. Spilled product that cannot be recovered should be absorbed and then shovelled into a suitable waste container, such as a plastic drum and then be treated as a solid waste. Follow Government regulations for disposal of such waste. All unused, waste or spilled product must be taken for recycling or disposal by suitably licensed contractors in accordance with Government regulations. **CONTAINERS:** Empty containers may contain residual product. CAUTION: Residues are highly flammable and will ignite with a source of ignition. Containers should be completely drained in a well ventilated area where vapours cannot accumulate and then stored until reconditioned or disposed of. Empty containers should be taken for recycling or disposal through suitably licensed contractors in

accordance with Government regulations. As containers may contain highly flammable residues, they should not be pressurised, cut by a grinder, drilled or exposed to heat, flames or other sources of ignition. Closed containers when exposed to such conditions/treatment may explode causing serious injury.

SECTION 14 – TRANSPORT INFORMATION

This product is regulated for land, sea or air transportation. (HS Code: 2710.12.90)

14.1 LAND (ADG Code): UN NUMBER: UN PROPER SHIPPING	1993
NAME:	FLAMMABLE, LIQUID, N.O.S (Contains Isohexane, Cyclopentane and Isopropanol).
TRANSPORT HAZARD	
CLASS(ES):	3
PACKAGING GROUP:	
ENVIRONMENTAL	
HAZARDS:	Yes
SPECIAL PRECAUTIONS	
FOR USER:	274.
HAZCHEM CODE:	3YE

SECTION 14 – TRANSPORT INFORMATION Continued

14.2 SEA (IMDG): UN NUMBER: UN PROPER SHIPPING NAME:	1993 FLAMMABLE, LIQUID, N.O.S (Contains Isohexane, Cyclopentane and Isopropanol).
TRANSPORT HAZARD CLASS(ES): PACKAGING GROUP: ENVIRONMENTAL HAZARDS: SPECIAL PRECAUTIONS FOR USER:	3 II Yes 274
14.3 AIR (IATA): UN NUMBER: UN PROPER SHIPPING NAME:	1993 FLAMMABLE, LIQUID, N.O.S (Contains Isohexane, Cyclopentane and Isopropanol).
TRANSPORT HAZARD CLASS(ES): PACKAGING GROUP: ENVIRONMENTAL HAZARDS: SPECIAL PRECAUTIONS	3 II Yes
FOR USER:	Not applicable.

SECTION 15 – REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS:

 APPLICABLE REGULATIONS:

 SUSMP:
 Schedule 5.

 AICS:
 All ingredients are on the AICS List.

 MONTREAL PROTOCOL:
 No data available.

 STOCKHOLM CONVENTION:
 No data available.

 ROTTERDAM CONVENTION:
 No data available.

 BASEL CONVENTION:
 No data available.

 INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS (MARPOL):
 Not determined.

 OTHER REGULATORY INFORMATION:
 Not determined.

GHS CLASSIFICATION HAZARD CLASS & CATEGORY
AND HAZARD STATEMENT: Flammable Liquids Category 2; H225 - Highly flammable liquid and vapour. Aspiration Hazard Category 1; H304 - May be fatal if swallowed and enters airways. Skin Corrosion/Irritation Category 2; H315 - Causes skin irritation. Serious Eye Damage/Irritation Category 2A; H319 - Causes serious eye irritation.
Specific Target Organ Toxicity (Single Exposure) Category 3; H336 - May cause drowsiness or dizziness. Chronic Aquatic Toxicity Category 2; H411 - Toxic to aquatic life with long lasting effects. Chronic Aquatic Toxicity Category 3; H412 - Harmful to aquatic life with long lasting effects.
HSNO APPROVAL NUMBER: HSR002528.

HSNO GROUP TITLE: Cleaning Products (Flammable) Group Standard 2006

SECTION 16 – ANY OTHER RELEVANT INFORMATION

SDS INFORMATION:

Date of SDS Preparation: 20th March 2017

Revision: 0.2

REVISION CHANGES: Changes to product formulation. Changes in Sections 1, 3 and 16.

ACRONYMS:

SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
CAS Number	Chemical Abstracts Service Registry Number
EINECS	European Inventory of Existing Commercial Chemical Substances
UN Number	United Nations Number
OSHA	Occupational Safety and Health Administration
ACGIH	American Conference of Governmental Industrial Hygienists
IMDG	International Maritime Dangerous Goods
IATA	International Air Transport Association
IUCLID	International Uniform Chemical Information Database
RTECS	Registry of Toxic Effects of Chemical Substances
%W/W	Percent weight for weight
OECD	Organisation for Economic Co-Operation and Development
ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail
HAZCHEM Code	Emergency action code of numbers and letters which gives information to emergency services
NOHSC	National Occupational Health and Safety Commission
AICS	Australian Inventory of Chemical Substances
TWA	Time-Weighted Average
STEL	Short term Exposure Limit
HSNO	Hazardous Substances and New Organisms Act 1996
GHS	Globally Harmonised System of Classification and Labelling of Chemicals
WHS	Work Health and Safety
PPE	Personal Protective Equipment.

LITERATURE REFERENCES AND SOURCES OF DATA:

OECD Guidelines for Testing of Chemicals

Annex I: OECD Test Guidelines for Studies Included in SIDS

Manual for the Assessment of Chemicals Chapter 2 Data Gathering

International Toxicity Testing Guidelines

Hazardous Substance Information System - Guidance Material for Hazard Classifications

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

Model Work Health and Safety Regulations.

Model Work Health and Safety Regulations - Transitional Principles

Workplace Exposure Standards for Airborne Contaminants

Australian Dangerous Goods Code 7th Edition

Approved Criteria for Classifying Hazardous Substances [NOHSC:1008 (2004)]

Guidance on the Classification of Hazardous Chemicals under the WHS Regulations

Assigning a Hazardous Substance to a Group Standard

User Guide to the HSNO Thresholds and Classifications

Summary User Guide to the HSNO Thresholds and Classifications of Hazardous Substances

Correlation between GHS and New Zealand HSNO Hazard Classes and Categories

HSNO Control Regulations

Record of Group Standard Assignment

Labelling of Hazardous Substances Hazard and Precautionary Information

Thresholds and Classifications Under the Hazardous Substances and New Organisms Act 1996

Workplace Exposure Standards and Biological Exposure Indices

All information contained in this Safety Data Sheet and the health, safety and environmental information are considered to be accurate to the best of our knowledge as of the issue date specified above. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this data sheet.

Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The Company accepts no responsibility for any injury, loss or damage, resulting from abnormal use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material.