### SECTION 1 – IDENTIFICATION: PRODUCT IDENTIFIER/CHEMICAL IDENTITY

#### 1.1 PRODUCT IDENTIFIER: Tyre Shine

1.2 PRODUCT CODE: CCTS020

1.3 RELEVANT IDENTIFIED USES OF THE MIXTURE AND USES ADVISED AGAINST:			
RELEVANT IDENTIFIED USES:	Tyre Shine.		
RESTRICTIONS ON USE:	None known.		
1.4 DETAILS OF THE SUPPLIER OF 1	THE SAFETY DATA SHEET:		
SUPPLIER NAME:	PENRITE OIL Company Pty Ltd (ABN: 25005 001 525),		
ADDRESS (Australia):	110-116 Greens Road, Dandenong South VIC, Australia, 3175		
TELEPHONE NUMBER (Australia):	1300 736 748; +61 3 8710 6600 (Int); Fax: 1800 736 748		
ADDRESS (New Zealand):	75 Lady Ruby Drive, East Tamaki, Auckland, New Zealand, 2013		
· · · ·			
TELEPHONE NUMBER (New Zealand):0800 533 698; Fax: 0800 533 698			
E-MAIL:	tech@penriteoil.com (Aust and NZ)		
1.5 EMERGENCY TEL. NUMBER:	Australia: 1300 736 748; New Zealand: 0800 533 698		
	(Poisons Information Centre (Aust 131 126; NZ 0800 764 766)		
1.6 HSNO DETAILS:			
HSNO APPROVAL NUMBER:	HSR002602.		
HSNO GROUP TITLE:	Lubricants (Combustible) Group Standard 2006.		

## **SECTION 2 – HAZARD(S) IDENTIFICATION**

## 2.1 CLASSIFICATION OF THE HAZARDOUS CHEMICAL:

GHS CLASSIFICATION HAZARD

CLASS & CATEGORY: Under the Model Work Health and Safety Regulations the product would be rated as hazardous: Flammable Liquid - Category 4 Aspiration Hazard - Category 1

Chronic Aquatic Toxicity - Category 2

SIGNAL WORD: PICTOGRAMS:	Danger
HAZARD STATEMENTS:	H227 - Combustible Liquid. H304 - May be fatal if swallowed and enters airways. H412 - Harmful to aquatic life with long lasting effects.
PRECAUTIONARY STATEME	
PREVENTION:	<ul> <li>P102 - Keep out of reach of children.</li> <li>P103 - Read label before use.</li> <li>P210 - Keep away from flames and hot surfaces – No smoking.</li> <li>P273 - Avoid release to the environment.</li> <li>P280 - Wear protective gloves/eye protection/face protection.</li> </ul>
RESPONSE:	<ul> <li>P101 - If medical advice is needed, have product container or label at hand.</li> <li>P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.</li> <li>P331 - Do NOT induce vomiting.</li> <li>P370+P378 - In case of fire: Use carbon dioxide, foam, dry chemical or water spray for extinction.</li> </ul>
STORAGE:	P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up.

## SECTION 2 – HAZARD(S) IDENTIFICATION Continued

#### **DISPOSAL:**

P501 - Dispose of contents/container in accordance with local regulations.

**2.3 OTHER HAZARDS:** This is a Schedule 5 Poison. Due to the presence of solvents there is a possibility of organ system damage. The presence of the solvent component suggests that the product may be irritating to the skin and eyes. The vapours may also lead to drowsiness and dizziness. The product will potentially form flammable/explosive mixtures in air. There may be static discharge issues with the product in large scale operations that could lead to a fire. As for all chemical products, persons should not expose open wounds, cuts, abrasions or irritated skin to this material.

## **SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS**

INGREDIENTS	CAS NUMBER	Concentration % W/W	GHS Classification*
Distillates, petroleum, hydrotreated light	64742-47-8	> 70%	Flam Liq 4 - H227 Asp Haz 1 - H304
Pentane, 2-methyl- (Isohexane)	107-83-5	< 6%	Flam Liq 2 - H225 Asp Haz 1 - H304 Skin Irrit 2 - H315 STOT SE 3 - H336
Other non-hazardous ingredients	-	To 100%	Chron Aq Tox 2 - H411 Not Applic

Not Applic = Not Applicable \* Please see Section 15 of this SDS for the full text description of the Label Elements.

## SECTION 4 – FIRST AID MEASURES

4.1 DESCRIPTION OF NECES INGESTION:	<b>SARY FIRST AID MEASURES:</b> Rinse mouth out with water. If swallowed, do NOT induce vomiting. For advice, contact the Poisons Information Centre (phone Australia 131 126; New Zealand 0800 764 766) or a doctor at once. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Within 6 hours of ingestion, if delayed symptoms, such as a fever greater than 38.3°C, shortness of breath, chest congestion or continued coughing/wheezing occurs transport immediately to a medical facility. As the product is hydrocarbon based and of low viscosity (5.5cSt @ 40°C), if ingested seek urgent medical assistance.
EYE:	If in eyes, hold eyelids apart and flush the eye immediately with large amounts of running water. Continue flushing for at least 15 minutes or until advised to stop by a Doctor. Check for contact lenses. If there are contact lenses, these should be removed after several minutes of rinsing by the exposed person or medical personnel if it can be done easily. After flushing, if irritation develops or persists, seek medical assistance.
SKIN CONTACT:	If skin or hair contact has occurred remove any contaminated clothing and footwear, wash skin or hair thoroughly with soap and water. If irritation develops or persists, consult a Doctor.
INHALATION:	If affected, remove the patient from further exposure into fresh air, if safe to do so. If providing assistance, avoid exposure to yourself - only enter contaminated environments with adequate respiratory equipment. Once removed, lay patient down in a well-ventilated area and reassure them whilst waiting for medical assistance. If not breathing, provide artificial respiration and seek immediate medical assistance. If unconscious, place in a recovery position and seek immediate medical assistance. If irritation develops or persists, consult a Doctor.

### **SECTION 4 – FIRST AID MEASURES Continued**

#### **PROTECTION FOR FIRST**

AIDERS: No personnel shall place themselves in a situation that is potentially hazardous to themselves. Assess the scenario for PPE requirements before entering. Assess environment for flammable vapours before entering. Never enter an environment with a flammable atmosphere. Do not enter contaminated area without a respirator. As the product is hydrocarbon based and of low viscosity, if the person has ingested the product, do not use direct mouth-to-mouth resuscitation techniques. Always ensure that you are wearing gloves when dealing with first aid procedures involving chemicals and/or blood.

## **FIRST AID FACILITIES:** Eye wash fountain and safety showers are recommended in the area where the product is used.

4.2 MOST IMPORTANT SYMPTOMS & EFFECTS, BOTH ACUTE & DELAYED, CAUSED BY EXPOSURE: ACUTE: Ingestion or inhalation of vapours may lead to irritation of the mouth and respiratory tract. Symptoms may include a burning sensation in the nose and throat, coughing or difficulty breathing. Ingestion may lead to nausea and diarrhoea. If material is aspirated into the lungs it may exhibit as coughing, wheezing, congestion or fever. Inhalation of high concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea. Eye contact may lead to localised burning, redness and tearing. Skin contact may lead to redness or itching.

## CHRONIC: Skin contact may aggravate/exacerbate existing skin conditions, such as dermatitis.

**4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NECESSARY: ADVICE TO DOCTOR:** Treat symptomatically. As the product is predominantly hydrocarbon based and of low viscosity, if vomiting has occurred after ingestion, the patient should be

or low viscosity, it vomiting has occurred after ingestion, the patient should be monitored for adverse effects to ensure that the product has not aspirated into the lungs. Small amounts of this product aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary oedema. Inhalation of high vapour concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea.

## **SECTION 5 – FIRE FIGHTING MEASURES**

#### 5.1 EXTINGUISHING MEDIA:

**SUITABLE MEDIA:** Use extinguishing media appropriate for surrounding fire. Use carbon dioxide, foam, dry chemical or water spray. Spray down fumes resulting from fire.

**UNSUITABLE MEDIA:** Avoid using full water jet directed at residual material that may be burning. Water may cause splattering on hot residues. Product will float on water.

#### 5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

**COMBUSTION HAZARDS:** Combustion may produce oxides of carbon and silicon, as well as smoke and irritating vapours.

#### **5.3 ADVICE FOR FIREFIGHTERS:**

- **FIRE:** This product is combustible with a typical flash point of 85°C. The vapour is heavier than air and will spread along the ground and may accumulate in low points or depressions. Therefore, ignition may occur well away from the point of release of the material. Keep storage tanks, pipelines, fire exposed surfaces, etc. cool with water spray.
- HAZCHEM CODE: Not applicable.
- **EXPLOSION:** No information to indicate that the product is an explosion hazard; though the solvent component may form an explosive mixture with air. Note: Under the WHS legislation, this product is rated as Flammable Liquid Category 4, with a typical Flash point of 85°C. Extinguish all sources of flame or spark. Closed containers may explode when exposed to extreme heat.

## **SECTION 5 – FIRE FIGHTING MEASURES Continued**

### PROTECTIVE

EQUIPMENT:

In the event of a fire, wear full protective clothing and self-contained breathing equipment with full-face piece operated in the pressure demand or other positive pressure mode.

## **SECTION 6 – ACCIDENTAL RELEASE MEASURES**

#### 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

**PERSONAL PROTECTION:** For small spills, wear Nitrile gloves, glasses/goggles, boots and full-length clothing. During routine operation for a small spill in the open a respirator is not required. However, if mists or vapours are generated, an approved organic vapour/particulate respirator is required. For large spills, or in confined spaces, a full chemically resistant body-suit is recommended and the atmosphere must be evaluated for oxygen deficiency and as a precaution whether the atmosphere is flammable. If in doubt about potential oxygen deficiency, wear self-contained breathing apparatus. Never enter an environment with a flammable atmosphere.

**CONTROL MEASURES:** Ventilate area and extinguish and/or remove all sources of ignition. CAUTION: Vapour may form an explosive mixture with air. Never enter a spill area unless you know the vapours have dissipated to make the area safe. Stop the leak if safe to do so. Caution: The spilled product will be slippery. Avoid contact with the spilled material.

**EMERGENCY PROCEDURES:** In the event of a spill or accidental release, notify the relevant authorities in accordance with all applicable regulations.

#### 6.2 ENVIRONMENTAL PRECAUTIONS:

SPILL ADVICE: Do not allow product to enter drains, surface water, sewers or watercourses inform local authorities if this occurs. Take precautions against static discharge. Ensure all equipment is grounded and use non-sparking tools during clean up operations.

#### 6.3 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

- **CONTAINMENT:** Contain the spill and absorb with a proprietary absorbent material, sand or earth. Caution: The spilled product will be slippery. Be careful of static discharges and/or sparking during clean up. For large spills prepare a bund/barrier/dyke ahead of the spill to confine the spill and allow later recovery. If there is the possibility of spills to enter drains, surface water, sewers or watercourses ensure bunding, or that drains are covered, to minimise the potential for this to occur.
- **CLEANING PROCEDURES:** Having contained the spill, as mentioned above, collect all material quickly and place used absorbent in suitable containers. Be careful of static discharges and/or sparking during clean up. Use only non-sparking tools during cleaning operations. Caution: The spilled product will be slippery. Follow local regulations for the disposal of waste. For large spills that have been bunded, the material can be pumped, using flammable liquid equipment, into vessels and returned for reprocessing or destruction. Personnel must wear gloves, goggles or glasses, boots and full-length clothing during cleaning procedures. Wash contaminated area and objects with detergent and water after spill has been cleared. Rinse the cleaned area with water. Do not allow wash water or rinsings to enter drains, surface water, sewers or water courses.

# SECTION 7 – HANDLING AND STORAGE, INCLUDING HOW THE CHEMICAL MAY BE SAFELY USED

#### 7.1 PRECAUTIONS FOR SAFE HANDLING:

SAFE HANDLING:

SAFE STORAGE:

Avoid contact with the product by using appropriate protective equipment such as gloves, glasses or goggles and full-length clothing. Extinguish any potential sources of ignition before using as flammable vapours will be generated during application. Avoid breathing mists or vapours. Do not smoke when handling the material. Prevent small spills and leakage to avoid slip hazards. Properly dispose of any contaminated rags or cleaning materials in order to prevent fire hazards. Eating, drinking, and smoking should be prohibited in the area where this material is handled, stored and processed. Workers should follow good personal hygiene practices, such as washing hands before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Keep containers tightly closed when not in use. Prevent product from entering waterways, drains or sewers. There is the potential for electrostatic accumulation in the product. As a precaution, containers should always be earthed before dispensing commences.

#### 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATABILITIES:

Classified as a Flammable Liquids Category 4 (Combustible Liquid) under the WHS Regulations (Flash Point=85°C). Store in a dry, well ventilated area away from direct sunlight, ignition sources, oxidising agents, foodstuffs and clothing. Keep containers closed when not in use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store only in original containers.

**INCOMPATIBILITIES:** Oxidising substances including strong acids.

### **SECTION 8 – EXPOSURE CONTROLS & PERSONAL PROTECTION**

#### 8.1 EXPOSURE CONTROL MEASURES:

**EXPOSURE LIMIT VALUES:** Exposure standards for the product have not been established. Therefore, the following Exposure Standard should be considered:

#### Isohexane (2-Methyl pentane) ACGIH

TWA: 500 ppm 1760 mg/m<sup>3</sup> STEL: 1000 ppm 3500 mg/m<sup>3</sup>

- 8.2 BIOLOGICAL MONITORING: No data available.
- **8.3 CONTROL BANDING:** No data available.

#### **8.4 ENGINEERING CONTROLS:**

**ENGINEERING CONTROLS:** Special ventilation is not normally required when using this product in normal use scenarios. However, at elevated temperatures, or in confined spaces mists or vapour may be generated and local exhaust ventilation should be provided to maintain airborne concentration levels below the nominated exposure standard and at an acceptable level that does not cause irritation. PLEASE NOTE: Due to the flammable nature of the product, if there is a necessity to use ventilation equipment it should not be a potential source of ignition for any vapours generated.

#### 8.5 INDIVIDUAL PROTECTION MEASURES:

- **EYE & FACE PROTECTION:** Wear safety glasses/goggles to avoid eye contact when handling. If there is a risk of splashing during use, a full face shield is recommended. Use eye protection in accordance with AS 1336 and AS 1337.
- **SKIN (HAND) PROTECTION:** If there is the chance of contact with the material wear gloves to provide hand protection. Nitrile rubber gloves are recommended.

## **SECTION 8 – EXPOSURE CONTROLS & PERSONAL PROTECTION Cont'd**

#### SKIN (CLOTHING) PROTECTION:

During normal operating procedures, long sleeved clothing is recommended to avoid skin contact. Soiled clothing should be washed with detergent prior to reuse.

**RESPIRATORY PROTECTION:** During routine operation a respirator is not required. However, if mists or vapours are generated, an approved half face organic vapour/particulate respirator is required. Use respirators in accordance with AS 1715 and AS 1716.

THERMAL PROTECTION: Not applicable.

### **SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

9.1 PHYSICAL AND CHEMICAL PROPERTIES:			
APPEARANCE:	Clear liquid.		
ODOUR:	Characteristic hydrocarbon odour.		
ODOUR THRESHOLD:	No data available.		
pH:	Not applicable.		
MELTING/FREEZING POINT:	No data available.		
INITIAL BOILING POINT:	No data available.		
BOILING RANGE (°C):	No data available.		
FLASHPOINT (°C):	Typically 85°C.		
EVAPORATION RATE:	No data available.		
FLAMMABILITY LIMITS (%):	No data available.		
VAPOUR PRESSURE (Pa):	No data available.		
VAPOUR DENSITY:	No data available.		
DENSITY @ 15.0°C:	Typically 0.75 - 0.85.		
SOLUBILITY IN WATER(g/L):	Immiscible with water.		
PARTITION COEFFICIENT:	No data available for the product.		
AUTO-IGNITION TEMP (°C):	No data available.		
DECOMPOSITION TEMP (°C):	: No data available.		
VISCOSITY (cSt @ 100°C):	Typically 2.7.		
VISCOSITY (cSt @ 40°C):	Typically 5.5.		

### **SECTION 10 – STABILITY AND REACTIVITY**

10.1 REACTIVITY:	The product does not pose any further reactivity hazards other than those listed in the following sub-sections.	
10.2 CHEMICAL STABILITY: 10.3 POSSIBILITY OF	Stable under recommended storage and handling conditions (see section 7).	
HAZARDOUS REACTIONS:	Keep away from strong oxidising agents, such as strong acids, chlorates, nitrates and peroxides. Hazardous polymerisation does not occur.	
10.4 CONDITIONS TO AVOID	The product has a relatively low flash point. Avoid ignition sources including heat and sparks. Observe the usual precautionary measures for handling chemicals. Do not heat the container or leave the container open when not in use.	
10.5 INCOMPATIBLE		
MATERIALS:	Strong oxidising agents including strong acids.	
10.6 HAZARDOUS DECOMPOSITION		
PRODUCTS:	Hazardous decomposition products are not expected to form during normal storage requirements. See Section 5.2 for Hazardous Combustion products.	

## **SECTION 11 – TOXICOLOGICAL INFORMATION**

#### **11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:**

The product is a mixture and test data is not available for the product as a whole.

	<b>Distillates, petroleum, hydrotreated light</b> (IUCLID) Oral - LD <sub>50</sub> (Rat): > 5000mg/kg Dermal - LD <sub>50</sub> (Rabbit): > 2000mg/kg		
11.2 SWALLOWED:	The hydrocarbon component means this is a Schedule 5 Poison. As the product is hydrocarbon based and the viscosity is low, caution should be taken in respect to aspiration into the lungs. Small amounts of this product aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary oedema. Ingestion of large amounts may lead to nausea and vomiting. During normal usage ingestion should not be a means of exposure.		
11.3 SKIN CORROSION/			
IRRITATION:	This product is not expected to exhibit Dermal Corrosivity/Irritation based on the available data and the known hazards of the components. This product contains a component that is rated as an irritant, however this is present at amounts below the Concentration cut-off level that would indicate that there is a potential corrosion/irritation hazard. May be mildly irritating to the skin. Correct handling procedures incorporating appropriate protective clothing and gloves should minimise the risk of skin irritation. People with pre-existing skin conditions, such as dermatitis, should take extreme care so as not to exacerbate the condition.		
11.4 SERIOUS EYE DAMAGE			
IRRITATION: 11.5 RESPIRATORY OR	This product is not expected to exhibit Eye Irritation or Serious Damage/ Corrosivity based on the available data and the known hazards of the components. May be mildly irritating to the eyes. Symptoms may include localised burning, redness and tearing. Correct handling procedures incorporating appropriate eye protection should minimise the risk of eye irritation.		
SKIN SENSITISATION:	This product is not expected to be a skin sensitiser based on the available data and the known hazards of the components. This product is not expected to be a respiratory tract sensitiser, based on the available data and the known hazards of the components.		
11.6 GERM CELL MUTAGENICITY:	This product is not expected to be mutagenic based on the available data and the known hazards of the components.		
11.7 CARCINOGENICITY:	This product is not expected to be a carcinogen based on the available data and the known hazards of the components.		
11.8 REPRODUCTIVE TOXICITY:	This product is not expected to be a reproductive hazard based on the available data and the known hazards of the components.		
11.9 SPECIFIC TARGET ORGAN TOXICITY (STOT) -			
SINGLE EXPOSURE:	There is no data available for the product as a whole. This product contains volatile hydrocarbon components, hence inhalation of vapours or mist (generated at elevated temperatures or by mechanical action) may cause irritation to the nose and throat. Inhalation of high concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea. Exposure to high levels of hydrocarbon solvent vapours may impact on the liver and kidneys.		
11.10 SPECIFIC TARGET OR			
REPEATED EXPOSURE:	There is no data available for the product as a whole. This product is not		

**REPEATED EXPOSURE:** There is no data available for the product as a whole. This product is not expected to cause organ damage from prolonged or repeated exposure based on the available data and the known hazards of the components.

## **SECTION 11 – TOXICOLOGICAL INFORMATION Continued**

**11.11 ASPIRATION HAZARD:** This product is rated as an aspiration hazard - May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary oedema. This can be fatal. As the product is hydrocarbon based, if the product has been ingested or vomiting has occurred after ingestion, the patient must seek medical attention and should be monitored for adverse effects.

**11.12 OTHER INFORMATION:** No additional information is available.

### **SECTION 12 – ECOLOGICAL INFORMATION**

12.1 ECOTOXICITY:	There is no data available for the product as a whole. The Isohexane component has been rated as Toxic to aquatic life with long lasting effects. Based upon these nominated values the product is expected to be Harmful to aquatic life with long lasting effects.
12.2 PERSISTENCE &	
DEGRADABILITY:	Based on the available data and the known hazards of the components and similar products the manufacturer states that the product is expected to be biodegradable.
12.3 BIOACCUMULATIVE	
POTENTIAL:	There is no data available for the product as a whole.
12.4 MOBILITY IN SOIL:	There is no data available for the product as a whole. The solvent component is relatively volatile and would be expected to evaporate to the air if released to the environment.
12.5 OTHER ADVERSE	
EFFECTS:	There is no data available for the product as a whole. Based on the available data and the known hazards of the components and similar products the product is not expected to have ozone depletion potential. The product will float

### **SECTION 13 – DISPOSAL CONSIDERATIONS**

on water.

**13.1 DISPOSAL METHODS:** PRODUCT: The product should not be released to the environment, so any unused material should be recycled wherever possible or be disposed of as hazardous waste at an appropriate collection depot. The product is also suitable for incineration at very high temperatures to prevent formation of undesirable combustion products. Spilled product that cannot be recovered should be absorbed and then shovelled into a suitable waste container, such as a plastic drum and then be treated as a solid waste. Follow Government regulations for disposal of such waste. All unused, waste or spilled product must be taken for recycling or disposal by suitably licensed contractors in accordance with Government regulations. **CONTAINERS:** Empty containers may contain residual product. CAUTION: Residues are combustible and will ignite with a source of ignition. Containers should be completely drained in a well ventilated area where vapours cannot accumulate and then stored until reconditioned or disposed of. Empty containers should be taken for recycling or disposal through suitably licensed contractors in accordance with Government regulations. As containers may contain combustible residues, they should not be pressurised, cut by a grinder, drilled or exposed to heat, flames or other sources of ignition. Closed containers when exposed to such conditions/treatment may explode causing serious injury.

## **SECTION 14 – TRANSPORT INFORMATION**

This product is not regulated for land, sea or air transportation. (HS Code: 3403.99.12.00)

14.1 LAND (ADG Code):	
UN NUMBER: UN PROPER SHIPPING	Not applicable
NAME:	Not applicable
TRANSPORT HAZARD	
CLASS(ES): PACKAGING GROUP:	Not applicable Not applicable
ENVIRONMENTAL	Not applicable
HAZARDS:	Not applicable
SPECIAL PRECAUTIONS	
FOR USER:	Not applicable
HAZCHEM CODE:	Not applicable
14.2 SEA (IMDG):	<b>N</b> I / <b>N</b> II
UN NUMBER: UN PROPER SHIPPING	Not applicable
NAME:	Not applicable
TRANSPORT HAZARD	
CLASS(ES):	Not applicable
PACKAGING GROUP: ENVIRONMENTAL	Not applicable
HAZARDS:	Not applicable
SPECIAL PRECAUTIONS	
FOR USER:	Not applicable
14.3 AIR (IATA):	
UN NUMBER:	Not applicable
UN PROPER SHIPPING NAME:	Not applicable
TRANSPORT HAZARD	
CLASS(ES):	Not applicable
PACKAGING GROUP:	Not applicable
ENVIRONMENTAL HAZARDS:	Not applicable
SPECIAL PRECAUTIONS	
FOR USER:	Not applicable

## **SECTION 15 – REGULATORY INFORMATION**

```
15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS:APPLICABLE REGULATIONS:SUSMP:Schedule 5 (S5).AICS:All ingredients are on the AICS List.MONTREAL PROTOCOL:Not applicable to this product.STOCKHOLM CONVENTION:Not applicable to this product.ROTTERDAM CONVENTION:Not applicable to this product.BASEL CONVENTION:Not applicable to this product.INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM<br/>SHIPS (MARPOL):Not determined.
```

## **SECTION 14 – TRANSPORT INFORMATION Continued**

#### OTHER REGULATORY INFORMATION:

#### **GHS CLASSIFICATION HAZARD CLASS & CATEGORY**

AND HAZARD STATEMENT	<ul> <li>Flammable Liquids Category 2; H225 - Highly flammable liquid and vapour.</li> <li>Flammable Liquids Category 4; H227 - Combustible liquid.</li> <li>Aspiration Hazard Category 1; H304 - May be fatal if swallowed and enters airways.</li> <li>Skin Corrosion/Irritation Category 2; H315 - Causes skin irritation.</li> <li>Specific Target Organ Toxicity (Single Exposure) Category 3; H336 - May cause drowsiness or dizziness.</li> <li>Chronic Aquatic Toxicity Category 2; H411 - Toxic to aquatic life with long lasting effects.</li> <li>Chronic Aquatic Toxicity Category 3; H412 - Harmful to aquatic life with long lasting effects.</li> </ul>
HSNO APPROVAL NUMBER:	HSR002602.
HSNO GROUP TITLE:	Lubricants (Combustible) Group Standard 2006.

## **SECTION 16 – ANY OTHER RELEVANT INFORMATION**

SDS INFORMATI Date of SDS Prep		20 <sup>th</sup> September 2017	Revision: 1.0
<b>REVISION CHAN</b>	GES:	Changes to supplier information. Changes to Sections 1, 2, 16.	7, 8, 9, 11, 13 and
ACRONYMS:			
SUSMP	Standard fo	r the Uniform Scheduling of Medicines and Poisons	
CAS Number		ostracts Service Registry Number	
EINECS		ventory of Existing Commercial Chemical Substances	
UN Number	United Natio		
OSHA		al Safety and Health Administration	
ACGIH		onference of Governmental Industrial Hygienists	
HSE-WEL		Safety Executive - Workplace Exposure Limit	
EH40		Workplace Exposure Limits	
		I Maritime Dangerous Goods	
IATA IUCLID		I Air Transport Association I Uniform Chemical Information Database	
RTECS		Foxic Effects of Chemical Substances	
%W/W	0, 1	ght for weight	
OECD		n for Economic Co-Operation and Development	
ADG Code		ode for the Transport of Dangerous Goods by Road and Rail	
HAZCHEM Code		action code of numbers and letters which gives information to e	emergency services
NOHSC		cupational Health and Safety Commission	
NICNAS		ustrial Chemicals Notification & Assessment Scheme	
IMAP		ulti-Tiered Assessment and Prioritisation	
AICS		iventory of Chemical Substances	
TWA		ited Average	
STEL	Short Term	Exposure Limit	
HSNO		Substances and New Organisms Act 1996	
GHS		monised System of Classification and Labelling of Chemicals	
WHS	Work Health		
PPE		otective Equipment.	
LD <sub>50</sub>	Median Leth		
		al Concentration	
EC <sub>50</sub>		ncentration of a substance that causes 50% of the maximum rent rent rent rent rent rent rent rent	esponse after
NOAEL	No Observe	d Adverse Effect Level	
NOEC		d Effect Concentration	
ECHA		hemicals Agency	
REACH	Registration	, Evaluation, Authorisation and Restriction of Chemicals	

## **SECTION 16 – ANY OTHER RELEVANT INFORMATION Continued**

LITERATURE REFERENCES AND SOURCES OF DATA: OECD Guidelines for Testing of Chemicals Annex I: OECD Test Guidelines for Studies Included in SIDS Manual for the Assessment of Chemicals Chapter 2 Data Gathering International Toxicity Testing Guidelines Hazardous Substance Information System - Guidance Material for Hazard Classifications Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice. Model Work Health and Safety Regulations. Model Work Health and Safety Regulations - Transitional Principles Workplace Exposure Standards for Airborne Contaminants Australian Dangerous Goods Code 7th Edition Approved Criteria for Classifying Hazardous Substances [NOHSC:1008 (2004)] Guidance on the Classification of Hazardous Chemicals under the WHS Regulations Assigning a Hazardous Substance to a Group Standard User Guide to the HSNO Thresholds and Classifications Summary User Guide to the HSNO Thresholds and Classifications of Hazardous Substances Correlation between GHS and New Zealand HSNO Hazard Classes and Categories **HSNO** Control Regulations Record of Group Standard Assignment Labelling of Hazardous Substances Hazard and Precautionary Information Thresholds and Classifications Under the Hazardous Substances and New Organisms Act 1996 Workplace Exposure Standards and Biological Exposure Indices

All information contained in this Safety Data Sheet and the health, safety and environmental information are considered to be accurate to the best of our knowledge as of the issue date specified above. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this data sheet.

Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The Company accepts no responsibility for any injury, loss or damage, resulting from abnormal use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material.