



COOLANT RANGE

- ✓ Exclusive Technology ✓ OEM applications
- ✓ Most advanced & complete coolant offer on the market



**Proudly 100% Australian
Owned and Made Since 1926**



8 YEAR / 500,000 KMs MANUFACTURER APPROVED COOLANT

8 Year 500,000KM Red Coolant is a **GENUINE G40 Original Equipment Manufacturer (OEM), Fully Licensed and Warranty Approved, Type "A"** Ethylene glycol, anti-freeze anti-boil coolants used in initial manufacturer factory fills.

- Increased drain intervals to meet or exceed the latest manufacturer requirements
- **OEM Approved** to maintain manufacturer's warranty & performance specifications
- Most advanced **Organic Acid Technology (OAT)** available in the market
- Increased vehicle applications and approvals
- Safe to be mixed with previous 6 Year Coolant
- Compatible with all plastics, rubbers and seals
- Protects all internal surfaces from corrosion, including aluminium
- **Phosphate free** formulation allows use with hard water
- **Amine, Borate and Nitrite free**

Safe for vehicles requiring Organic Type A **RED, MAGENTA** or **ORANGE** coolants including: Audi, Ford, GM Holden, Hyundai, Honda, Jeep, KIA, Mazda, Mitsubishi, Mercedes, Porsche, Suzuki, Toyota, VW and more.

OEM APPROVALS: VW, Audi, Mercedes, Seat, Skoda, Porsche, Bugatti, Bentley & Lamborghini. For a complete list of approvals visit penriteoil.com



REPLACES



**6 YEAR
350,000 KMs
COOLANT**

Product Code	Dilution	Type	Colour	OEM	1L	2.5L	5L	20L	60L	205L
COOLRED	100% Concentrate	Type A OAT	Red	Yes	✓	✓	✓	✓	✓	✓
COOLREDPMX	Premix @ 50%	Type A OAT	Red	Yes	✓		✓			✓

7 YEAR / 450,000 KMs MANUFACTURER APPROVED COOLANT



7 Year 450,000KM Green Coolant is a **GENUINE G48 Original Equipment Manufacturer (OEM), Fully Licensed and Warranty Approved, Type "A"** Ethylene glycol, anti-freeze anti-boil as used in initial manufacturer factory fills.

- Increased drain intervals to meet or exceed the latest manufacturer requirements
- **OEM Approved** to maintain manufacturer's warranty & specifications
- Most advanced **Hybrid Organic Acid Technology (HOAT)** available in the market
- Increased vehicle applications and approvals
- Safe to be mixed with previous 4 Year Coolant
- Compatible with plastics, rubbers and seals
- Protects all internal surfaces from corrosion, including aluminium
- **Phosphate free** formulation allows use with hard water
- **Amine and Nitrite free**

Safe for vehicles requiring Type A **GREEN** or **YELLOW** coolants including: Audi, BMW, Ford, GM Holden, Daewoo, Hyundai, Jeep, KIA, Mazda, Mitsubishi, Mercedes, Porsche, Nissan, VW and more.

OEM APPROVALS: Audi, BMW, Mini, Porsche, Mercedes, Volvo, Skoda, Opel, Bentley & Jaguar. For a complete list of approvals visit penriteoil.com



REPLACES



**4 YEAR
COOLANT
& HD 50/50**

Product Code	Dilution	Type	Colour	OEM	1L	2.5L	5L	20L	60L	205L
COOLGREEN	100% Concentrate	Type A HOAT	Dark Green	Yes	✓	✓	✓	✓	✓	✓
COOLGREENPMX	Premix @ 50%	Type A HOAT	Dark Green	Yes	✓		✓	✓		✓

7 YEAR / 450,000 KMs MANUFACTURER APPROVED COOLANT

7 Year 450,000KM Blue Coolant is a **GENUINE G30 Original Equipment Manufacturer (OEM), Fully Licensed and Warranty Approved, Type "A"** Ethylene glycol, anti-freeze anti-boil as used in initial manufacturer factory fills.

- Increased drain intervals to meet or exceed the latest manufacturer requirements
- **OEM Approved** to maintain manufacturer's warranty & specifications
- Most advanced **Organic Acid Technology (OAT)** available in the market
- Increased vehicle applications and approvals
- Safe to be mixed with previous 3 Year Coolant
- Compatible with all plastics, rubbers and seals
- Protects all internal surfaces from corrosion, including aluminium
- **Phosphate free** formulation allows use with hard water
- **Amine, Borate, Nitrite and Silicate free**

Safe for vehicles requiring Organic Type A **BLUE** coolants including: Audi, Ford, GM Holden, Hyundai, Honda, Mazda, Mitsubishi, Mercedes, Nissan, Porsche, Subaru, Suzuki, Toyota, VW and more.

OEM APPROVALS: Audi, Porsche, Mini Cooper D, MAN, MTU, DAF Trucks, Seat & Skoda. For a complete list of approvals visit penriteoil.com



REPLACES



**COOLANT
TOP UP
& 3 YEAR**

Product Code	Dilution	Type	Colour	OEM	1L	2.5L	5L	20L	60L	205L
COOLBLUE	100% Concentrate	Type A OAT	Blue	Yes	✓		✓	✓	✓	
COOLBLUEPMX	Premix @ 50%	Type A OAT	Blue	Yes	✓		✓			

350,000 KM's COOLANT

350,000KM Green Coolant is a **Type A** anti-freeze / anti-boil coolant. It is a **Silicate, Phosphate & Amine** free coolant, safe for all types of light and heavy duty vehicles.

- Increased drain intervals to meet or exceed the latest manufacturer requirements
- Most advanced **Hybrid Organic Acid Technology (HOAT)** available in the market
- Compatible with all plastics, rubbers and seals
- Protects all internal surfaces from corrosion, including aluminium
- **Phosphate free** formulation allows use with hard water
- **Amine and Silicate free**
- Suitable for Asian vehicles specifying non-silicate coolant

Safe for vehicles requiring Hybrid Type A **GREEN, BLUE** or **YELLOW** coolants including: BMW, Ford, Mazda, GM Holden, Daewoo, Daihatsu Hyundai, KIA, Jeep, Mercedes, Mitsubishi, Porsche, Nissan, Suzuki and more.



Product Code	Dilution	Type	Colour	OEM	1L	2.5L	5L	20L	60L	205L
COOL350	100% Concentrate	Type A HOAT	Light Green	-	✓	✓	✓	✓	✓	✓
COOL350PMX	Premix @ 33%	Type A HOAT	Light Green	-	✓		✓			

Replaces PROAFAB

RCI 100 RADIATOR CORROSION INHIBITOR

RCI 100 is a **Type "B"** radiator inhibitor that protects against corrosion, cavitation, scaling and oxidation in vehicles that DO NOT require a Type "A" Anti-Freeze Anti-Boil coolant.

- Protects all internal surfaces from corrosion, including aluminium
- Most advanced **Hybrid Organic Acid Technology (HOAT)** available in the market
- Safe for all plastics, rubber hoses & seals
- Contains an anti foam agent to help protect against cavitation erosion
- **Amine, Phosphate and Silicate free**
- Cost effective engine protection
- 1L makes 20L



Replaces ADRIC &
PRO COOLANT INHIBITOR

Product Code	Dilution	Type	Colour	OEM	500mL	1L	2.5L	5L	20L	205L
COOL100	100% Concentrate	Type B HOAT	Dark Green	-	✓	✓			✓	✓

ENGINE COOLANTS & ADDITIVES

UNIVERSAL TOP UP

- Type A.
- Compatible with all coolant types.
- Will not discolour original coolant.
- Phosphate free formulation.
- Ready to use.
- Available in 1L.



RACE COOLANT

- Type B, non glycol.
- Leaves no slippery residue if dropped on the track.
- Superior heat transfer.
- Maximum heat dissipation.
- Available in 1L.



CLASSIC CAR COOLANT

- Type B, non glycol.
- Suitable for use in both hard and soft water.
- Will not stain engine castings or radiators surrounds.
- Available in 1L



RADIATOR FLUSH

- Fast acting, cleans in 7 minutes.
- Removes internal rust & corrosion.
- Improves cooling system performance.
- Non-acidic formulation.
- Available in 375mL & 20L.



RADIATOR STOP LEAK

- Stops coolant leaks.
- Safe for rubber hoses and all metals, including aluminium.
- Compatible with anti-freeze/anti-boil solutions.
- Available in 375mL.



COOLANT TEST STRIPS

- Quick and effective coolant tests.
- All in one product.
- Prevent costly repairs.
- Works on all types of coolants.
- Available in packs of 50's



HD LONGLIFE ECO1

- Type A.
- 8 year drain intervals for heavy duty for heavy duty applications.
- 1.25 Million km drain intervals for on highway engines.
- 15,000 hour drain interval in off highway engines.
- Silicate and amine free.
- Available as Premix & Concentrate in 20L & 205L.



PGXL COOLANT

- Type A, Propylene glycol.
- Lasts 12,000 Hours or 1,000,000 km's.
- For light & heavy commercial vehicles.
- Low toxicity compared to Mono Ethylene Glycol based coolants
- Excellent protection for aluminium & heavy diesel wet sleeve liners.
- Available as Premix in 20L & 1000L.



PENRITE OIL COMPANY PTY. LTD.
ABN 25 005 001 525

88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152

Enquiries Phone: 1300-PENRITE (1300 736 7483)

Fax: 1800-PENRITE (1800 736 7483)

International Phone: 61 3 9801 0877 Fax: 61 3 9801 0977

Web: penriteoil.com.au Email: sales@penriteoil.com

NEW ZEALAND

Web: penriteoil.co.nz Email: salesnz@penriteoil.com

Ph: 0800 533 698 Fax: 0508 736 748

Technical Enquiries: tech@penriteoil.com



A Better Class of Oil