



ENGINE OILS - HEAVY DUTY

Penrite blend a range of Heavy Truck, Commercial and Farm lubricants that meets and exceed the requirements for major truck and engine manufacturers. Our heavy diesel range now spans from mono grade 2 stroke oils through to the latest European powertrains.

OEM APPROVALS

Brand:	OEM Approval:
Enviro+ 10W-40	MB-Approval 228.51
	Cummins CES 20081
	Volvo VDS-4
	Mack EO-O Premium Plus
	Renault RLD-3
Diesel HD	MB-Approval 228.31
	Cummins CES 20081
	MAN M 3575
	Volvo VDS-4
	Mack EO-O Premium Plus
	Renault RLD-3



Enviro+ 10W-40

Product Code	Pack Size	Carton Qty
EPLUS10W40005	5 Litres	4
EPLUS10W40010	10 Litres	1
EPLUS10W40020	20 Litres	1
EPLUS10W40060	60 Litres	1
EPLUS10W40205	205 Litres	1

Viscosity: 10W-40 Base Oil: Full Synthetic
Alternative Viscosities: 15W-40

Key Specifications: API CJ-4/SM, ACEA E4/E6/E9, MB 228.31, MAN 3277CRT/3477/3575, Caterpillar ECF-3-a, MTU Type 3, DAF Extended Drain, JASO DH-2

OEM Approvals: MB-Approval 228.51, Cummins CES 20081, Volvo VDS-4, Mack EO-O Premium Plus, Renault RLD-3

Penrite Enviro+ 10W-40 is a highly advanced, full synthetic OEM Warranty Approved, extended drain/mixed fleet, ultra high performance diesel (UHPD) oil. It is formulated with the highest standard additives to ensure protection against wear, corrosion, oil oxidation and sludge.



Diesel HD

Product Code	Pack Size	Carton Qty
DHD005	5 Litres	4
DHD010	10 Litres	1
DHD020	20 Litres	1
DHD060	60 Litres	1
DHD205	205 Litres	1
DHD1000LTR	1000 Litres	1

Viscosity: 15W-40 Base Oil: Premium Mineral

Key Specifications: API CJ-4/SM, ACEA E7/E9, Allison C-4, JASO DH-2, Detroit PGOS 93K218, MTU Type 2, MB 228.3, Caterpillar ECF-1-a/ECF-2/ECF-3

OEM Approvals: MB-Approval 228.31, Cummins CES 20081, Volvo VDS-4, Mack EO-O Premium Plus, Renault RLD-3 Compliant, MAN M 3575

Penrite Diesel HD is a high performance, heavy duty, low ash, OEM Warranty Approved, SAE 15W-40 premium mineral diesel engine oil designed for use in vehicles with and without Diesel Particulate Filters (DPF). It is made from a combination of hydrocracked base stocks and the latest OEM (Original Equipment Manufacturer) approved additive technology.



Diesel FX

Product Code	Pack Size	Carton Qty
DFX020	20 Litres	1
DFX060	60 Litres	1
DFX205	205 Litres	1
DFX1000LTR	1000 Litres	1

Viscosity: 15W-40 Base Oil: Premium Mineral

Key Specifications: API CI-4 PLUS/SL, ACEA E7/A3/B3, MIL-PRF-2104H/NATO O-1236, MB 228.3/229.1, MAN 3275, Allison C4, Global DHD-1, Volvo VDS-3, JASO DH-1, Cummins CES 20071/72/76/77/78, Caterpillar ECF-1-a

Penrite Diesel FX is a premium quality, mineral, SAE 15W-40, mid ash, full zinc, diesel engine oil formulated with high quality additives and hydrocracked mineral base oils. It is designed predominantly for use in four stroke heavy duty diesel engines.



Universal Farm Oil

Product Code	Pack Size	Carton Qty
UFO020	20 Litres	1
UFO205	205 Litres	1

Viscosity: 15W-40 Base Oil: Premium Mineral
Alternative Viscosities: 15W-30, 20W-40

Key Specifications: API CG-4/SJ, ACEA E3, API GL-4, MB 227.1, MAN 271, MF 1135/1139/1141/1143/1144/1145, Ford M2C159-B/C, John Deere JDM J27/JD20 A/C, New Holland 420A

Fuel Types: Petrol, Diesel, LPG

Penrite Universal Farm Oil is designed for use over a multitude of farm equipment to minimise product inventory and simplify lubricant usage on farm machinery and equipment. Universal Farm Oil is an SAE 15W-40 universal oil manufactured from advanced multi-functional additives and highly refined base oils.



HPR Diesel 5

Product Code	Pack Size	Carton Qty
HPRD5001	1 Litre	6
HPRD5005	5 Litres	4
HPRD5010	10 Litres	1
HPRD5020	20 Litres	1
HPRD5060	60 Litres	1
HPRD5205	205 Litres	1

Viscosity: 5W-40 Base Oil: Semi Synthetic
Alternative Viscosities: 5W-30, 10W-30, 10W40

Key Specifications: API CI-4 PLUS/SL, ACEA A3/B4/E7, MB 228.3/229.3, Global DLD-2/DLD-3, JASO DH-1, JASO MA, Peugeot PSA D-02, VW 502.00/505.00, Opel B040 2098, Ford M2C153-H/171-C/913-B/913-C

Penrite HPR Diesel 5 is a premium high performance semi synthetic SAE 5W-40, non-friction modified engine oil. It contains a DOUBLE LAYER of engine wear protection with FULL ZINC and Penrites advanced EXTRA TEN technology.



HPR Diesel 10

Product Code	Pack Size	Carton Qty
HPRD10001	1 Litre	6
HPRD10005	5 Litres	4
HPRD10010	10 Litres	1
HPRD10020	20 Litres	1
HPRD10060	60 Litres	1
HPRD10205	205 Litres	1

Viscosity: 10W-40 Base Oil: Semi Synthetic
Alternative Viscosities: 10W-30

Key Specifications: API CI-4 PLUS/SL, ACEA A3/B4/E7, MB 228.3/229.3, Global DLD-2/DLD-3, JASO DH-1, JASO MA, Peugeot PSA D-02, VW 502.00/505.00, Opel B040 2098, Ford M2C153-H/171-C

Penrite HPR Diesel 10 is a premium high performance semi synthetic SAE 10W-40, non-friction modified engine oil. It contains a DOUBLE LAYER of engine wear protection with FULL ZINC and Penrite's advanced EXTRA TEN technology.



HPR Diesel 15

Product Code	Pack Size	Carton Qty
HPRD15001	1 Litre	6
HPRD15005	5 Litres	4
HPRD15010	10 Litres	1
HPRD15020	20 Litres	1
HPRD15060	60 Litres	1
HPRD15205	205 Litres	1

Viscosity: 15W-50 Base Oil: Semi Synthetic
Alternative Viscosities: 15W-40, 20W-40, 20W-50

Key Specifications: API CI-4 PLUS/SL, ACEA A3/B4/E7, Ford M2C171-C/153-F/153-G, JASO MA, JASO DH-1, MB 228.3/229.3

Penrite HPR Diesel 15 is a premium high performance semi synthetic SAE 15W-50, non-friction modified engine oil. It contains a DOUBLE LAYER of engine wear protection with FULL ZINC and Penrite's advanced EXTRA TEN technology.



HPR Diesel

Product Code	Pack Size	Carton Qty
HPRD001	1 Litre	6
HPRD005	5 Litres	4
HPRD010	10 Litres	1
HPRD020	20 Litres	1
HPRD060	60 Litres	1
HPRD205	205 Litres	1

Viscosity: 20W-60 Base Oil: Premium Mineral
Alternative Viscosities: 20W-40, 20W-50, Mono 30

Key Specifications: API CH-4/SJ, ACEA A3/B3/E7, Global DLD-1, JASO MA, JASO CD Plus, Ford WSS-M2C911-A1, VW 500.00, MTU Type 2, MB 228.3

Penrite HPR Diesel is a premium high performance mineral SAE 20W-60, non-friction modified engine oil. It contains a DOUBLE LAYER of engine wear protection with FULL ZINC and Penrite's advanced EXTRA TEN technology.



Mono Truck 30 SAE 30

Product Code	Pack Size	Carton Qty
MONO30020	20 Litres	1
MONO30205	205 Litres	1

Viscosity: SAE 30 Base Oil: Premium Mineral

Key Specifications: API CF-2/CF/SG, ACEA E1, API CF-2/CF/SG, Allison C3, MB 228.0/ 227.0, MIL-L-2104F, Mack EO-K/2, Detroit 7SE-270, Caterpillar TO-2

Penrite Mono Truck 30 is a monograde diesel engine oil that has been formulated from modern additives to ensure protection against wear, corrosion, oil oxidation and sludge. It may also be used in Komatsu powershift transmissions and Allison transmissions requiring C3 oils.



Mono Truck 40 SAE 40

Product Code	Pack Size	Carton Qty	Viscosity: SAE 40	Base Oil: Premium Mineral
MONO40020	20 Litres	1		
MONO40205	205 Litres	1		

Key Specifications: API CF-2/CF/SF, MIL-L-2104F, Mack EO-K/2, MB 227.0, Detroit 7SE-270, Caterpillar TO-2

Penrite Mono Truck 40 is a monograde diesel engine oil that has been formulated from modern additives to ensure protection against wear, corrosion, oil oxidation and sludge. It is primarily designed for use in Detroit Diesel Two Stroke engines, except for 149 series.



ENGINE OILS - HEAVY DUTY

Mono Truck 50 SAE 50

Product Code	Pack Size	Carton Qty	Viscosity: SAE 50	Base Oil: Premium Mineral
MONO50020	20 Litres	1		

Key Specifications: API CF-2/CF/SF, MB 227.0, Detroit 7SE-270, Caterpillar TO-2

Penrite Mono Truck 50 is a monograde diesel engine oil that has been formulated from modern additives to ensure protection against wear, corrosion, oil oxidation and sludge. It is recommended in higher ambient conditions and may also be used in manual transmissions requiring API GL1 90 or API CC/CD 50 engine oils. It is the only viscosity grade that should be used in Detroit Series 149 engines.



Penblue (AdBlue®)

Product Code	Pack Size	Carton Qty	Colour: Clear
PENBLUE010	10 Litres	1	
PENBLUE210	210 Litres	1	
PENBLUE1000LTR	1000 Litres	1	

Key Specifications: DIN 70070, AUS 32, ISO 22241

Penrite Penblue is an aqueous solution of Urea, 32.5% in weight. (AdBlue®) SCR (Selective Catalytic Reduction) systems require a continuous provision of a solution of Urea at 32.5% in order to operate correctly. SCR technology has been developed to fulfil the requirements of emissions standards EURO 4 and EURO 5.



PENRITE PRODUCT	Litres							
	1	5	10	20	60	205	210	1000
Enviro+ 10W-40	-	●	●	●	●	●	-	-
Diesel HD	-	●	●	●	●	●	-	●
Diesel FX	-	-	-	●	●	●	-	●
Universal Farm Oil	-	-	-	●	-	●	-	-
HPR Diesel 5	●	●	●	●	●	●	-	●*
HPR Diesel 10	●	●	●	●	●	●	-	●*
HPR Diesel 15	●	●	●	●	●	●	-	●*
HPR Diesel	●	●	●	●	●	●	-	-
Mono Truck 30	-	-	-	●	-	●	-	-
Mono Truck 40	-	-	-	●	-	●	-	-
Mono Truck 50	-	-	-	●	-	-	-	-
Penblue (AdBlue®)	-	-	●	-	-	-	●	●

*On Request



Visit our website at www.penriteoil.com