



100 Celebrating
YEARS

**AUSTRALIAN OWNED AND
TRUSTED SINCE 1926** 

AUTO TRANS STOP LEAK

Last updated: 04/06/2024 4:06 pm

PRODUCT CODE PACK SIZE CARTON QTY

PRODUCT BENEFITS

Auto Trans Stop Leak has been specifically formulated to control leaks in automatic transmission systems due to deteriorating or worn seals and gaskets.

APPLICATION

Auto Trans Stop Leak has been designed for use in conventional automatic transmissions units. It is suitable for cars, 4WDs, and light commercial vehicles.

Auto Trans Stop Leak is suitable for use with vehicles that use the following Penrite automatic transmission fluids -

- [Penrite ATF BMV](#)
- [Penrite Multi-Vehicle DX-III](#)
- [Penrite Multi-Vehicle LV](#)
- [Penrite Multi-Vehicle MHP](#)
- [Penrite Multi-Vehicle FS](#)
- [Penrite ATF 33 Type F](#)
- [Penrite ATF Top Up](#)
- [Penrite Classic ATF](#)

Note: Cannot be used in CVT or DCT type transmissions.

FOR BEST RESULTS:

- One 375ml bottle treats up to 10 litres of transmission fluid.
- Add one bottle (375ml) through transmission filling point.

Note:

If leaks are still evident after use, replacement or repair of the transmission may be required

PRODUCT BENEFITS

- Revitalises worn seals and gaskets
- Reduces leaks
- Contains additives to maintain performance
- Compatible with Mineral and Synthetic ATF's
- Extends component life
- Compatible with automatic transmission sensors
- Reduces noise and wear

PRODUCT PERFORMANCE LEVELS

TYPICAL DATA

Colour	Red
Density at 15°C, kg/L	0.888
Viscosity, Kinematic, cSt at 40°C	130
Viscosity, Kinematic, cSt at 100°C	15.0
Viscosity Index	118
Phosphorus, Mass %	0.032

