



PENRITE



85% REDUCTION
IN LANDFILL
WASTE

BRAKE FLUID DOT 4 ESP

Last updated: 23/01/2018 3:05 pm

| PRODUCT CODE | PACK SIZE | CARTON QTY |
|---------------|-----------|------------|
| BFDOT4ESP0005 | 500mL | 6 |

PRODUCT BENEFITS

BRAKE FLUID DOT 4 ESP is a premium quality, non-silicone & non- mineral / petroleum based, fully synthetic low viscosity brake fluid optimized for use in vehicles with **ABS** (Anti Brake Skid), **AEB** (Auto Emergency Braking) and **ESP** (Electronic Stability Program) systems as well as standard brake and clutch applications.

ADDITIONAL PRODUCT INFORMATION

- [Click Here](#) for Technical Bulletin on Brake Fluid Testers
- [Click Here](#) for Technical Bulletin on Choosing the Right Brake Fluid
- [Click Here](#) for Technical Bulletin on Rolls Royce 363 and Mineral Brake Fluid

APPLICATIONS

BRAKE FLUID DOT 4 ESP is recommended for re-fill or top-up of brake and clutch systems in passenger cars, 4WD, motorcycles, light and heavy duty commercial vehicles, mining, construction and agricultural equipment that require a non petroleum based DOT 3, DOT 4 or Super DOT 4 brake & clutch hydraulic fluid. It is highly suited for vehicles fitted with ESP, ABS and AEB vehicle control systems and is especially designed to operate in lower ambient temperatures and to provide faster response times than standard Dot 3 or Dot 4 Brake Fluids.

BRAKE FLUID DOT 4 ESP is suitable for use in all brake and clutch systems where the manufacturer specifies either DOT 3 or DOT 4 fluids. It can also be safely mixed with either Dot 3 or Dot 4 fluids if topping up is required. It can be used for first fill or refilling a brake or clutch system. For best results, the system should always be flushed with Penrite Brake Fluid DOT 4 ESP prior to first fill or before refilling the system. It should be changed according to the manufacturer's specifications.

PLEASE NOTE

- Do not mix this product with SILICONE DOT 5 or MINERAL type brake fluids.
- For vehicles that require mineral based products i.e. Citroen, **Penrite LHM Plus** should be used.
- Not mixable with Silicone type assembly compounds
- Avoid contact with skin, varnish & paint. If skin contact occurs wash with water.

CAUTION

Brake Fluids are naturally hygroscopic and will absorb water from the air. This will lower the effectiveness of the product. After opening bottle, ensure cap is resealed tightly to avoid water contamination.

PRODUCT BENEFITS

- Improved braking and faster reaction than standard brake fluids
- Specially formulated for use in cars with ABS
- Optimised for vehicles fitted with Electronic Stability Control
- High boiling point 260°C / 500°F
- High wet equilibrium boiling point (165°C) ensuring retention of stopping power over life of fluid.
- Suitable for all hydraulic brake & clutch systems where DOT 3 & DOT 4 fluid is specified.

INDUSTRY & MANUFACTURER'S SPECIFICATIONS

- DOT 3
- DOT 4
- FMVSS 116 DOT 4
- ISO 4925 Class 3
- ISO 4925 Class 4
- ISO 4925 Class 6
- SAE J1704





PENRITE



**85% REDUCTION
IN LANDFILL
WASTE**

TYPICAL DATA

| | |
|--|------------------|
| Colour | Amber |
| Density at 20°C, kg/L | 1.055 |
| Viscosity, Kinematic, cSt at -40°C | 700 |
| Viscosity, Kinematic, cSt at 100°C | 2.1 |
| Equilibrium Reflux Boiling Point (wet), (typical) | 165°C / 330°F |
| Equilibrium Reflux Boiling Point (dry), (typical) | 260°C / 525°F |
| pH | 7.0-11.5 |