

# CLASSIC 20W-50 (UK)

#### Premium Mineral Engine Oil

Issue: May 2017


| PRODUCT CODE | PACK SIZE | CTN/QTY |
|--------------|-----------|---------|
| CLAS20W50001 | 1 Litre   | 6       |
| CLAS20W50005 | 5 Litre   | 4       |
| CLAS20W50020 | 20 Litre  |         |
| CLAS20W50205 | 205 Litre |         |

## Description

Classic 20W-50 is a premium mineral, multigrade engine oil designed specifically for classic light duty petrol and diesel fuelled vehicles manufactured between the 1970s to the mid-1990s.

### **Applications**

**Classic 20W-50** is suitable for passenger cars, motorcycles, 4WD's, light & heavy duty commercial vehicles that originally specified SAE 30, SAE 20W-40 or SAE 20W-50 engine oils and operate in cooler ambient temperatures. This oil is suitable for use for both winter and summer conditions.



Classic 20W-50 meets API SL/CF engine oil specifications and contains optimised ZINC levels for added anti-wear protection for older engines.

Classic 20W-50 also meets the JASO MA specification, making it suitable for use in motorcycles fitted with wet clutches.

#### Product Benefits

- Contains a balanced formulation of modern additives to suit vehicles of this period, exceeding the originally required oil specifications
- Maintains engine cleanliness and includes optimised zinc levels for wear protection
- Shear stable formulation
- Suitable for use as a winter and summer engine oil

#### **Industry Specifications**

API SL/CF JASO MA

#### **Typical Data**

| Density at 15°C, kg/L             | 0.880 |
|-----------------------------------|-------|
| Flash Point, °C                   | 220   |
| Viscosity, Kinematic, cSt         |       |
| at 40°C                           | 152   |
| at 100°C                          | 17.5  |
| Viscosity Index                   | 125   |
| Viscosity, Cold Cranking @ -15 °C | 5800  |
| Magnesium, mass %                 | 0.136 |
| Zinc, mass %                      | 0.108 |
| Phosphorus, mass %                | 0.098 |
|                                   |       |





Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



