



PENRITE



85% REDUCTION
IN LANDFILL
WASTE

CLASSIC MINI 20W-50 (Mineral)

Last updated: 17/11/2022 3:36 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
CLASMINI005	5L	4

PRODUCT BENEFITS

Classic Mini is a premium mineral, high zinc, SAE 20W-50 viscosity, API SJ/CE, GL-4 engine oil, designed in conjunction with International Mini Clubs and owners in the UK and Australia specifically for all classic Minis (Austin, BMC & Leyland). It has been designed to provide an excellent combination of engine protection and smooth gear shifts. Classic Mini contains a high zinc anti-wear package for ultimate engine wear protection combined with premium quality base oils and additives that exceed original manufacturers specifications for these vehicles.

APPLICATION

Classic Mini has been developed for use in classic Mini' from 1959 to 2000 where a combined engine and gearbox utilises the same oil. It can also be used in other vehicles from the period including Mini Moke & Austin Metro. Classic Mini can be used in derivatives such as -

- Austin 850
- Austin Partner
- Austin Mini
- Austin Seven
- Innocenti Mini
- Leyland Mini
- Mini Wildgoose
- Morris 850
- Morris Mascot
- Morris Mini
- Riley Elf
- Rover Mini
- Wolseley 1000
- Wolseley Hornet

Classic Mini is also suitable for other combined engine / gearbox vehicles manufactured by Austin, BMC & Leyland such as -Morris 1000S, 1300 Nomad, 1100, 1100S, 1500, 1500 Nomad, 850 VanAustin 1800 Mk 1 & MK 2, X6, Tasman / Kimberley ()

Classic Mini has been specifically formulated to replace older style 20W-40, 20W-50 or where straight 30 grades were originally used and specified in these vehicles.

NOTE: when changing oil, Penrite recommend using **Penrite Engine Flush**, a fast acting, solvent free, engine cleaning formulation that removes engine deposits, sludge and contaminants with the oil service drain. It contains added zinc for engine wear protection and its fast acting formulation works in 10 minutes.

PRODUCT BENEFITS

- Excellent combined engine and gearbox lubrication for all classic Minis
- Smoother gear shift and excellent gear wear protection
- SAE 20W-50, stay-in-grade engine protection
- Exceeds original manufacturers specifications
- Exceeds OEM's drain specifications
- High zinc levels for wear protection
- Provides protection against rust & corrosion

PRODUCT PERFORMANCE LEVELS

- API GL-4
- API SJ/CE
- CCMC G2
- MB 227.1.
- MIL-L-2104D





PENRITE



**85% REDUCTION
IN LANDFILL
WASTE**

**SUITABLE FOR USE WHERE SPECIFICATIONS BELOW ARE REQUIRED
(FOR OUT OF WARRANTY SERVICE)**

- API SF
- API SG
- API SH

TYPICAL DATA

Colour	Amber
Density at 15°C, kg/L	0.879
Viscosity, Kinematic, cSt at 40°C	176
Viscosity, Kinematic, cSt at 100°C	20.0
Viscosity Index	131
Zinc, Mass %	0.139
Phosphorus, Mass %	0.142
Magnesium, Mass %	Nil