



COPPER EZE

Anti Seize Lubricant

Issue: April 2017

PRODUCT CODE	PACK SIZE	CTN QTY
CEZE0001	100 gram	6
CEZE0005	500 gram	6

Description

Copper Eze is a bentone based anti-seize grease containing micro-size copper, zinc oxide and additional synthetic base oil that will resist temperatures of up to 1093°C.

Application

Copper Eze is used to coat flanges, threads, nuts, bolts that are subject to corrosion or seizure etc. prior to assembly, to enable easy disassembly for service or replacement. It is also ideal for exhaust manifold studs, exhaust clamps, turbocharger connections, spark plug threads and in drum and disc brake assemblies. It can stop brake squeaking if applied to the back of disc brake pads and is ideal for disc brake calliper sliding pins.

Copper Eze may be used in all types of industries including corrosive marine and mining environments as well as the petroleum (exploration, refining) industry.

Copper Eze is ideal for boat trailer wheel studs to stop them rusting and seizing. It can be used on external hinges, flanges, screws, nuts & bolts to prevent seizure and corrosion in automotive, marine, industrial, agricultural and general domestic environments.

It may be used at all temperatures from sub-zero to 1093°C.

Product Benefits

- Protects against corrosion in severe environments.
- Reduces friction and wear
- Synthetic lubricant forms a tough plating in metal pores to prevent galling
- Low toxicity
- Does not wash or burn off in everyday use
- Protects against seizing
- Resists high temperatures
- Reduces torque during assembly

CAUTION

Should not be used on internal components of engines, transmissions or brake systems.

Industry Specifications

NLGI 1.5

Typical Data

Appearance

Soap Type

Dropping Point, °C

Solidification Point, °C

Copper
Bentone Clay
non-melt
-18

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. A MSDS is available on request.



PENRITE



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 7483)
Fax: 1800-PENRITE (1800 736 7483)
International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748

United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**

