



100 Celebrating YEARS

AUSTRALIAN OWNED AND TRUSTED SINCE 1926

CV JOINT GREASE

Last updated: 21/09/2017 10:45 am

PRODUCT CODE	PACK SIZE	CARTON QTY
CVJGR0001	100g	6

PRODUCT BENEFITS

CV Joint Grease is a premium heavy duty, lithium complex, NLGI No. 1.5 grease containing molybdenum disulphide and graphite for boundary protection against the heaviest sliding, shock or impact loading conditions. It is a smooth black grease formulated with extreme pressure additives for maximum loading applications, anti-wear protection and water washout resistance. It contains effective rust, oxidation and corrosion inhibitors and will resist "squeeze out" from surfaces requiring lubrication under load conditions.

APPLICATION

CV Joint Grease is ideal for Constant Velocity (CV) and Universal Joints in automotive applications where a heavy duty, high load carrying grease is required. It is perfect for ball joints, king pins and general chassis lubrication.

CV Joint Grease can also be used on plain bearings, slow speed bearings (not anti-friction) and roller bearings in industrial applications. It is also suitable for use in heavy duty applications in mining, construction, agriculture and industry in general where an extreme pressure, high load carrying, grease is required.

CV Joint Grease has excellent water washout resistance where in these applications, provides outstanding protection against rust and corrosion. It is also extremely shear stable for both high and low temperatures and provides protection for intermittent operation up to 200°C.

PRODUCT BENEFITS

- Extreme pressure grease for high load applications
- Contains molybdenum disulphide for boundary lubrication protection
- High product stability and shear resistance for long life protection
- Excellent water washout resistance
- Protects against rust and corrosion in wet environments
- Good adhesion and resists "squeeze out"
- Handy 100gm tube perfect for 1 x CV Joint

PRODUCT PERFORMANCE LEVELS

- NLGI 1.5

TYPICAL DATA

Colour	Grey/Black
NLGI Grade	1.5
Soap Type	Lithium Complex
Density at 15°C, kg/L	0.9
Base Oil Viscosity, ISO	460
Operating Temperature Range °C	0°C to +160°C
Appearance	Smooth/Tacky
Timkin OK Load, kg	>20
Drop Point, °C	300
4-ball Weld Load, kg	500
Rust Prevention Rating, D1743	Pass
Pumpability, Lincoln Ventmeter @ 0°C, psi	800
Water Washout, 1hr/80°C, %	<5

