



CYL OIL MINERAL 900

Steam Cylinder Oil

Issue: December 2015

Product Code	Pack Size	Ctn / Qty
CYL900205	205 Litre	1



PENRITE

Description

Penrite Cyl Oil Mineral 900 is a heavy straight run mineral oil manufactured via a hydro-treating process that **DOES NOT** contain any compounding additives.

Application

Penrite Cyl Oil Mineral 900 may be used for the lubrication of steam cylinders as well as valve lubrication and is suitable for heavily loaded slow moving bearings and gears, where a demulsifiable oil is required.

Penrite Cyl Oil Mineral 900 can also be used in old gearboxes where a "250" style oil is required and no extreme pressure additives are needed.

Product Benefits

- Extended oil life due to inherent oxidation stability.
- Good demulsibility characteristics of the pure mineral oil allows for outstanding lubrication.

Typical Data

Density at 15°C	0.911
Viscosity, Kinematic, cSt	
at 40°C	930
at 100°C	41.9
Viscosity Index	74
Pour Point, °C	+2.0

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)
International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**



United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com