



# DIESEL TOTAL SYSTEM CLEANER

## Fuel System Cleaner

Issue: April 2017

PRODUCT CODE	PACK SIZE	CTN / QTY
ADDTSC375	375 ml	6

### Product Description

**Diesel Total System Cleaner** is a professional strength diesel fuel additive that effectively cleans the entire fuel system from fuel tank to engine. It uses a powerful and proven additive technology that cleans stubborn deposits and inhibits new contaminant build ups forming.

### Application

**Diesel Total System Cleaner** is suitable for use in all diesel engines. It is safe for use with diesel particulate filters (DPF's) and SCR exhaust gas recirculation systems and it can be used in either direct injected or common rail induction systems including turbo and supercharged engines.

**Diesel Total System Cleaner** cleans carbon deposits from inlet valves that can affect engine efficiency and performance. It unblocks injectors and provides a lubricant to the fuel system that increases the service life of the fuel system components.

**Diesel Total System Cleaner** dislodges and removes fuel system contaminants especially those found in commercial pump fuel that can affect the engine's performance. Its powerful formulation is designed to clean in one tank of fuel.

### Dosage

1 x 375ml bottle treats 75 Litres of Diesel fuel.

**Please Note:** If your vehicle is fitted with a "Capless" Fuel Filler system, we recommend using the vehicles emergency fuel filling funnel when adding this product to the fuel tank.

**Diesel Total System Cleaner** should be used every 10,000km to clean, maintain and prevent fuel system deposits being formed. This is particularly important for intake valve deposits that can build up after only 2000km if poor quality fuel is used. Penrite recommend the use of **Penrite Diesel Injector Cleaner** every 2500 KM to maintain maximum benefits of the **Diesel Total System Cleaner**.

### Product Benefits

- Cleans fuel tank, lines, injectors, rails and inlet valves
- Prevents fuel system deposits and contaminants
- Improves power and performance
- Improves fuel economy and reduces emissions
- Improved idling and engine starting
- Reduces fuel consumption
- Safe for emission systems and oxygen sensors
- Reduces soot and smoke emissions
- Safe with Bio-Diesel B10

### Typical Data

Colour	STRAW
Density	0.903
Viscosity, Kinematic, cSt at 40°	3.3
at 100°C	1.4
Flash Point °C	71°C

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



PENRITE



**PENRITE OIL COMPANY PTY LTD**, 88 Lewis Road, Wantirna South  
 Victoria AUSTRALIA 3152, ABN 25 005 001 525  
 Enquiries: Phone 1300-PENRITE (1300 736 748)  
 Fax: 1800-PENRITE (1800 736 748)  
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977  
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748  
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234  
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN  
 FAMILY OWNED  
 SINCE 1926**

