



ENVIRO+™

ENVIRO+ DL-1

Full Synthetic Engine Oil

Issue: April 2017

PRODUCT CODE	PACK SIZE	CTN / QTY
EPLUSDL1001	1 Litre	6
EPLUSDL1005	5 Litre	4
EPLUSDL1010	10 Litre	
EPLUSDL1020	20 Litre	
EPLUSDL1020BOX	20 Litre	
EPLUSDL1060	60 Litre	
EPLUSDL1205	205 Litre	

Product Description

ENVIRO+ DL-1 is a premium full synthetic, SAE 5W-30 engine oil. It is manufactured using the latest advances in mid SAPS (Sulphated Ash, Phosphorus and Sulphur)* additive technology.

Enviro+ DL-1 meets the requirements of European ACEA C2 and is On-File for JASO DL-1 applications.

Application

ENVIRO+ DL-1 is designed for use in modern 4, 6 & 8+ cylinder multi-cam, multi-valve (including VVT), naturally aspirated, supercharged & turbocharged low emission engines.

ENVIRO+ DL-1 is a SAE 5W-30, mid SAPS oil designed for use in European petrol and light duty diesel passenger cars and 4WDs that require an ACEA C2 engine oil and in Japanese light duty diesels that specify JASO DL-1 in the owner's handbook, especially those fitted with Diesel Particulate Filters (DPFs).

Applications include –

Alfa Romeo 159 Series
 Fiat 500/Freemont/Panda/Ritmo/Ducato
 FUSO Canter
 Hyundai i30/i40/ix35/Tucson
 Jeep Cherokee
 Land Rover Discovery IV/Sport/Freelander
 Mitsubishi ASX/Outlander/Triton
 Peugeot 207/307/308/407/508/3008/4007/RCZ
 Range Rover Evoque/Hybrid Sport/ Sport
 and many others.

Citroen C3/C4/C5/6/Berlingo/Dispatch
 Ford Mondeo MA Series
 Honda Civic
 Iveco Daily
 Kia Carnival/Sorrento/Sportage
 Mazda 3/6/CX3/CX5/CX7
 Subaru Forester/Outback
 Peugeot Expert/Partner
 Toyota Fortuna/Hilux/Prado/Land Cruiser/Rav4

Vehicle and Fuel Types

ENVIRO+ DL-1 is suitable for use in passenger cars, 4WD's & light commercial vehicles and can be used with Petrol / E10 & light duty diesel engines with / without a DPF. It is not recommended for use in motorcycles.

Product Benefits

- Maximises DPF life and engine performance
- On File JASO DL-1 registered product
- Extends exhaust catalyst life
- Long drain intervals
- Emissions system friendly
- Maximises fuel economy**



PENRITE



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 748)
 Fax: 1800-PENRITE (1800 736 748)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**






Industry Specifications

ACEA C2
Fiat 9.55535-S1

Approvals

JASO DL-1 - Registration Number D061POA001

Manufacturer Specifications



PRODUCT MEETING JASO M 355
COMPANY GUARANTEEING THIS PRODUCT:
PENRITE OIL COMPANY PTY. LTD.

Typical Data

Density at 15°C, kg/L	0.851
Viscosity, Kinematic, cSt	
at 40°C	53
at 100°C	9.5
Viscosity Index	163
HT/HS Viscosity at 150°C	2.96
Cold Cranking Viscosity, cP -30°C	4130
Zinc, Mass %	0.080
Phosphorus, Mass %	0.073
Sulphated Ash, mass %	0.59

*Low SAPS oils may sometimes be referred to as "Low Ash" oils

**Fuel economy improvement of >2.9% compared to reference oil in the M111FE engine test

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



Available in



85% REDUCTION IN LANDFILL WASTE



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)
International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748
United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**

