



100 Celebrating
YEARS

AUSTRALIAN OWNED AND TRUSTED SINCE 1926 

ENVIRO+ K3 5W-30

Last updated: 30/11/-0001 12:00 am

PRODUCT CODE	PACK SIZE	CARTON QTY
XEPLUSK3001	1L	12

PRODUCT BENEFITS

ENVIRO+ K3 is a premium grade, full synthetic SAE 5W-30 engine oil developed for low emission passenger car and light duty vehicles fitted with after-treatment systems such as gasoline catalytic converter or diesel particulate filter (DPF) technology. It provides excellent protection against wear and sludge build up.

APPLICATION

ENVIRO+ K3 can be used in petrol (gasoline), LPG, hybrid & diesel engines whether naturally aspirated, turbocharged or supercharged.

ENVIRO+ K3 is designed for use where **API SN** and **ACEA C3** lubricants are specified. It is also ideal for use where **ACEA A1/B1 (Obsolete)**, **ACEA A5/B5** and **ILSAC GF-5** lubricants are required. Other examples include engines used in Kia, Hyundai and Chevrolet vehicles.



PRODUCT BENEFITS

- Long oil life
- Safe for DPF and oxygen sensors
- Minimises sludge formation
- Maximises wear protection
- Reduces piston deposits

PRODUCT PERFORMANCE LEVELS

- ACEA C3
- API SN

SUITABLE FOR USE WHERE SPECIFICATIONS BELOW ARE REQUIRED

(FOR OUT OF WARRANTY SERVICE)

- ACEA C2
- MB 229.31

TYPICAL DATA

Density at 15°C, kg/L	0.853
Viscosity, Kinematic, cSt at 40°C	70
Viscosity, Kinematic, cSt at 100°C	12.0
Viscosity Index	163
Cold Cranking Viscosity, cP at -30°C	5870
Zinc, Mass %	0.088
Sulphated Ash, Mass %	0.8
Total Base Number (TBN)	7.7