



100 Celebrating
YEARS

AUSTRALIAN OWNED AND TRUSTED SINCE 1926 

EXP SUPA DSL 10W-30

Last updated: 22/11/2017 11:51 am

PRODUCT CODE	PACK SIZE	CARTON QTY
--------------	-----------	------------

PRODUCT BENEFITS

EXP SUPA DSL 10W-30 is an **OEM Approved**, premium mineral engine oil manufactured from ultra-pure, advanced hydrocracked based stocks and new leading edge additive technology for maximum engine protection.

EXP SUPA DSL 10W-30 is approved by Ford Motor Company for use where WSS-M2C171-F1 specifications are required. It is **licensed** by the API (American Petroleum Institute) to meet CK-4, CJ-4 and CI-4 specifications ensuring quality and satisfaction. It also meets many other manufacturers specifications.

APPROVALS AND LICENSES

•
•

APPLICATION

EXP SUPA DSL 10W-30 is suitable for use in diesel engines in pick-ups, passenger cars, SUVs, and in newer commercial engines in trucks, tractors, agricultural & earthmoving equipment, fork lifts and stationary engines.

EXP SUPA DSL 10W-30 is designed for use in modern naturally aspirated, supercharged and turbocharged diesel engines and is ideal for those that are common rail/direct injection.

EXP SUPA DSL 10W-30 is ideal for many vehicles fitted with a DPF (Diesel Particulate Filter) that require a lower SAPS engine oil meeting API CJ-4 or CK-4. On road, it is suitable for many Euro IV, Euro V and Euro VI emissions specification engines.

PRODUCT BENEFITS

- **OEM Approved** for Ford WSS-M2C171-F1
- Latest **FULL ZINC** anti-wear additive package for ultimate engine wear protection
- Protects against corrosion and engine sludge
- Keeps pistons cleaner for longer
- Reduces oxidative thickening compared to API CJ-4 oils
- Reduces wear by improved control of soot deposits
- Shear stable viscosity modifier helps to maintain oil pressure

PRODUCT PERFORMANCE LEVELS

- | | |
|-----------------|----------------------|
| • ACEA E9 | • Ford M2C171-E |
| • API CI-4 PLUS | • Ford WSS-M2C171-F1 |
| • API CJ-4 | • JASO DH-2 |
| • API CK-4 | • MB 229.31 |

TYPICAL DATA

Density at 15°C, kg/L	0.873
Viscosity, Kinematic, cSt at 40°C	83
Viscosity, Kinematic, cSt at 100°C	11.8
Viscosity Index	135
Cold Cranking Viscosity, cP at -30°C	6800
Zinc, Mass %	0.126
Phosphorus, Mass %	0.112
Sulphated Ash, Mass %	1.00
Total Base Number (TBN)	10.2

