



PENRITE

# EXTREME PRESSURE GREASE

## Lithium Grease

Issue: May 2016

Product Code	Pack Size	CTN / QTY
EPGR00045	450gm	6
EPGR0005	500gm	6
EPGR0025	2.5kg	4
EPGR020	20kg	1
EPGR055	55kg	1
EPGR180	180kg	1



### Description

**EXTREME PRESSURE GREASE** is an NLGI No 2, red coloured, general purpose grease manufactured from high quality base oils and uses a lithium soap base.

### Application

**Extreme Pressure Grease** is suitable for use in all general grease applications in automotive and industrial service. This includes plain bearings, slow speed wheel and anti-friction bearings, chassis grease, general plant lubrication and agricultural and construction equipment lubrication.

**Note:** For high speed, high temperature applications, including wheel bearings of vehicles fitted with disc brakes, **Penrite High Temperature Wheel Bearing Grease** should be used.

### Product Information

- Resists water wash out.
- Protects against rust and corrosion
- Long service life.
- Tackiness additive helps grease stay in place.

### Industry Specifications

NLGI 2

ISO 6743

DIN 51502: KP2K-30

### Typical Data

Soap Type	Lithium
Water Washout at 80°C, %	4
Base Oil Viscosity, ISO	320
Drop Point, °C	190
Colour	Red
Timken OK Load, kg	18
Continuous Operating Temperature, °C	-20 to +130
Four Ball Weld Load, kg	400

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request



**PENRITE OIL COMPANY PTY LTD**, 88 Lewis Road, Wantirna South  
 Victoria AUSTRALIA 3152, ABN 25 005 001 525  
 Enquiries: Phone 1300-PENRITE (1300 736 748)  
 Fax: 1800-PENRITE (1800 736 748)  
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977  
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748

**PROUDLY AUSTRALIAN  
 FAMILY OWNED  
 SINCE 1926**



**United Kingdom and EU** Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234  
 Website: [www.penriteoil.com](http://www.penriteoil.com), Email: [penrite@penriteoil.com](mailto:penrite@penriteoil.com)