



PENRITE

FULL SYNTHETIC 5W-30

Full Synthetic Engine Oil

Issue: June 2017

PRODUCT CODE	PACK SIZE	CTN QTY
EDS05001	1 Litre	6
EDS05004	4 Litre	4
EDS05006	6 Litre	3
EDS05020	20 Litre	
EDS05060	60 Litre	
EDS05205	205 Litre	

Product Description

Full Synthetic 5W-30 is a premium, full synthetic, SAE 5W-30 engine oil, engineered to provide **Complete Protection** for engine durability and cleanliness. It features the latest additive technology with a **FULL ZINC** anti wear additive package and a low shear rate viscosity modifier, to ensure additional protection against wear, corrosion, oil oxidation, piston deposits and sludge under all conditions.

Full Synthetic 5W-30 exceeds API SL and ACEA A1/B1, A5/B5 as well as many other specifications.

Application

Full Synthetic 5W-30 is designed for use in modern 4, 6 & 8+ cylinder multi-cam, multi-valve (including VVT), naturally aspirated, supercharged & turbocharged engines.

Full Synthetic 5W-30 is designed for use where SAE 5W-30 and SAE 5W-20 grade oils are recommended in the owners handbook. It may also be used in petrol and light duty diesel engines where ACEA A3/B3 or A3/B4 is specified by the manufacturer. It is formulated to meet the latest generation Ford Euro 5 and Euro 6 petrol and diesel emission legislation. It is also suitable for Ford wet timing belt technology and compatible with Ford specifications WSS M2C912A, WSS M2C913-A/B/C/D.

Full Synthetic 5W-30 is suitable for use in many late model Hyundai, Kia, Mazda, Mitsubishi, Nissan, Toyota and Fords such as Fiesta, Focus, EcoSport, Kuga, Mondeo, Mustang, Ranger, Territory and Transit.

Full Synthetic 5W-30 is suitable for use in passenger cars, 4WD's and light commercial vehicles. It is compatible with Petrol/LPG (Dual Fuel), E10, Diesel and most other conventional fuels. If using with E85 fuel, Penrite recommend more frequent oil change periods.

Product Benefits

- Engineered to provide **COMPLETE PROTECTION** for engine durability & cleanliness.
- **FULL ZINC** anti-wear additive package for ultimate engine wear protection
- **EUROPEAN ACEA A1/B1 & A5/B5** extended drain performance
- **FULL SYNTHETIC** base oil for heat resistance and high performance
- **LOW SHEAR VI** Improvers reduce oil consumption and maintains oil pressure
- Longer engine life by reducing formation of high temperature engine deposits
- Proven and trusted protection for performance engines

Industry Specifications

API SL* ACEA A1/B1, A5/B5 Renault RN 0700 Ford M2C913-B/C/D

* Passes all engine test performance requirements of API SN and SM but although using the same base chemistry, cannot claim API SM or SN due to the full zinc content.

Typical Data

Density at 15°C, kg/L	0.852
Viscosity, Kinematic, cSt	
at 40°C	52
at 100°C	9.6
Viscosity Index	170
Viscosity, Cold Cranking @ -30 °C	3660
Zinc, mass %	0.105
Sulphated Ash, mass %	1.09
Phosphorus, mass %	0.096
Base Number	10.1

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 748)
 Fax: 1800-PENRITE (1800 736 748)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**

