



**100** Celebrating  
**YEARS**

**AUSTRALIAN OWNED AND TRUSTED SINCE 1926** 

## HI-PER 2 STROKE (Semi Syn.)

Last updated: 30/11/-0001 12:00 am

PRODUCT CODE	PACK SIZE	CARTON QTY
SEHPTS001	1L	6

### PRODUCT BENEFITS

**Hi-Per Two Stroke** is a high performance, semi synthetic, low smoke, low ash two stroke engine oil made from the latest synthetic additives and premium base oils. It exceeds many manufacturer requirements including API TC, JASO FC & ISO EG-C requirements.

### APPLICATION

**Hi-Per Two Stroke** is suitable for use in all types of two stroke engines including motorcycles, mopeds and scooters that use either a premix or oil injection system. It is suitable for use in two stroke chainsaws, brush cutters, lawn mowers and other gardening equipment in domestic and industrial use. It is also suitable for stationary engines and industrial power units.

**Hi-Per Two Stroke** is suitable for use and exceeds the requirements for Sea-Doo Personal Water Craft (PWC).

### MIXING RATIO CHART

[Click here](#) to view a comprehensive mix ratio chart

Fuel Oil Ratio	Petrol	Oil
25:1	5 Litre	200ml
50:1	5 Litre	100ml
100:1	5 Litre	50ml

**Please Note:** A 58mm cap with pouring tap is available to fit 20 litre packs. <https://penriteoil.com.au/products/58mm-plastic-tap>

### PRODUCT BENEFITS

- Low Smoke, Low Ash formulation
- Extends engine life
- Good anti-scuff properties
- Maximises spark plug life
- Reduces exhaust port blockages
- Keeps piston rings free from deposits
- Mixes readily with petrol
- Enhanced lubricity and detergency, keeping engines clean

### PRODUCT PERFORMANCE LEVELS

- API TC
- ISO EG-C
- JASO FC

### TYPICAL DATA

Colour	Red / Orange
Density at 20°C, kg/L	0.862
Viscosity, Kinematic, cSt at 40°C	57
Viscosity, Kinematic, cSt at 100°C	9.0
Viscosity Index	136
Sulphated Ash, Mass %	0.09
Total Base Number (TBN)	1.6

