



HYDRAULIC JACK OIL

Hydraulic Oil

Issue: December 2014

Product Code:	Pack Size:	Ctn / Qty
HJO0005	500ml	6



Description

Penrite Hydraulic Jack Oil is a low zinc, premium quality ISO 46 hydraulic oil made from selected base stocks and an advanced anti-wear additive.

Application

Penrite Hydraulic Jack Oil is recommended for use in all types of hydraulic jacks and hoists.

Penrite Hydraulic Jack Oil is also suitable for use in systems that use vane, piston or gear pumps, airline lubricators, vacuum pumps, lightly loaded gear sets and bearings (such as headstocks, windmill gears) and hydraulic hoists and jacks. It may also be used in some types of reciprocating and piston compressors where this type of oil is called for.

Penrite Hydraulic Jack Oil is available only in a handy 500ml pack.

Product Benefits

- Formulated to combat rust, oxidation, wear and foaming.
- Reduces sludge formation.
- Compatible with silver components.
- Provides good water separation.
- Compatible with other hydraulic oils.

Industry Specifications

Denison HF0, HF1, HF2
DIN 51524 Part 2 (HLP Type)

Vickers I-286-S, M-2950-S
US Steel 136, 127

Cincinnati Milacron P-69 (HM)

Typical Data

Density at 15°C, kg/L	0.872
Viscosity, Kinematic, cSt	
at 40°C	44.6
at 100°C	6.8
Viscosity Index	98
Zinc, mass %	0.032

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 748)
 Fax: 1800-PENRITE (1800 736 748)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**



United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com