



100 Celebrating
YEARS

**AUSTRALIAN OWNED AND
TRUSTED SINCE 1926** 

HYDRAULIC JACK OIL

Last updated: 13/01/2025 3:46 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
HJO0005	500mL	6

PRODUCT BENEFITS

Penrite Hydraulic Jack Oil is a low zinc, premium quality ISO 46 hydraulic oil made from selected base stocks and an advanced anti-wear additive.

Note - New Improved Packaging with nozzled dispenser

APPLICATION

Penrite Hydraulic Jack Oil is recommended for use in all types of hydraulic jacks and hoists.

Penrite Hydraulic Jack Oil is also suitable for use in systems that use vane, piston or gear pumps, airline lubricators, vacuum pumps, lightly loaded gear sets and bearings (such as headstocks, windmill gears) and hydraulic hoists, trolley and bottle jacks. It may also be used in some types of reciprocating and piston compressors where this type of oil is called for.

Penrite Hydraulic Jack Oil is available only in a handy 500ml pack.



PRODUCT BENEFITS

- Formulated to combat rust, oxidation, wear and foaming.
- Reduces sludge formation
- Compatible with silver components
- Provides good water separation
- Compatible with other hydraulic oils

PRODUCT PERFORMANCE LEVELS

- Cincinnati Milacron P-69 (HM)
- Denison HF-0
- Denison HF-1
- Denison HF-2
- DIN 51524 Part 2 (HLP Type)
- ISO 46
- ISO 6743 Part 4, Type HM
- US Steel 126
- US Steel 127
- Vickers I-286-S
- Vickers M-2950-S

TYPICAL DATA

Colour	Amber
Density at 15°C, kg/L	0.866
Viscosity, Kinematic, cSt at 40°C	44.6
Viscosity, Kinematic, cSt at 100°C	6.8
Viscosity Index	98
Zinc, Mass %	0.032