



**100** Celebrating  
**YEARS**

**AUSTRALIAN OWNED AND TRUSTED SINCE 1926** 

# INDGREASE 1615WR

Last updated: 21/07/2014 12:20 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
INDGR1615WR020	20Kg	

## PRODUCT BENEFITS

**Indgrease 1615WR** is an NLGI 1.5, calcium sulphonate complex thickened extreme pressure lubricating grease. The grease contains mineral oil base with antioxidants and corrosion inhibitors. The product does not contain conventional EP and anti-wear additives as they are built in as an integral part of the soap structure.

## APPLICATION

**Indgrease 1615WR** is a modern high performance product especially suitable for industrial applications. The extreme load carrying capacity and the excellent water resistance make the product a perfect choice for heavily loaded applications or wet and corrosive environments.

**Indgrease 1615WR** has a functional soap () that gives the product excellent load carrying capacity making it suitable for heavily loaded applications.

**Indgrease 1615WR** is suitable for applications including in the journals of antifriction bearings used in equipment in as paper mills and steel rolling mills.

## PRODUCT BENEFITS

- Superb mechanical stability
- Good corrosion protection
- Excellent water resistance
- Exceptional load carrying capacity

## PRODUCT PERFORMANCE LEVELS

- DIN 51502: KP1.5N-20
- ISO 6743: ISO-L-XBDFB 1.5
- NLGI 1.5

## TYPICAL DATA

Colour	Brown
NLGI Grade	1.5
Soap Type	Calcium Complex
Density at 15°C, kg/L	<1.0
Base Oil Viscosity, ISO	460
Operating Temperature Range °C	-20° to +150°
Appearance	Smooth/Tacky
Drop Point, °C	>260
4-ball Weld Load, kg	>6500 N

