INDGREASE LITH EP2

Last updated: 24/02/2025 4:12 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
IGRLITHEP2180	180kg	

PRODUCT BENEFITS

Indgrease Lith EP2 is an NLGI 2, lithium based, industrial mineral lubricating grease. It is made with a combination of antioxidants, corrosion inhibitors and extreme pressure (EP) and anti-wear (AW) additives.

APPLICATION

Indgrease Lith EP2 is high quality multi-purpose grease for use in many types of industrial applications where medium to high loads are encountered.

Indgrease Lith EP2 is suitable for use in general purpose bearing applications such as rolling element bearings and plain bearings, where an NLGI 2 grease is required.

Indgrease Lith EP2 is also formulated with the ability to be pumped more easily than an NLGI 2 grease like Penrite Extreme Pressure Grease, making its use and handling more convenient, especially where pumpability is important.

NOTE For high speed, high temperature applications, including wheel bearings of vehicles fitted with disc brakes, Penrite High Temperature Wheel Bearing Grease should be used.

PRODUCT BENEFITS

- Reduced wear under high to medium loads
- Superior protection against rust and corrosion
- Excellent resistance to water washout
- · Excellent mechanical stability
- · Good pumpability
- · Outstanding storage stability
- · Lead, Chlorine, Nitrite & Extract free

PRODUCT PERFORMANCE LEVELS

DIN 51502: KP2K-20ISO 6743: ISO-L-XBCEB 2

NLGI 2

TYPICAL DATA

4 Ball Weld Scar, mm

Colour Amber **NLGI** Grade 2 Soap Type Lithium Density at 15°C, kg/L 0.9 Base Oil Viscosity, ISO 180 - 210 Operating Temperature Range °C -20° to +130° **Appearance** Smooth/Tacky Drop Point, °C 195

4-ball Weld Load, kg 250
Pumpability, Lincoln Ventmeter @ 0°C, psi

International Ph: +61 3 9801 0877, Fax: +61 (0)3 8710 6601 New Zealand Ph:0800 533 698, Fax: 0508 736 748 Website: www.penriteoil.com.au

Fax: 1800-PENRITE (1800 736 746)

Website: www.perinteoli.com.au

Fax: 1800-PENRITE (1800 736 748)

Email: penrite@penriteoli.com.au

0.45