



**100** Celebrating  
**YEARS**

**AUSTRALIAN OWNED AND TRUSTED SINCE 1926** 

# INDUS COMPRESSOR OIL 2KH ISO 68

Last updated: 30/11/-0001 12:00 am

PRODUCT CODE	PACK SIZE	CARTON QTY
CO2KH68020	20L	

## PRODUCT BENEFITS

**Indus Compressor Oil 2KH (2000 HOURS)** series are a range of mineral based air compressor oils made from pure hydrocracked base oils and an effective ashless additive system. This formulation provides enhanced protection against wear, rust and oxidation.

## APPLICATION

**Indus Compressor Oil 2KH** series are designed for use in rotary screw, reciprocating and rotary vane compressors, providing up to 2000 hour oil drain periods. They meet the requirements of major compressor manufacturers such as Atlas Copco, Champion, Sullair and Ingersoll-Rand.

**Indus Compressor Oil 2KH32** is recommended for oil flooded or oil injected, single or two stage rotary screw compressors, with air discharge temperatures of <100°, where an ISO 32 mineral oil is recommended.

**Indus Compressor Oil 2KH68 and 2KH100** are primarily designed for use in single-stage and multi-stage reciprocating compressors with discharge temperatures of up to 200°. They are also suitable for use in oil flooded rotary screw compressors requiring these viscosities. 2KH100 may also be used in ammonia compressors where an ISO 100 oil is required.

These oils can also be used in turbo blowers and centrifugal pumps, as well as being suitable as R&O (Rust & Oxidation) lubricants in circulating systems. Please Note: These products are not recommended for breathing air unit compressors.

**Please Note:** A 58mm cap with pouring tap is available to fit 20 litre packs. <https://penriteoil.com.au/products/58mm-plastic-tap>

## PRODUCT BENEFITS

- Up to 2000 hour oil drains
- High resistance to oxidation, reducing sludge deposits
- Good water demulsibility
- Excellent protection against wear
- Excellent filterability

## PRODUCT PERFORMANCE LEVELS

- Cincinnati Milacron
- DIN 51506 VDL
- DIN 51524 Part 1
- Hagglunds Denison HF-1

## TYPICAL DATA

Colour	Amber
ISO Grade	68
Density at 15°C, kg/L	0.873
Viscosity, Kinematic, cSt at 40°C	68
Viscosity, Kinematic, cSt at 100°C	9.5
Viscosity Index	118

