

# **INDUS MR 68 HYDRAULIC OIL**

Heavy Duty Hydraulic Oil Issue Date: May 2016

| Product Code | Pack Size  | Carton Qty |
|--------------|------------|------------|
| INDMR68020   | 20 Litre   | 1          |
| INDMR68205   | 205 Litre  | 1          |
| INDMR681000  | 1000 Litre | 1          |



## Description

**Indus MR 68 Hydraulic Oil** is a high quality, zinc free hydraulic oil made from selected base stocks, shear stable viscosity modifier and an anti-wear additive. It is dyed orange for easy identification.

## Application

**Penrite Indus MR 68 Hydraulic Oil** is designed for use in hydraulic systems subjected to wide range of ambient temperatures and service environments such as in marine, mining, construction, agricultural equipment and forestry.

**Penrite Indus MR 68 Hydraulic Oil** is recommended for use in all types of hydraulic systems using vane, piston or gear pumps, airline lubricators, vacuum pumps, lightly loaded gear sets and bearings (such as headstocks, windmill gears) as well as hydraulic hoists and jacks. Marine applications include deck equipment, steering gear and bow thrusters.

For maximum energy savings and protection, Penrite recommends the Indus HV range.

#### **Product Benefits**

- Formulated to combat rust, oxidation, wear and foaming
- Reduces sludge formation.
- Compatible with silver components
- Provides good water separation
- Can be used over a wide range of temperatures

## **Industry Specifications**

| Vickers I-286-S3, M-2952-S | DIN 51524 Part 2         | US Steel 126, 127        |
|----------------------------|--------------------------|--------------------------|
| Hagglunds AC-4.8           | ISO 6743 Part 4, Type HM | AAMA 524 Part 2          |
| Denison HF-2, HF-0         | Bosch Rexroth RE90 220   | German Steel SEB 181 222 |
| Cincinatti Milacron P-69   |                          |                          |

# Typical Data

| Colour                    | Orange |
|---------------------------|--------|
| ISO Grade                 | 68     |
| Viscosity, Kinematic, cSt |        |
| at 40°C                   | 64     |
| at 100°C                  | 9.4    |
| Viscosity Index           | 134    |



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South Victoria AUSTRALIA 3152, ABN 25 005 001 525 Enquiries: Phone 1300-PENRITE (1300 736 748) Fax: 1800-PENRITE (1800 736 748) International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977 New Zealand Ph: 0800 533 698, Fax: 0508 736 748 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234 Website: www.penriteoil.com, Email: penrite@penriteoil.com

PROUDLY AUSTRALIAN FAMILY OWNED SINCE 1926