INDUS PRO HYDRAULIC 10

Last updated: 22/12/2017 8:43 am

PRODUCT CODE	PACK SIZE	CARTON QTY
PROHYD10205	205L	

PRODUCT BENEFITS

Indus Pro Hydraulic 10 is a premium mineral, high quality, ISO 10, <u>zinc free</u>, hydraulic oil made from selected base stocks and advanced AW (anti-wear) additives to satisfy the requirements of stationary, mobile and industrial machines. It provides outstanding protection against wear and corrosion.

It meets ISO 6743 Part 4, Type HM and DIN 51524 Part 2 (HLP Type) specifications.

ADDITIONAL PRODUCT INFORMATION

Click Here to download the Industrial Catalogue

APPLICATION

Indus Pro Hydraulic 10 is recommended for use in all types of hydraulic systems using vane, piston or gear pumps, airline lubricators, vacuum pumps, lightly loaded gear sets and bearings (such as headstocks & windmill gears) as well as hydraulic hoists and jacks.

Indus Pro Hydraulic 10 can be used with silver components and is safe for all hydraulic hoses & seal types.

Please Note: for severe duty and high temperature applications, Penrite recommend Indus HV Fluids

PRODUCT BENEFITS

- Formulated to combat rust, oxidation, wear and foaming.
- · Reduces sludge formation.
- · Compatible with silver components.
- Provides good water separation.

INDUSTRY & MANUFACTURER'S SPECIFICATIONS

- Cincinnati Milacron P-62
- Denison HF-0
- Denison HF-1
- Denison HF-2
- DIN 51524 Part 2 (HLP Type)

- ISO 6743 Part 4, Type HM
- US Steel 126
- US Steel 127
- Vickers I-286-S
- Vickers M-2950-S

TYPICAL DATA

Colour	Amber
ISO Grade	10
Density at 15°C, kg/L	0.854
Viscosity, Kinematic, cSt at 40°C	11.0
Viscosity, Kinematic, cSt at 100°C	2.8
Viscosity Index	116
Zinc, Mass %	NIL