



PENRITE



85% REDUCTION
IN LANDFILL
WASTE

INDUS PRO HYDRAULIC 22

Last updated: 29/08/2024 9:40 am

PRODUCT CODE	PACK SIZE	CARTON QTY
PROHYD22205	205L	

PRODUCT BENEFITS

Indus Pro Hydraulic 22 is a premium mineral, high quality, ISO 22, "Zinc Free", hydraulic oil made from selected base stocks and advanced AW (anti-wear) additives to satisfy the requirements of stationary, mobile and industrial machines. It provides outstanding protection against wear and corrosion.

It meets ISO 6743 Part 4, Type HM and DIN 51524 Part 2 (HLP Type) specifications.

APPLICATION

Indus Pro Hydraulic 22 is recommended for use in all types of hydraulic systems using vane, piston or gear pumps, airline lubricators, vacuum pumps, lightly loaded gear sets and bearings (such as headstocks & windmill gears) as well as hydraulic hoists and jacks.

Indus Pro Hydraulic 22 can be used with silver components due to its zinc free content and is safe for all hydraulic hoses & seal types.

Note: for severe duty and high temperature applications, Penrite recommend Indus HV Fluids

Please Note: A 58mm cap with pouring tap is available to fit 20 litre packs.
<https://penriteoil.com.au/products/58mm-plastic-tap>



PRODUCT BENEFITS

- Formulated to combat rust, oxidation, wear and foaming.
- Reduces sludge formation.
- Compatible with silver components.
- Provides good water separation.

PRODUCT PERFORMANCE LEVELS

- Denison HF-0
- Denison HF-1
- Denison HF-2
- DIN 51524 Part 2 (HLP Type)
- ISO 6743 Part 4 Type HM
- US Steel 126
- US Steel 127
- Vickers I-286-S
- Vickers M-2950-S

TYPICAL DATA

Colour	Amber
ISO Grade	22
Density at 15°C, kg/L	0.834
Viscosity, Kinematic, cSt at 40°C	19.2
Viscosity, Kinematic, cSt at 100°C	4.3
Zinc, Mass %	Nil
Flash Point, °C	>100