## **MARINE INBOARD 25W-40 (Mineral)**

Last updated: 02/05/2019 8:30 am

| PRODUCT CODE | PACK SIZE | CARTON QTY |
|--------------|-----------|------------|
| MAR25W40005  | 5L        | 4          |
| MAR25W40020  | 20L       |            |
| MAR25W40205  | 205L      |            |

# PRODUCT BENEFITS

Marine Inboard Four Stroke 25W-40 is a premium mineral NMMA (National Marine Manufacturers Association) FC-W<sup>®</sup>, fully licensed and registered petrol engine oil. It contains a complate anti-wear additive package combined with specialised rust inhibitors to provide optimum engine protection in marine and salt water environments.

#### **APPROVALS AND LICENSES**

Click Here for NMMA FC-W<sup>®</sup> License Registration Number FB-13827W

#### **APPLICATION**

**Marine Inboard Four Stroke 25W-40** is designed for use in inboard / outboards and stern drive petrol engines. It can be used where SAE 25W-40 and SAE 30 oils are required and where FC-W<sup>®</sup> and FC-W (CAT)<sup>®</sup> products are specified by the manufacturer. It is especially suitable for:

| Mercruiser | Chevrolet   | Chrysler      | Indmar |
|------------|-------------|---------------|--------|
| Mariner    | OMC         | Nissan        | PCM    |
| Tohatsu    | Volvo Penta | and many more |        |

**Marine Inboard Four Stroke 25W-40** may be used in some modern petrol engine cars that require API SL oils. Diesel fuelled engines should use the appropriate Penrite diesel oil.

#### **PRODUCT BENEFITS**

- · Specially formulated for protection for marine salt water environments
- Registered NMMA FC-W® approved engine oil
- Complete Anti-wear additive package for maximum wear protection

### **MANUFACTURER'S (OEM) APPROVALS & INDUSTRY LICENSES**

NMMA FC-W® Registration Number FC-13827W

## **INDUSTRY & MANUFACTURER'S SPECIFICATIONS**

API SL

China National GB 11121-2006

NMMA FC-W®

#### **TYPICAL DATA**

| Colour                               | Amber |
|--------------------------------------|-------|
| Density at 15°C, kg/L                | 0.889 |
| Viscosity, Kinematic, cSt at 40°C    | 138   |
| Viscosity, Kinematic, cSt at 100°C   | 14.9  |
| Viscosity Index                      | 109   |
| Cold Cranking Viscosity, cP at -10°C | 5722  |
| Zinc, Mass %                         | 0.085 |
| Phosphorus, Mass %                   | 0.077 |
| Sulphated Ash, Mass %                | 0.77  |
| Total Base Number (TBN)              | 7.4   |

PENRITE OIL COMPANY PTY LTD ABN 25 005 001 525

110 Greens Rd, Dandenong South, Victoria 3175 Australia

Phone: 1300-PENRITE (1300 736 748) Fax: 1800-PENRITE (1800 736 748)