



PENRITE

MARINE DIESEL 15W-40

Semi Synthetic Marine Oil

Issue: March 2015



Product Code:	Pack Size:	Carton Qty:
MARD15W40005	5 Litre	4
MARD15W40020	20 Litre	1
MARD15W40205	205 Litre	1
MARD15W401000 LTR	1000 Litre	1

Description

Marine Diesel 15W-40 is a SAE 15W-40, semi-synthetic, mid ash marine diesel engine oil formulated with a carefully selected blend of high performance additives and a mix of mineral and synthetic base oils to provide complete protection for marine diesel engines. It exceeds the requirements of API CI-4 and ACEA E4/E7 industry standards and also meets many marine engine manufacturers' performance specifications, including long oil drain requirements.

Application

Marine Diesel 15W-40 is designed for use in moderate to severe service, high speed and some medium speed four stroke European, U.S. and Japanese marine diesel engines, where a 15W-40 engine oil is required. It can be used in both turbocharged and naturally aspirated engines running either low or high sulphur diesel fuel. It is especially suited to coastal and fishing fleets but can also be used in recreational craft.

Marine Diesel 15W-40 can be used in marine engines manufactured by Caterpillar (except for 3600 series), Cummins, Iveco (except C13 ENT M77), MAN, Mercedes Benz, MTU, Perkins, Scania, Volvo and many others.

Marine Diesel 15W-40 is formulated with additive technology that is highlighted by the inclusion of special corrosion inhibitors as well as a high TBN (Total Base Number) content, allowing it to be able to achieve long oil drain requirements while providing outstanding engine protection for the life of the oil drain. It will provide excellent start-up wear protection and resistance to oil thickening due to soot build up.

Marine Diesel 15W-40 is also suitable for use in on- and off-highway equipment such as in agricultural, earthmoving and road transport, where the specifications meet those required by manufacturers.

Marine Diesel 15W-40 is **NOT SUITABLE** for use in **PETROL** powered engines

Product Benefits

- Meets long drain requirements for European, U.S., and Japanese engines
- Excellent anti-corrosion protection of engine parts
- High TBN to protect against and neutralise acid build up
- Semi-synthetic formulation
- Resists oil thickening
- Shear stable viscosity modifier maintains oil viscosity in service
- Mid ash formulation controls combustion chamber deposits especially around piston area
- Start-up viscosity protection



Industry Specifications

API CI-4
Cummins CES 20078
MAN M3277
Volvo VDS-3

ACEA E4/E7
Detroit DDC
Mercedes Benz 228.5 (level)
China National GB 11122-2006

Allison C4
JASO DH-1
MTU Type 3

Caterpillar ECF-1-a
Mack EO-M Plus
Renault RXD/RLD-2

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 52
Enquiries: Phone 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)
International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**



United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com



Typical Data

Density at 15°C, kg/L	0.873
Viscosity, Kinematic, cSt	
at 40°C	112
at 100°C	15.1
Viscosity Index	141
Viscosity, Cold Cranking, cP @ -20 °C	5,372
Phosphorus, mass %	0.101
Zinc, mass %	0.112
Calcium, mass %	0.377
Sulphated Ash, Mass %	1.35
Base Number, mg KOH/g	12.6

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

PENRITE



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 52
Enquiries: Phone 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)
International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**



United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com