



PENRITE



85% REDUCTION
IN LANDFILL
WASTE

MB15 SUSPENSION FLUID (MINERAL)

Last updated: 12/07/2022 11:39 am

PRODUCT CODE	PACK SIZE	CARTON QTY
MB15001	1L	6

PRODUCT BENEFITS

MB 15 Suspension Fluid is a light, high viscosity index, zinc free Premium Mineral oil designed for suspension components & hydraulic self-levelling suspension units that specify MB 343.0. Colour of product is Amber.

APPLICATION

MB 15 Suspension Fluid is designed for use in Mercedes-Benz self-levelling suspension units that specify this type of oil.

MB 15 Suspension Fluid has also suitable for servicing racing shock absorbers (such as Ohlins) where this type of fluid is specified. It is also ideal for use as a motorcycle fork oil where "5W" Fork oils are specified.

MB 15 Suspension Fluid may also be used as a light industrial hydraulic oil in air-line lubricators and other applications that require very light oils. It may also be used as a light hydraulic oil in air tools and other applications requiring a light oil grade.

PRODUCT BENEFITS

- Provides excellent wear and anti-corrosion protection
- Good low temperature flow properties
- Compatible with OEM fluids

PRODUCT PERFORMANCE LEVELS

- ISO 15
- MB 343.0.

TYPICAL DATA

Colour	Amber
Density at 15°C, kg/L	0.835
Viscosity, Kinematic, cSt at 40°C	15.3
Viscosity, Kinematic, cSt at 100°C	4.0
Viscosity Index	151
Flash Point, °C	200

