

MC FORK OIL 5, 10 & 15

Suspension Fork Oils

Issue: August 2016

| _ | | | |
|--------------|-----------|------------|--|
| Product Code | Pack Size | Carton Qty | |
| MCFO05001 | 1 Litre | 6 | |
| MCFO05020 | 20 Litre | 1 | |
| MCFO10001 | 1 Litre | 6 | |
| MCFO10020 | 20 Litre | 1 | |
| MCFO15001 | 1 Litre | 6 | |



MC Fork Oils 5, 10 & 15 are fully synthetic, very high viscosity index fluids made from a special combination of synthetic base oils, viscosity modifiers and anti-wear and EP additives.

Application

Motorcycle Fork Oils 5, 10 and 15 are recommended for use in motorcycle forks and other suspension systems.

MC Fork 5 may be used in motorcycle forks that require SAE 5W and 7.5W grades. These include:

- Ducati
- **BMW**
- Husqvarna

IIGH PERFORMANCE

IGH PERFORMANCE

- KTM
- Kawasaki
- Triumph

MC Fork 10 may be used in motorcycle forks that require SAE 10W grade. These include:

- Honda
- Kawasaki
- Suzuki

- Moto Guzzi
- Ducati
- Yamaha

BMW

MC Fork 15 may be used in motorcycle forks that require SAE15W grade. These include:

- Aprilia
- Kawasaki
- Honda

- Moto Guzzi
- Suzuki
- Triumph

- VMoto
- Yamaha

Product Benefits

- Stable viscosity over temperature variations
- Protects system from wear
- Compatible with brass and copper alloys
- Compatible with seal materials
- Excellent low temperature properties



Typical Data

| Product | FORK 5 | FORK 10 | FORK 15 |
|---------------------------|--------|---------|---------|
| Density at 15°C, kg/L | 0.847 | 0.856 | 0.871 |
| Viscosity, Kinematic, cSt | | | |
| at 40°C | 20 | 37 | 47 |
| at 100°C | 5.0 | 7.5 | 8.9 |
| Viscosity Index | 193 | 174 | 173 |
| Zinc. mass % | 0.139 | 0.13 | 0.13 |

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.





