



# PENRITE



85% REDUCTION  
IN LANDFILL  
WASTE

## MC GEAR OIL (MINERAL)

Last updated: 16/03/2020 9:49 am

PRODUCT CODE	PACK SIZE	CARTON QTY
MCGO80001	1L	6

### PRODUCT BENEFITS

**MC Gear Oil** is a premium mineral high performance, SAE 10W-40 API GL-4 gear oil, specially formulated for separate gearboxes used in two stroke and four stroke motorcycles including ATV's.

### CAN BE USED WHERE THE FOLLOWING SAE VISCOSITIES ARE RECOMMENDED:

- SAE 10W-30
- SAE 10W-40
- SAE 15W-40
- SAE 80
- 80W-85

### APPLICATION

**MC Gear Oil** is a premium mineral high performance, SAE 10W-40 API GL-4 gear oil, specially formulated for separate gearboxes used in two stroke and four stroke motorcycles including ATV's.

**MC Gear Oil** is recommended for use in motorcycle gearboxes that require SAE 10W-30, 10W-40 or 15W-40 engine oils. It is also suitable for use where an API GL-4, SAE 80W or 80W-85 gear oil is required. It is especially suitable in gearboxes that have oil immersed clutches. Motorcycle Gear Oil is also suitable for use in passenger cars, 4WDs, light & heavy commercial vehicle gearboxes and transfer cases where a SAE 80W or 80W-85, API GL-4 gear oil is recommended.

### PRODUCT BENEFITS

- **SMOOTH** & precise gear shifts
- **COMPETITION PROVEN** and trusted for performance machines
- **OPTIMUM** clutch slip prevention in 4 stroke motorcycles with wet clutches
- Purpose designed additives improve the shift feel for the life of the drain
- Highly shear stable formulation, providing ultimate performance
- Enhanced oxidation stability, reducing harmful deposits
- Excellent wear protection
- Formulated to meet manufacturers requirements for transmission oils

### PRODUCT PERFORMANCE LEVELS

- API GL-4

### TYPICAL DATA

Density at 15°C, kg/L	0.873
Viscosity, Kinematic, cSt at 40°C	78
Viscosity, Kinematic, cSt at 100°C	14.1
Viscosity Index	188
Cold Cranking Viscosity, cP at -25°C	6167
Ca content, Mass %	0.313
Zinc, Mass %	0.123
Sulphated Ash, Mass %	1.22
Total Base Number (TBN)	9.4

