



MC FORK OIL 5, 10 & 15

Suspension Fork Oils

Issue: July 2017

PRODUCT CODE	PACK SIZE	CTN QTY
MCFO05001	1 Litre	6
MCFO10001	1 Litre	6
MCFO15001	1 Litre	6



Description

MC Fork Oils 5, 10 & 15 are fully synthetic, very high viscosity index fluids made from a special combination of synthetic base oils, viscosity modifiers and anti-wear and EP additives.

Application

Motorcycle Fork Oils 5, 10 and 15 are recommended for use in motorcycle forks and other suspension systems.

MC Fork 5 may be used in motorcycle forks that require SAE 5W and 7.5W grades. These include:

- Ducati
- BMW
- Husqvarna
- KTM
- Kawasaki
- Triumph

MC Fork 10 may be used in motorcycle forks that require SAE 10W grade. These include:

- Honda
- Kawasaki
- Suzuki
- Moto Guzzi
- Ducati
- Yamaha
- BMW

MC Fork 15 may be used in motorcycle forks that require SAE15W grade. These include:

- Aprilia
- Kawasaki
- Honda
- Moto Guzzi
- Suzuki
- Triumph
- VMoto
- Yamaha

Product Benefits

- Stable viscosity over temperature variations
- Protects system from wear
- Compatible with brass and copper alloys
- Compatible with seal materials
- Excellent low temperature properties

Typical Data

Product	FORK 5	FORK 10	FORK 15
Density at 15°C, kg/L	0.847	0.856	0.871
Viscosity, Kinematic, cSt			
at 40°C	20	37	47
at 100°C	5.0	7.5	8.9
Viscosity Index	193	174	173
Zinc, mass %	0.139	0.13	0.13

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 7483)
 Fax: 1800-PENRITE (1800 736 7483)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**

