



MC-4 FULL SYNTHETIC 10W-40

Full Synthetic Motorcycle Engine Oil

Issue: March 2017



Product Code	Pack Size	Carton Qty
MC4FULL10004	4 Litre	4
MC4FULL10020	20 Litre	-
MC4FULL10205	205 Litre	-

Product Description

MC-4 FULL SYNTHETIC 10W-40 is a premium full synthetic, SAE 10W-40, non friction modified, modern 4 stroke engine oil. It contains a superior anti wear package of **FULL ZINC** (exceeding 1200+ ppm) for ultimate engine, gearbox & clutch protection combined with the latest engine oil technology that provides protection against wear, corrosion, oil oxidation, piston deposits and sludge under all conditions.

MC-4 FULL SYNTHETIC 10W-40 meets the requirements of API SN/CF and JASO MA2.

Application

MC-4 FULL SYNTHETIC 10W-40 is designed for use in all four stroke road & sports bikes, dirt & enduro bikes, ATV's/Quad bikes and scooters that require a full synthetic engine oil. It is also equally suitable for use in transmissions with wet clutch systems where engine & gearbox oils are combined. It has optimum clutch slip prevention in these systems and is suitable for use where JASO MA1 and JASO MA2 is specified.

MC-4 FULL SYNTHETIC 10W-40 can be used where semi synthetic or other types of oils are specified by the manufacturer including where SAE 10W-30 & SAE 10W-40 grade oils are recommended such as in Aprilia, BMW, Cagiva, Can-Am, Ducati, Hyosung, Kawasaki, Suzuki, Triumph, Yamaha & more.

MC-4 FULL SYNTHETIC 10W-40 is a full synthetic base engine oil providing superior oil film strength, heat resistance and oil shear protection. It provides an un-paralleled layer of protection for engine compression & oil sealing rings, cylinder sleeve lubrication, bearing and valve train.

MC-4 FULL SYNTHETIC 10W-40 is also suitable for use in other four stroke engines such as stationary engines & generators or other vehicles that require this grade and specification of engine oil and can be used with petrol, racing & other conventional fuels.

Product Benefits

- **FULL SYNTHETIC** base oils for maximum heat resistance and high performance
- **FULL ZINC** anti-wear additive package for ultimate engine wear protection.
- **LATEST** oil technology for maximum wear protection, minimum sludge formation & reduced piston deposits
- **SHEAR STABLE** formulation protects against viscosity loss
- **FACTORY PROVEN** by competition race teams and trusted protection for performance engines
- **MAXIMUM** power & acceleration
- Suitable for use with wet clutch systems (JASO MA, JASO MA 1 & JASO MA 2)
- Extends engine life by reducing formation of high temperature engine deposits

Industry Specifications

API SN/CF JASO MA2

(Backward compatible and suitable for use where SM, SL, SJ, SH & SG oils are recommended by the manufacturer)

Typical Data

Density at 15°C, kg/L	0.865
Viscosity, Kinematic, cSt	
at 40°C	97
at 100°C	15.1
Viscosity Index	165
Viscosity, Cold Cranking @ -25 °C	5,049
Zinc, mass %	0.124
Sulphated Ash, mass %	1.17
Base Number	9.0

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request. Penrite recommend the right product for the right application. Please consult the Penrite lube guide for the correct oil recommendation.



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)
International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**

