



MC-4 SEMI SYNTHETIC 10W-30

Semi Synthetic 4 Stroke Engine Oil

Issue March 2017

Product Code	Pack Size	Carton Qty
MC4SEMI10W30001	1 Litre	6
MC4SEMI10W30025	2.5 Litre	4
MC4SEMI10W30004	4 Litre	4

Description

MC4 SEMI 10W-30 is a premium semi synthetic, SAE 10W-30, non-friction modified, modern, 4 stroke engine oil. It contains a superior anti wear package of **FULL ZINC** for ultimate engine, gearbox & clutch protection and semi synthetic base oils for outstanding high temperature protection and maximum performance.

MC4 SEMI 10W-30 meets the requirements of API SL/CF and JASO MA

Application

MC4 SEMI 10W-30 is designed for use in four stroke road & sports bikes, dirt & enduro bikes, ATV's/Quad bikes and scooters. It is also equally suitable for use in transmissions with wet clutch systems where engine & gearbox oils are combined. It has optimum clutch slip prevention in these systems being compliant with JASO MA as is suitable for use where JASO MA1 and JASO MA2 is specified.

MC4 SEMI 10W-30 can also be used in motor cycles with a separate gear box and clutch assembly as a gear oil where the manufacturer recommends a 10W-30 engine oil for this application.

MC4 SEMI 10W-30 is an excellent choice for Golf Carts, that stop / start constantly and can also be used in lawnmowers, generator sets and pumps, four stroke outboards / inboards, four stroke brushcutters and in other gardening equipment that specify this viscosity grade.

Motor Cycles

Honda
Suzuki

Hyosung
Yamaha

Kawasaki
and more

Product Benefits

- **PREMIUM** quality blended base stock
- **OUTSTANDING** engine and gearbox protection
- **TRUSTED & PROVEN** protection for engines
- **WET CLUTCH** compatible (JASO MA, JASO MA1 and JASO MA2)
- Suitable for use in gear boxes where SAE10W-30 is specified.
- Suitable for many other 4 Stroke engines

Industry Specifications

API SL/CF

JASO MA

CHINA NATIONAL GB 11121-2006

Typical Data

Colour	Straw
Density at 15°C, kg/L	0.867
Viscosity, Kinematic, cSt	
at 40°C	74
at 100°C	11.5
Viscosity Index	149
Viscosity, Cold Cranking @ -25 °C	4651
Sulphated Ash, mass %	0.83
Phosphorus, mass %	0.098
Zinc, mass%	0.108
Base Number	7.6

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



PENRITE



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)
International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748
United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**

