



**100** Celebrating  
**YEARS**

**AUSTRALIAN OWNED AND TRUSTED SINCE 1926** 

## MC4 ST 15W-40

Last updated: 30/11/-0001 12:00 am

PRODUCT CODE	PACK SIZE	CARTON QTY
XMC4MIN15W400008	800mL	6
XMC4MIN15W40001	1L	6

### PRODUCT BENEFITS

**MC4 ST Mineral 15W-40** is a premium mineral synthetic, SAE 15W-40, non-friction modified, modern, 4 stroke engine oil. It contains a superior anti wear package of **FULL ZINC** for ultimate engine, gearbox & clutch protection

**MC4 ST Mineral 15W-40** exceeds the requirements of API SL and JASO MA

### APPLICATION

**MC4 ST MINERAL 15W-40** is designed for use where either SAE 15W-30 or 15W-40 oils are required.

**MC4 ST MINERAL 15W-40** can be used in four stroke road and sports bikes, utility tricycle (Xe Loi) in good condition, scooters, dirt bikes and agricultural ATV's/Quad bikes. This includes for use in where the engine and gearbox oils are combined as well as where the compartments are separate.

**MC4 ST MINERAL 15W-40** can also be used in lawnmowers, generator sets and pumps, four stroke outboards/inboards, four stroke brushcutters and in other gardening equipment that specify this viscosity grade. May also be used in car engines that require API SL oils.



### PRODUCT BENEFITS

- Maintains oil pressure
- Shear stable formulation for long drain protection
- Compatible with wet clutch systems (JASO MA)
- outstanding engine and gearbox protection in hot climates

### PRODUCT PERFORMANCE LEVELS

- API SL
- China National GB 11121-2006
- JASO MA

### TYPICAL DATA

Colour	Straw
Density at 15°C, kg/L	0.871
Viscosity, Kinematic, cSt at 40°C	100
Viscosity, Kinematic, cSt at 100°C	14.4
Viscosity Index	148
Cold Cranking Viscosity, cP at -20°C	6594
Zinc, Mass %	0.108
Phosphorus, Mass %	0.098
Sulphated Ash, Mass %	0.83
Total Base Number (TBN)	7.6