



100 Celebrating
YEARS

AUSTRALIAN OWNED AND TRUSTED SINCE 1926 

MC4 ST 25W-50

Last updated: 30/11/-0001 12:00 am

| PRODUCT CODE | PACK SIZE | CARTON QTY |
|-----------------|-----------|------------|
| XMC4MIN25W50001 | 1L | 6 |

PRODUCT BENEFITS

MC4 ST MINERAL 25W-50 is a premium mineral synthetic, SAE 25W-50, non-friction modified, modern, 4 stroke engine oil. It contains a superior anti wear package of **FULL ZINC** for ultimate engine, gearbox & clutch protection

MC4 ST MINERAL 25W-50 exceeds the requirements of API SL and JASO MA

APPLICATION

MC4 ST MINERAL 25W-50 is designed for use where either SAE 20W-40, 20W-50 or 25W-50 oils are required. It is highly recommended in older bikes where low pressure or high oil consumption is a problem.

MC4 ST MINERAL 25W-50 can be used in four stroke road and sports bikes, utility tricycle (Xe Loi), scooters, dirt bikes and agricultural ATV's/Quad bikes. This includes for use in where the engine and gearbox oils are combined as well as where the compartments are separate.

MC4 ST MINERAL 25W-50 can also be used in older four stroke lawnmowers, generator sets and pumps. May also be used in older car engines and outboards that require API SL oils.



PRODUCT BENEFITS

- Maintains oil pressure
- Shear stable formulation for long drain protection
- Compatible with wet clutch systems (JASO MA)
- Outstanding engine and gearbox protection in hot climates
- Reduces oil consumption in older engines.

PRODUCT PERFORMANCE LEVELS

- API SL
- JASO MA

TYPICAL DATA

| | |
|--------------------------------------|-------|
| Colour | Straw |
| Density at 15°C, kg/L | 0.889 |
| Viscosity, Kinematic, cSt at 40°C | 179 |
| Viscosity, Kinematic, cSt at 100°C | 18.5 |
| Viscosity Index | 115 |
| Cold Cranking Viscosity, cP at -10°C | 4352 |
| Zinc, Mass % | 0.108 |
| Phosphorus, Mass % | 0.098 |
| Sulphated Ash, Mass % | 0.83 |
| Total Base Number (TBN) | 7.6 |