

MC4-ST 10W-60

100% PAO & Ester Full Synthetic Engine Oil

Issue: March 2017

PRODUCT CODE	PACK SIZE	CTN / QTY
MC410W60001	1 Litre	6
MC410W60004	4 Litre	4
MC410W60020	20 Litre	1

Product Description

MC-4 10W-60 is a premium 100% PAO & Ester, full synthetic, SAE 10W-60, non-friction modified, 4-stroke engine oil. It contains a superior anti wear package of *FULL ZINC + (exceeding 1800+ ppm levels) for maximum engine, gearbox & clutch protection against wear, corrosion, oil oxidation, piston deposits and sludge under all conditions

MC-4 10W-60 exceeds the requirements of API SN/CF and JASO MA.

Application

MC-4 10W-60 is designed for use in modern four stroke road & sports bikes, dirt & enduro bikes, ATV's/Quad bikes and 4 stroke scooters that require a full synthetic engine oil. It is also equally suitable for use in transmissions with wet clutch systems where engine & gearbox oils are combined. It has optimum clutch slip prevention in these systems being compliant with JASO MA as is suitable for use where JASO MA1 and JASO

MC-4 10W-60 features an extra high operating temperature viscosity for increased protection under load and high temperature operating conditions. It can be used where semi synthetic or other types of oils are specified by the manufacturer including where SAE 10W-50 grade oils are recommended such as in Aprilia, Benelli, Cagiva, Husqvarna, KTM, Moto Guzzi, MV Agusta & more.

MC-4 10W-60 is a 100% PAO and Ester base engine oil providing superior oil film strength, heat resistance and oil shear protection. It provides an un-paralleled layer of protection for engine compression & oil sealing rings, cylinder sleeve lubrication, bearing and valve train.

MC-4 10W-60 is also suitable for use in other four stroke engines such as stationary engines & generators or other vehicles that require this grade and specification of engine oil. It is suitable for use with most petrol, racing and other conventional fuels.

Product Benefits

- Blended using 100% PAO (Poly Alpha Olefin Group IV) and ESTER (Group V) base oils for maximum heat resistance and high performance
- *FULL ZINC + anti-wear additive package for ultimate engine wear protection
- LATEST oil specification technology exceeding petrol API SN for maximum wear protection, minimum sludge formation & reduced piston deposits
- **MAXIMUM** power and acceleration
- FACTORY PROVEN by competition race teams and trusted protection for performance engines
- Suitable for wet clutch systems (JASO MA, JASO MA1 and JASO MA2)
- Extends engine life by reducing formation of high temperature engine deposits.

Industry Specifications

API SN/CF JASO MA

Typical Data

Viscosity, Kinematic, cSt



*Full Zinc + = Zinc level + Boron level combined as a total anti-wear package

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.





PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South Victoria AUSTRALIA 3152, ABN 25 005 001 525 Enquiries: Phone 1300-PENRITE (1300 736 748) Fax: 1800-PENRITE (1800 736 748) ternational: Phone: 61 3 9801 0877,Fax: 61 3 9801 0977 New Zealand Ph: 0800 533 698, Fax: 0508 736 748 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234

Website: www.penriteoil.com, Email: penrite@penriteoil.com

PROUDLY AUSTRALIAN **FAMILY OWNED SINCE 1926**

