



MONO TRUCK 30

Premium Mineral Oil

Issue: May 2016

Product Code	Pack Size	CTN QTY
MONO30020	20 Litre	1
MONO30205	205 Litre	1



PENRITE

Description

Mono Truck 30 is a monograde **SAE 30** engine oil for older & classic engines formulated with premium mineral base oil and modern additives to provide outstanding protection in diesel and petrol engines against wear, corrosion, oil oxidation and sludge.

Mono Truck 30 meets the requirements of API CF/CF-2/SG and ACEA E1 as well as many other specifications.

Application

Mono Truck 30 is designed for use in a wide range of engines where the manufacturer specifies a SAE 30 monograde engine oil. It can also be used in transmissions and hydraulic applications where this type of oil is specified by the manufacturer.

Mono Truck 30 is specifically designed for use in naturally aspirated & turbo-charged diesel engines operating under severe on and off highway conditions. It is particularly suitable for pre-1983 Japanese engines, marine applications, stationary engines (including gardening equipment and generators) as well as 4 stroke petrol engines where this grade of oil is required. It can also be used in Komatsu powershift transmissions and Allison transmissions requiring C3 oils.

Mono Truck 30 are suitable for many older design small diesel engines used in fishing boats and trawlers, and in stationary engines. It may be used in the following engines:

Gardner-Denver	Daihatsu	Delta	Belarus	Allis Chalmers
Yanmar	Detroit Diesel	Dorman	Fiat	Ford
Hino	Iseki	Honda	International	Isuzu
John Deere	Kawasaki	Shibaura	Kohler	Kubota
Leyland	Lister Petter	Lombardini	Komatsu	Nissan
Onan	Perkins	Ruston	Waukesha	

Product Benefits

- Balanced base oil & additives pack provides ultimate engine protection
- Low ash formulation minimises engine and combustion chamber deposits.
- Multi-use product minimising inventory costs
- Keeps engine clean & prolongs engine life.

Industry Specifications

API CF-2/CF/SG	ACEA E1	MIL-L-2104F
Allison C3	Mercedes Benz 227.0	Mercedes Benz 228.0
Mack EO-K/2	Detroit 7SE-270	Caterpillar TO-2

Typical Data

SAE Grade	30
Density at 15°C, kg/L	0.880
Viscosity, Kinematic, cSt	
at 40°C	84
at 100°C	10.8
Viscosity Index	114
Zinc, mass %	0.122
Sulphated Ash, mass %	1.22
Base Number	9.4

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. A MSDS is available on request.



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 748)
 Fax: 1800-PENRITE (1800 736 748)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**



United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com