# P26 MULTI PURPOSE MoS2 LUBRICANT

Last updated: 21/07/2014 12:31 pm

| PRODUCT CODE | PACK SIZE | CARTON QTY |
|--------------|-----------|------------|
| P26MPL0004   | 400mL     | 6          |

#### **PRODUCT BENEFITS**

**P26 Multi-Purpose MoS<sub>2</sub> Lubricant** is an advanced formula, professional and universal automotive maintenance oil, containing molybdenum disulphide, that infiltrates, penetrates, dispels water, lubricates moving parts, acts as a contact agent (electrical), cures squeaks and creaks and protects metal against corrosion. It contains a solvent carrier that evaporates from the treated components whilst leaving a thin film of corrosion protecting oil.

#### **APPLICATION**

**P26 Multi-Purpose MoS<sub>2</sub> Lubricant** is suitable for use in all automotive, marine, industrial and domestic applications. These include drying wet automotive ignition and electrical systems and is useful in many other automotive and domestic applications such as hinges, locks, catches and other squeaking or seized moving parts. It can also

be used as a corrosion protector for metal. It can be used wherever a normal penetrant or light lubrication is necessary to assist in free movement of parts. It is excellent as a penetrant pre-spray for rusted on nuts and bolts prior to disassembling corroded parts.

**P26 Multi-Purpose MoS<sub>2</sub> Lubricant** can help eliminate problems by protecting exposed parts from corrosive effects of climatic conditions especially in high humidity and areas close to coastal sea and salt. It acts as a water dispelling or displacement fluid so is excellent for contact points.

**P26 Multi-Purpose MoS<sub>2</sub> Lubricant** is flammable and should be kept away from flames and ignition sources. It has a non-toxic formulation and does not stain metal surfaces.

## **INSTRUCTIONS FOR USE**

- 1. Use directly from the aerosol spray can
- 2. Spray on to problem area
- 3. Leave product for a few minutes to penetrate

# **PRODUCT BENEFITS**

- Protects against corrosion, rust and oxidation
- Acts as a water displacement fluid
- Stops squeaks & creaks
- · Many & varied product uses
- · New design spray nozzle with built in tube

### PRODUCT PERFORMANCE LEVELS

# **TYPICAL DATA**

Colour Brown-Grey liquid

Density at 15°C, kg/L 0.83

 PENRITE OIL COMPANY PTY LTD ABN 25 005 001 525
 International Ph: +61 3 9801 0877, Fax: +61 (0)3 8710 6601

 110 Greens Rd, Dandenong South, Victoria 3175 Australia
 New Zealand Ph:0800 533 698, Fax: 0508 736 748

 Phone: 1300-PENRITE (1300 736 748)
 Website: www.penriteoil.com.au

Fax: 1800-PENRITE (1800 736 748)

Website: www.perinteoli.com.au

Fax: 1800-PENRITE (1800 736 748)

Email: penrite@penriteoli.com.au

