# PAS FLUID - (Power Assisted Steering Fluid)

PRODUCT CODE	PACK SIZE	CARTON QTY
PAS001	1L	6

## PRODUCT BENEFITS

**PAS Fluid** is a premium, semi synthetic oil specially designed for use in Australian, European, US & Korean power steering and suspension systems. It contains a special Anti-Shudder (noise & chatter) additive.

**PAS Fluid** fully meets the requirements of Land Rover PAS 14315 (Power Assisted Steering).

## **APPLICATION**

**PAS Fluid** is recommended for use in the power steering and active cornering enhancement system (ACE) of Land Rover vehicles such as the Discovery and Defender.

PAS Fluid also meets or exceeds the requirements for power steering units used by

Chrysler and General Motors North America and for ZF power steering units. It may be used in power steering units where automatic transmission fluids are specified and use of a semi-synthetic fluid is desired.

**PAS Fluid** can be used where products such as Pentosin CHF 7.1 or 4548 are recommended and where Dexron VI is recommended in Holden Commodore / Calais / Caprice & HSV VE series vehicles.

**PAS Fluid** can also be used where 7.5W motorcycle fork oil is required.

Other applications include the power steering and suspension systems of -

Aston Martin	BMW	Dodge	Ferrari	Ford
Holden/HSV	Hyundai	Infinity	Jaguar	Jeep
Kia	Mazda	Mercedes	Nissan	SAAB
Subaru	Volvo	and many others		

Penrite also market special power steering and suspension fluids -

- Power Steering Fluid
- HPSO Fluid
- LHM Plus
- MB 15
- LDAS

Please check your handbook or call Penrite to clarify any applications for these products.

#### **PRODUCT BENEFITS**

- · Semi synthetic performance
- Minimises shudder & noise
- Extends seal and hose life
- · Good low temperature fluidity
- Protects against rust and corrosion



Last updated: 29/01/2025 12:33 pm

Gelebrating AUSTRALIAN OWNED AND TRUSTED SINCE 1926





## PRODUCT PERFORMANCE LEVELS

- AMC 4124
- Chrysler MS-5931
- Chrysler MS-9462
- Esso EZL 998 (Jaguar S)
- Ford M2C128-C
- Ford M2C128-D
- Ford M2C195-A (Power steering only)
- GM 9985819
- GM 9985835
- Hyundai PSF-3
- Kia PSF-3

### **TYPICAL DATA**

Colour	Green
Density at 15°C, kg/L	0.860
Viscosity, Kinematic, cSt at 40°C	25.6
Viscosity, Kinematic, cSt at 100°C	6.4
Viscosity Index	196
Viscosity, Brookfield, cSt @ -40°	4,500
Phosphorus, Mass %	0.021

- Land Rover STC 50717 (ACE)
- MB 236.3.
- MB 341.0.
- Opel 90 513486
- PAS 14315
- Pentosin CHF 4548
- Pentosin CHF 7.1
- VW TL VW-570-26
- ZF TE ML 09
- ZF TE ML 09B