



POWER SPORTS GREASE

Lithium Complex Grease

Issue: February 2016

Product Code:	Pack Size:	Carton Qty:
PSGR0001	100gm	6

Description

Power Sports Grease is a water resistant, high temperature, multi-purpose, Lithium Complex grease that contains a special anti-rust additive for enhanced protection against oxidation and corrosion. It also contains a tacking agent to provide increased protection during severe performance conditions allowing for exceptional water wash out resistance and spray off resilience.

Application

Power Sports Grease has been formulated to provide outstanding lubrication and protection in all outdoor activities such as Motorcycling, Marine, Automotive and other outdoor activities where a water-resistant, high shock load type grease is required. It has excellent resistance to water, snow, ice & mud and provides outstanding film strength and washout protection.

Power Sports Grease can be used on wheel bearings including those fitted with disc brakes, cables, throttle lines, linkages, winch gears and most other greasing points where protection is needed against the elements.

Power Sports Grease is excellent for motor cycles and bicycles for bearings and water-proofing areas that are exposed and prone to retaining water and dirt that could potentially rust. It can be used on motorcycles, quad bikes, snow mobiles and ATV's on the front and rear wheel axles as well as the front fork steering bearing, shock absorber linkages and swing arm / suspension pivots. In marine applications it can be used on boats and jet skis for dog seals, deck equipment, trailer rollers, prop shaft splines, steering mounts and general greasing points.

Power Sports Grease is packed in a convenient 100g tube for easy dispensing and so can be carried as part of a small tool kit for on the spot protection. Its translucent green colour makes it easy to see and it won't harm paint or plastics.

Product Benefits

- Race Proven by Factory Race Teams including Team Honda MX Australia
- High water resistance and low water wash out
- Excellent rust & corrosion protection
- Multi-purpose product suitable for many greasing applications
- High shock loading protection.
- Tacking agent improves product adhesion
- Long service life.
- Lead and chlorine free.

Industry Specifications

NLGI 2, DIN 51502: KP2N-30, ISO 6743: ISO-L-XCDIB2

Typical Data

Soap Type	Lithium Complex
Colour	Green
NLGI Grade	2
Drop Point, °C	275
Base Oil Viscosity, ISO	220
Timken OK Load, kg	23
4-ball Weld Load, kg	315
Continuous Operating Temperature, °C	-15 to +170
Maximum Temperature, Intermittent use, °C	180
EMCOR Corrosion Test, synthetic sea water	0/0

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



PENRITE



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 7483)
 Fax: 1800-PENRITE (1800 736 7483)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**

