



100 Celebrating
YEARS

**AUSTRALIAN OWNED AND
TRUSTED SINCE 1926** 

POWER STEERING STOP LEAK

Last updated: 22/09/2027 3:57 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
ADPSL375	375mL	6

PRODUCT BENEFITS

Power Steering Stop Leak has been specifically formulated to control leaks in the power steering system due to deteriorated or worn seals and gaskets.

APPLICATION

Power Steering Stop Leak has been designed for use in power steering systems that utilise Automatic Transmission Fluids (ATF's) as the power steering fluid. It is suitable for passenger cars, 4WD's, and light commercial vehicles.

Power Steering Stop Leak is suitable for use with vehicles that use the following Penrite power steering and automatic transmission fluids as well as most systems that use GM Dexron® type fluids that are utilised in power steering systems -

- [Penrite Power Steering Fluid](#)"
- [Penrite Multi-Vehicle DX-III](#)
- [Penrite Multi-Vehicle LV](#)
- [Penrite Multi-Vehicle MHP](#)
- [Penrite ATF BMV](#)
- [Penrite Multi-Vehicle FS](#)
- [Penrite ATF 33 Type F](#)

Power Steering Stop Leak will not affect the performance of the Power Steering System

FOR BEST RESULTS:

- 1) Ensure the reservoir has 375ml capacity prior to filling.
- 2) Add one bottle (375ml) for up to 1 litre of power steering fluid.

NOTE: If leaks are still evident after use, replacement or repair of these parts may be required.

PRODUCT BENEFITS

- Reduces system leaks
- Revitalises worn seals and gaskets
- Extends component life
- Reduces squawk
- Increases the viscosity of the power steering fluid
- Can reduce costly repairs

PRODUCT PERFORMANCE LEVELS

TYPICAL DATA

Colour	Red
Density at 15°C, kg/L	0.888
Viscosity, Kinematic, cSt at 40°C	130
Viscosity, Kinematic, cSt at 100°C	15.0
Viscosity Index	118
Phosphorus, Mass %	0.032

