



PENRITE



85% REDUCTION IN LANDFILL WASTE

PRO 10 10W-30 (Semi Syn.)

Last updated: 04/08/2017 4:45 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
PRO10020	20L	
PRO10060	60L	
PRO10205	205L	

PRODUCT BENEFITS

Pro 10 is a premium grade, semi synthetic SAE 10W-30 engine oil developed for use in modern petrol engines exclusively in professional workshops and vehicle service centres. It uses a combination of the latest additive technology and a low shear rate viscosity modifier, to ensure additional protection against wear, corrosion, oil oxidation, piston deposits and sludge under tough conditions. **Pro 10** exceeds API SN Resource Conserving and ILSAC GF-5 fuel economy specifications. It also meets many other manufacturers' requirements.



ADDITIONAL PRODUCT INFORMATION

- [Click Here](#) to view Guide to Oils
- [Click Here](#) to view Hybrid Engine Oils Technical Bulletin

APPLICATION

Pro 10 is designed for use in modern 4, 6 & 8+ cylinder multi-cam, multi-valve (including VVT), naturally aspirated, supercharged & turbocharged engines.

Pro 10 is recommended where the manufacturer specifies a 10W-30 or 7.5W-30 engine oil.

Pro 10 is ideal for late model vehicles such as -

- Ford AU/BA/BF/FG Series
- Ford Territory SX/SY/SZ (Petrol)
- Holden VY/VZ/VE Series
- Toyota Aurion, Corolla & Camry
- Mitsubishi ASX, Lancer & Outlander
- Mazda 3 & 6 Series
- Nissan Dualis, Micra & Tida
- as well as many other manufacturers & vehicles.

Pro 10 is suitable for use with Petrol, E10 and E85. As an ILSAC GF-5 rated product, it is highly suited for use in vehicles that can run on ethanol based fuels such as E85. It is also suitable for use in petrol/electric hybrid powered vehicles such as Toyota, Lexus & Honda.

Note: Pro 10 is not designed for use in diesel engines or in Mazda Rotary Engines.

NOTE: when changing oil, Penrite recommend using [Penrite Engine Flush](#), a fast acting, solvent free, engine cleaning formulation that removes engine deposits, sludge and contaminants with the oil service drain. It contains added zinc for engine wear protection and its fast acting formulation works in 10 minutes.

PRODUCT BENEFITS

- **LATEST** SN oil specification
- **FUEL EFFICIENT** ILSAC GF-5 product
- **SAFE** for Catalytic converters and oxygen sensors
- **SUITABLE** for use in **Hybrid** petrol/electric vehicles
- **MINIMISES** sludge formation
- **MAXIMISES** wear protection
- **REDUCES** piston deposits

INDUSTRY & MANUFACTURER'S SPECIFICATIONS

- API SN Resource Conserving
- Ford M2C910-A
- ILSAC GF-3
- ILSAC GF-4
- ILSAC GF-5



PENRITE



**85% REDUCTION
IN LANDFILL
WASTE**

TYPICAL DATA

Colour	Amber
Density at 15°C, kg/L	0.87
Viscosity, Kinematic, cSt at 40°C	76
Viscosity, Kinematic, cSt at 100°C	11.3
Viscosity Index	140
Cold Cranking Viscosity, cP at -25°C	6664
Zinc, Mass %	0.085
Phosphorus, Mass %	0.077
Sulphated Ash, mass %	0.78
Base Number	8.3