



PENRITE

PRO 20

Premium Mineral 20W-50 Engine Oil

Issue: November 2015

Product Code	Pack Size	Ctn / Qty
PRO20020	20 Litre	1
PRO20060	60 Litre	1
PRO20205	205 Litre	1



Description

Pro 20 is a premium quality, SAE 20W-50 premium mineral engine oil developed for use in modern petrol, LPG and light duty diesel (Non DPF) engines exclusively by professional workshops and vehicle service centres. It uses a combination of the latest additive technology and a low shear rate viscosity modifier, to ensure additional protection against wear, corrosion, oil oxidation, piston deposits and sludge under tough conditions.

Application

Pro 20 is designed for use in 4, 6 & 8+ cylinder multi-cam, naturally aspirated, supercharged & turbocharged engines. It is ideal for use in most older and large capacity engines where this viscosity is recommended by the manufacturer.

Pro 20 is recommended where the manufacturer specifies a either SAE 20W-40 or 20W-50 viscosity engine oil. It can also be used where SAE 30 grade engine oil was originally recommended.

Pro 20 can also be used where ambient temperatures a very high or where oil consumption is becoming an issue where SAE 15W-40 was originally specified and in other older worn and larger capacity engines.

Pro 20 may be used with LPG and some diesel engine passenger cars, 4WDs and light commercials. It is not suitable for use in diesel vehicles fitted with a diesel particulate filter that require a low "SAPS" engine oil.

Product Benefits

- Can be used where SJ, SL, SG or SF oils were recommended
- Superior performance to older specification engine oils
- **FULL ZINC** anti-wear additive package for ultimate engine wear protection
- Reduces oil consumption and maintains oil pressure
- Catalytic converter compatible.
- Ideal for light duty diesel engines

Industry Specifications

API SM/CF

Typical Data

SAE Grade	20W-50
Density at 15°C, kg/L	0.876
Viscosity, Kinematic, cSt	
at 40°C	152
at 100°C	17.5
Viscosity Index	125
Viscosity, Cold Cranking @ -15 °C	5801
Zinc, mass %	0.108
Sulphated Ash, mass %	0.83
Base Number	7.6



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 748)
 Fax: 1800-PENRITE (1800 736 748)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**



United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com