



PENRITE

PRO 5 5W-30

Premium Full Synthetic Engine Oil

Issue: March 2017

PRODUCT CODE	PACK SIZE	CTN QTY
PRO5020	20 Litre	1
PRO5060	60 Litre	1
PRO5205	205 Litre	1
PRO51000LTR	1000 Litre	1



Description

Pro 5 is a premium grade, full synthetic SAE 5W-30 engine oil developed for use in modern petrol & diesel engines exclusively in professional workshops and vehicle service centres. It uses a combination of the latest additive technology and a low shear rate viscosity modifier, to ensure additional protection against wear, corrosion, oil oxidation, piston deposits and sludge under tough conditions.

Pro 5 exceeds **API SN/CF** specifications and **ACEA C3** for use in light duty diesel engines including those fitted with DPF's (Diesel Particulate Filters).

Application

Pro 5 is designed for use in modern 4, 6 & 8+ cylinder multi-cam, multi-valve (including VVT), naturally aspirated, supercharged & turbocharged engines.

Pro 5 can be used where the manufacturer specifies a SAE 5W-20, 5W-30 or 7.5W-30 viscosity engine oil. It may also be used where the fuel economy specifications ACEA A1/B1, A5/B5 and ILSAC GF-5 are specified and in vehicles requiring ACEA A3/B4 made before the 2010 model year, and where ACEA C2 or C3 is specified. It may be used where GMW 16177 and Ford M2C913-B/C is specified for out of warranty service.

Pro 5 can be used in petrol, LPG, hybrid & diesel engines. Its API SN petrol specification provides exceptional wear protection, minimisation of sludge formation and reduced piston deposits compared to lower grade oils. As an ACEA C3 oil it is Catalyst compatible with diesel catalysts and diesel particulate filters (DPF's) and can be used where the manufacturer specifies a low "SAPS" oil meeting this specification.

Product Benefits

- **LATEST** oil specification technology exceeding **API SN**
- Exceeds **ACEA C3** specifications
- Full Synthetic performance
- Suitable for use both Petrol & Diesel engines
- Suitable for **HYBRID** powered vehicles
- Safe for DPF and oxygen sensors
- Minimises sludge formation
- Maximises wear protection
- Reduces piston deposits

Industry Specifications

API SN/CF ACEA C3 BMW LL-04 MB 229.31 Fiat 9.55535.S3

Typical Data

Density at 15°C, kg/L	0.853
Viscosity, Kinematic, cSt	
at 40°C	70
at 100°C	12
Viscosity Index	163
Viscosity, Cold Cranking @ -30 °C	5,870
Zinc, mass %	0.088
Sulphated Ash, mass %	0.81
Base Number	7.7

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 748)
 Fax: 1800-PENRITE (1800 736 748)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**

