



PENRITE

# PRO GEAR 70W-75

## Full Synthetic Gear Oil

Issue: March 2017

PRODUCT CODE	PACK SIZE	CTN QTY
PROG7075001	1 Litre	6
PROG70750025	2.5 Litre	4
PROG7075020	20 Litre	-
PROG7075060	60 Litre	-
PROG7075205	205 Litre	-



### Description

**Pro Gear 70W-75** is a premium full synthetic, high performance oil manufactured from a blend of synthetic base oils including ester. It uses the latest technology, purpose designed additives for long service life and meets the performance requirements of API GL-4 Plus as well as many other manufacturer specifications.

### Application

**Pro Gear 70W-75** is primarily designed for 5 & 6 speed manual gearboxes and transaxles in passenger cars, 4WDs & light commercial vehicles such as -

BMW	Ford Falcon XR/FPV BA/BF/FG (T-56)	Holden VY/VZ/VE 6 Speed (T-56)
Jaguar S 2.7L D	Land Rover Discovery 3/Freelander 2	VW 6 speed manual gearboxes
ZF gearboxes S5-31, S5-39, S6-37 and S6-53		

**Pro Gear 70W-75** is ideal in manual gearboxes and transfer cases that require automatic transmission fluids, or in vehicles that are suffering from shift quality problems with higher viscosity fluids. It can also be used in dry clutch DSG gearboxes in VW vehicles that require VW G052 512 and in BMW vehicles requiring BMW MTF LT-3.

**Pro Gear 70W-75** may be used where the following part numbers are specified:

BMW 2300 1434404	BMW 2300 7533513	Ford 52171VX00	GM1052931
VW G052171	VW G052178	VW G052798	

### Product Benefits

- Smooth shift feel for the life of the oil drain
- Enhanced oxidation stability, reducing harmful deposits
- Improved load carrying capacity compared to automatic transmission fluids
- Contains synthetic base oils for longer life
- Will not harm brass or bronze
- Compatible with synchro materials
- Very fast flow at start up for slick gear shifts

### Industry Specifications

API GL-4 Plus	ZF TE-ML 11 (manual)	MTF BOT 338	Tremec (T-56)
---------------	----------------------	-------------	---------------

### Typical Data

Colour	Brown
Density at 15°C, kg/L	0.874
Viscosity, Kinematic, cSt	
at 40°C	38
at 100°C	7.5
Viscosity Index	177
Viscosity, Brookfield, cSt at -55°C	109,680
Zinc, mass %	0.131
KRL 20 Cycle, Visc @ 100°C cSt After shear (calc)	7.0
Pour Point, °C	-66

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



**PENRITE OIL COMPANY PTY LTD**, 88 Lewis Road, Wantirna South  
 Victoria AUSTRALIA 3152, ABN 25 005 001 525  
 Enquiries: Phone 1300-PENRITE (1300 736 748)  
 Fax: 1800-PENRITE (1800 736 748)  
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977  
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748  
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234  
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN  
 FAMILY OWNED  
 SINCE 1926**

