



PRO GEAR 75W-85

Full Synthetic Gear Oil

Issue: October 2016

| Product Code | Pack Size | Ctn / Qty |
|--------------|-----------|-----------|
| PROG7585001 | 1 Litre | 6 |
| PROG75850025 | 2.5 Litre | 4 |
| PROG7585020 | 20 Litre | 1 |
| PROG7585060 | 60 Litre | 1 |
| PROG7585205 | 205 Litre | 1 |



PENRITE

Description

Pro Gear 75W-85 is a premium full synthetic manual gearbox oil manufactured from a blend of carefully selected synthetic base oils. It uses the latest technology, purpose designed additives for long service life and excellent load carrying capacity. It contains a unique viscosity modifier for stay-in-grade performance for the life of the drain. It meets the performance requirements of API GL-4 Plus as well as many manufacturer requirements.

Application

Pro Gear 75W-85 is suitable for manual gearboxes, transfer cases and transaxles in passenger cars, 4WDs and trucks that specify the use of SAE 75W-85 oils. It may also be used in place of an SAE 80 or SAE 80W-85 gearbox oil, especially to improve cold shift problems, where the lower start up viscosity will provide an easier shift.

Pro Gear 75W-85 is also ideal in vehicles that are operating in highly loaded conditions such as in competition or when towing. It may also be used in manual gearboxes and transaxles that require a SAE 75W-80.

Pro Gear 75W-85 is recommended for use in Aisin 6 speed manual gearboxes used by Toyota and in Holden Commodore VE V6 and is also suitable for use in GM NV3500 and NV4500 manual gearboxes.

NOTE: Pro Gear 75W-85 is not suitable for use in differentials that require API GL-5 or higher. For these applications please use **Penrite GL-5 75W-85**

Product Benefits

- Smooth shift feel for the life of the oil drain
- Enhanced oxidation stability, reducing harmful deposits
- Will not harm brass or bronze
- Compatible with synchromesh materials
- Excellent wear protection
- Contains synthetic base oils for longer life

Industry Specifications

| | | | |
|---------------|-------------------|------------------|------------|
| API GL-4 Plus | ZF TE-ML 01/02/08 | MB 235.4/235.5 | BTR 5M-42 |
| MAN 341 | GM 12346190 | Chrysler MS 9224 | GM HN 2276 |
| GM HN 2013 | Opel 040 1067 | Opel 040 0063 | |

Typical Data

| | |
|-----------------------------------|---------|
| Colour | Amber |
| Density at 15°C, kg/L | 0.873 |
| Viscosity, Kinematic, cSt | |
| at 40°C | 77 |
| at 100°C | 12.0 |
| Viscosity Index | 152 |
| Viscosity, Brookfield, cP @ -40°C | 111,000 |
| Zinc, mass % | 0.139 |

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 748)
 Fax: 1800-PENRITE (1800 736 748)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**

