

RUBBER GREASE

Clay Based Grease

Issue Date: October 2015

Product Code	Pack Size	Ctn / Qty
RUBGR0001	100gm	6
RUBGR0005	500gm	6



Description

Penrite Rubber Grease is a premium quality, NLGI No. 2, general purpose, non- harmful clay based grease containing castor oil for use when contact with natural and/or synthetic rubber is likely to occur.

Application

Penrite Rubber Grease can be used for automotive, industrial and consumer rubber parts such as hydraulic dust covers, braking system components, seals and washers. It is specially designed for use on rubber components in hydraulic systems where compatibility with the rubber seals is essential. It is also suitable for use with other rubber components such as gaiters or boots used on these systems. It is also ideal for use as an automotive tyre mounting aid.

RUBBER GREA

500g

Penrite Rubber Grease is also recommended in other applications where the resistance to hydrocarbon solvents is required, such as automotive shock absorbers.

Penrite Rubber Grease can be used in the assembly of platen rollers used in the printing industry. This type of grease is used as a lubricant to aid the insertion of the steel mandrel into the very tight rubber outer.

NOTE: Penrite Rubber Grease is **NOT** recommended for the lubrication and protection of brake backing plates and plunger housings.

Recommended operating range is -9°C to 80°C.

Product Benefits

- Excellent lubricity
- Compatible with natural and synthetic rubbers
- Easy to use
- Long storage life
- Protects against rust and corrosion
- Resists hydrocarbon solvents (such as petrol)

Industry Specifications

NLGI 2

Typical Data

Soap Type	Clay
Base Oil Viscosity, ISO	320
Drop Point, °C	275
Colour	Red





Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

