



100 Celebrating
YEARS

AUSTRALIAN OWNED AND TRUSTED SINCE 1926 

RUBBER GREASE

Last updated: 21/11/2017 10:42 am

PRODUCT CODE	PACK SIZE	CARTON QTY
RUBGR0001	100g	6
RUBGR0005	500g	6

PRODUCT BENEFITS

Rubber Grease is a premium quality, NLGI No. 2, general purpose, non-harmful clay based grease containing castor oil for use when contact with natural and/or synthetic rubber is likely to occur.

APPLICATION

Rubber Grease can be used for automotive, industrial and consumer rubber parts such as hydraulic dust covers, braking system components, seals and washers. It is specially designed for use on rubber components in hydraulic systems where compatibility with the rubber seals is essential. It is also suitable for use with other rubber components such as gaiters or boots used on these systems. It is also ideal for use as an automotive tyre mounting aid.

Rubber Grease is also recommended in other applications where resistance to hydrocarbon solvents is required, such as automotive shock absorbers.

Rubber Grease can be used in the assembly of platen rollers used in the printing industry. This type of grease is used as a lubricant to aid the insertion of the steel mandrel into the very tight rubber outer.

NOTE: Penrite Rubber Grease is **NOT** recommended for the lubrication and protection of brake backing plates and plunger housings.

RECOMMENDED OPERATING RANGE

- -9° to 80°.

PRODUCT BENEFITS

- Excellent lubricity
- Compatible with natural and synthetic rubbers
- Easy to use
- Long storage life
- Protects against rust and corrosion
- Resists hydrocarbon solvents (such as petrol)

PRODUCT PERFORMANCE LEVELS

- NLGI 2

TYPICAL DATA

Colour	Red
NLGI Grade	2
Soap Type	Clay
Density at 15°C, kg/L	0.9
Base Oil Viscosity, ISO	320
Operating Temperature Range °C	-9° to +80°
Appearance	Smooth Texture
Drop Point, °C	275

